

ConocoPhillips

Wellsite Schematic
SAN JUAN 31-6 UNIT #301 SWD

API / UWI 3003924549		Surface Legal Location NMPM-30N-06W-06-B		Field Name SWD; MORR BLUFF ENTRA		License No.		Well Configuration Type Vertical	
Ground Elevation (ft) 6,322.00		Orig KB/RT (ft) 6,334.00		KB-Grd (ft) 12.00		KB-CF (ft)		KB-TF (ft)	
Other Elevation Type		Other Elevation (ft)							

Well Config Vertical - Original Hole, 5/22/2012 9:26 19 AM		WELLHEADS	
Type		Install Date	
Description		Make	Model
		WP (psi)	Top Ring Gasket
			Min Bore (in)

CASING STRINGS					
Casing Description	String OD (in)	String Wt (lbs/ft)	String Grade	String Top Thrd	Set Depth (ftKB)
Surface Casing	20	106.50	K-55		495.7
Intermediate1	13 3/8	61.00	K-55		3,599.6
Intermediate2	9 5/8	40.00	N-80		6,092.8
Production	7	23.00	N-80		9,039.0

PBTDS		
Depth (ftKB)	KO MD (ftKB)	TD (max) (ftKB)
9,008.0		9,039.0

PERFORATIONS			
Date	Top (ftKB)	Bot (ftKB)	Current Status
10/28/1989	8,056.0	8,318.0	MORRISON ENTRADA, Orig.
10/25/1989	8,461.0	8,608.0	MORRISON ENTRADA, Orig.
10/23/1989	8,768.0	8,986.0	MORRISON ENTRADA, Orig.

TUBING STRING				
Tubing Description	Run Date	Pull Date	String Length (ft)	Set Depth (ftKB)
Tubing-water Injection	12/1/2011		8,016.52	8,028.5
Comment				

Jts	Item Description	OD (in)	Nominal ID (in)	Wt (lbs/ft)	Grade	Make	Model	Len (ft)	Top (ftKB)
1	Pkr set in 30k lbs compression w/4.60' slack-off	3 1/2	2.992					-4.60	12.0
1	Tubing Joints (internally plastic coated - TK-99)	3 1/2	2.992	9.30	J-55	MAVE	T&C Upset	32.51	7.4
1	Tubing Pup Jt (internally plastic coated - TK-99)	3 1/2	2.992	9.30	J-55	BAKER OIL TOOLS	T&C Upset	10.20	39.9
244	Tubing Joints (internally plastic coated - TK-99)	3 1/2	2.992	9.30	J-55	MAVE	T&C Upset	7,928.67	50.1
1	3.50" X-Profile Nipple, 2.813" ID	3 1/2	2.813	9.30	L-80	BAKER OIL TOOLS	T&C Upset	1.06	7,978.8
1	Tubing Joint (internally plastic coated) - TK-99	3 1/2	2.992	9.30	L-80	MAVE	T&C Upset	32.54	7,979.8
1	Baker "Hornet" Retrievable Packer	6.276	2.992	9.30	L-80	BAKER OIL TOOLS	T&C Upset	7.97	8,012.4
1	3.50"-9.3#-J-55-8rd EUE Pup Jt	3 1/2	2.992	9.30	J-55	BAKER OIL TOOLS	T&C Upset	6.18	8,020.3
1	3.50" R-Profile Nipple 2.56" ID	3 1/2	2.560	9.30	L-80	BAKER OIL TOOLS	T&C Upset	1.48	8,026.5
1	Wireline re-entry guide	3 1/2	2.992	9.30	L-80	BAKER OIL TOOLS	T&C Upset	0.51	8,028.0

OTHER IN HOLE			
Run Date	Description	OD (in)	ID (in)
5/10/2001	Fill	6.3	
Top (ftKB)	Bottom (ftKB)	Make	Model
9,008.0	9,020.0		