Form 3160-5 (August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR

JUL 06 2112

FORM APPROVED OMB No 1004-0137

**BUREAU OF LAND MANAGEMENT** Expires, July 31, 2010 Farmington Field Office Serial No. Bureau of Land Managemen.
6. If Indian, Allottee or Tribe Name SF-078883 SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on page 2 7 If Unit of CA/Agreement, Name and/or No 1 Type of Well Canyon Largo Unit Oil Well X Gas Well Other 8 Well Name and No. Canyon Largo Unit 485E 9 API Well No 2 Name of Operator **Burlington Resources Oil & Gas Company LP** 30-039-31060 3a Address 3b Phone No (include area code) 10 Field and Pool or Exploratory Area PO Box 4289, Farmington, NM 87499 (505) 326-9700 Basin Mancos/Basin DK 4. Location of Well (Footage, Sec., T,R.,M, or Survey Description) 11 Country or Parish, State UNIT J (NWSE), 2515' FSL & 1890' FEL, Sec. 8, T25N, R6W Surface Rio Arriba **New Mexico** 12 CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Deepen Notice of Intent Acidize Production (Start/Resume) Water Shut-Off Alter Casing Fracture Treat Reclamation Well Integrity New Construction Other Casing Report X Subsequent Report Casing Repair Recomplete Change Plans Plug and Abandon Temporarily Abandon Plug Back Final Abandonment Notice Convert to Injection Water Disposal 13 Describe Proposed or Completed Operation Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones Attach the bond under which the work will be performed or provide the Bond No. on file with BLM/BIA Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once Testing has been completed Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection ) ACCEPTED FOR RECORD PLEASE SEE ATTACHED. AUG - 2 2012 PT will be conducted by Completion Rig. Results & TOC will appear on next report. FARMINGTON FIELD OFFICE RCVD AUG 6'12 OIL CONS. DIV. DIST. 3 14 I hereby certify that the foregoing is true and correct Name (Printed/Typed) DENISE JOURNEY Title REGULATORY TECHNICIAN 7/2/2012 ournes Signature Date THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by Title Conditions of approval, if any, are attached Approval of this notice does not warrant or certify

that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon

Office

Title 18 U S C Section 1001 and Title 43 U S C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

CANYON LARGO UNIT 485E 30-039-31060 Burlington Resources Basin Mancos/Basin DK

6/15/12 MIRU AWS 920.

6/16/12 PT 9 5/8" casing to 600#/30 min. Test OK <

**6/17/12** TIH w/ 8 ¾" bit, tag cmt @ 200' & DO. Drilled ahead w/ <u>8 ¾"</u> bit to <u>4,508'</u> – Inter. <u>TD reached 6/18/12</u>.

6/19/12 TIH w/ 108 jts., (86 jts., 20# ST&C & 22 jts., 23# LT&C), 7", J-55 casing, set @ 4,489'. RU to cmt. Pre-flush w/ 10 bbls FW, 10 bbls GW, & 10 bbls FW. Pumped scavenger, 19 sx (57cf-10bbls=3.02 yld) Prem. Lite cmt., w/ 0.3% CACL2, .25 pps celloflake, 0.4% FL-52, 5 pps LCM-1, 8% bentonite, & 0.4% SMS. Lead w/ 470 sx (1001cf-178bbls=2.13 yld) Prem. Lite cmt., w/ 0.3% CACL2, .25 pps cello-flake, 0.4% FL-52, 5 pps LCM-1, 8% bentonite, & 0.4% SMS. Tail w/ 105 sx (145cf-26bbls=1.38 yld) Type III cmt., w/ 1% CACL2, .25 pps cello-flake, & 0.2% FL-52. Drop plug & displaced w/ 176 bbls FW. Bump plug w/ 1398#. Plug down @ 16:34 hrs on 6/19/12. Circ. 60 bbls cement to surface. WOC. PT 7" casing to 1500#/30 min. @ 02:15 hrs on 6/19/12. Test OK. TIH w/ 6 1/4" bit, tag cement @ 4,447' & DO. Drilled ahead w/ 6 1/4" bit to 7,306'. 6/22/12 Please see NOI dated 6/22/12 for permission to deepen TD. Verbal approval received from Jim Lovato (BLM) & Charlie Perrin (NMOCD).
6/22/12 Drilled ahead w/ 6 1/4" bit to 7,355' (TD). TD reached 6/22/12.
6/23/12 Circ. hole. TIH w/ 171 jts., 4 1/2", 11.6#, L-80 casing, set @ 7,345'. RU to cmt. Pre-flush w/ 10 bbls FW, 10 bbls GW, & 10 bbls FW. Pumped scavenger 9 sx (27cf-

6/23/12 Circ. hole. TIH w/ 171 jts., 4 ½", 11.6#, L-80 casing, set @ 7,345'. RU to cmt. Pre-flush w/ 10 bbls FW, 10 bbls GW, & 10 bbls FW. Pumped scavenger 9 sx (27cf-5bbls=3.02 yld) Prem. Lite cmt., w/ 0.3% CD32, .25 pps cello-flake, 1% FL-52, & 6.25 pps LCM-1. Tail w/ 212 sx (42ocf-75bbls=1.98 yld) Prem. Lite cmt., w/ 0.3% CD-32, .25 pps cello-flake, 1% FL-52, & 6.25 pps LCM-1. Drop plug & displaced w/ 114 bbls FW (1<sup>st</sup> 10 bbls w/ sugar water). Bump plug w/ 1747#. Plug down @ 19:02 hrs on 6/23/12. WOC.

**6/24/12** ND WH. NU BOPE. RD RR @ 12:00 hrs on 6/24/12.