

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No 1004-0137
Expires July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5 Lease Serial No
NM NM 86080

6 If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1 Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2 Name of Operator
Encana Oil & Gas (USA) Inc.

3a Address
370 17th Street, Suite 1700
Denver, CO 80202

3b Phone No (include area code)
720-876-3437

7 If Unit of CA/Agreement, Name and/or No

8 Well Name and No.
Bisti H09-2510 01H

9 API Well No.
30-045-35341

10. Field and Pool or Exploratory Area
Gallegos - Gallup

4 Location of Well (Footage, Sec., T, R, M., or Survey Description)
SHL: 2183' FNL and 475' FEL Section 9, T25N, R10W
BHL: 2181' FNL and 343' FWL Section 9, T25N, R10W

11 Country or Parish, State
San Juan, New Mexico

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report <i>BP</i>	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other _____
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input checked="" type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13 Describe Proposed or Completed Operation Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection)

Plugged the motherbore between 06/16/12 and 06/18/12. Please see attached Motherbore Plug Back Procedure.

RCVD JUL 26 '12
OIL CONS. DIV.
DIST. 3

14 I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Amanda Cavoto

Title Engineering Technician

Signature

Amanda Cavoto

Date 07/05/12

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

ACCEPTED FOR RECORD

Approved by

Title

Date

JUL 19 2012

Conditions of approval, if any, are attached Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon

Office

FARMINGTON FIELD OFFICE
BY *[Signature]*

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

(Instructions on page 2)

NMCCD

Bisti H09-2510 01H
API 30-045-35341
Motherbore Plug Back Procedure

TOPS:	TVD
KOP	5100'
Graneros Shale	6310'
Dakota	6352'

Set 2 cement plugs in 8 ½" hole

Plug A: Bottom plug 100' above Graneros Shale

Plug B: Kick plug at KOP

Plug A (operations occurred 6/16/12)

1. TIH to TD of vertical pilot hole at 6709'
2. Spot 551' cement plug from 6158' - 6709'
 - a. 170sx of Type III cement with .1% CaCl₂ + 0.25#/sk celloflake + 0.2% FL-52A (1.38ft³/sk yield, 14.6 ppg)
 - b. Pump displacement and 10 bbl spacer
3. Pull uphole 250' and reverse out
4. Pull uphole and reverse out
5. Pump bottoms up 2 times, pull uphole
6. TIH and tag plug, proceed when cement is solid
7. Fill hole and move uphole to set bridge plug and spot kick plug

Plug B (operations occurred 6/18/12)

1. TIH and set open hole bridge plug at 5300'
2. Spot 356' kick plug from 4944' - 5300'
 - a. 129sx of Type III cement (1.52ft³/sk yield, 15.7 ppg)
 - b. Spot tuned spacer
3. Pull uphole and reverse out
4. Pump bottoms up 2 times, pull uphole
5. Tag plug at 4944', set 18,000 pounds, drill ahead to KOP