

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

AUG 13 2012

FORM APPROVED
OMB No 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on page 2

1 Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2 Name of Operator

Burlington Resources Oil & Gas Company LP

3a Address

PO Box 4289, Farmington, NM 87499

3b Phone No (include area code)

(505) 326-9700

4 Location of Well (Footage, Sec., T, R, M., or Survey Description)

Surface Unit N (SESW), 1175' FSL & 1805' FWL, Sec. 22, T30N, R13W

5 Lease Serial No

SF-078214

6 If Indian, Allottee or Tribe Name

7 If Unit of CA/Agreement, Name and/or No

8 Well Name and No

McCord 104S

9 API Well No

30-045-34289

10 Field and Pool or Exploratory Area

Basin Fruitland Coal

11. Country or Parish, State

San Juan, New Mexico

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☒ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☐ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☐ Well Integrity

☐ Other

13. Describe Proposed or Completed Operation Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof.

If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the bond under which the work will be performed or provide the Bond No on file with BLM/BIA Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once Testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection)

Burlington Resources requests permission to P&A the subject well per the attached procedure, current and proposed wellbore schematics.

**Notify NMOCD 24 hrs
prior to beginning
operations**

**RCVD AUG 17 '12
OIL CONS. DIV.**

DIST. 3

*** Place an inside plug across PC top from 1778' - 1700'**

14 I hereby certify that the foregoing is true and correct Name (Printed/Typed)

Dollie L. Busse

Title **Staff Regulatory Technician**

Signature

Dollie L. Busse

Date

8/10/12

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Original Signed: Stephen Mason

Title

Date

AUG 15 2012

Conditions of approval, if any, are attached Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U S C Section 1001 and Title 43 U S C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

(Instruction on page 2)

NMOCD

ConocoPhillips
MCCORD 104S
Expense - P&A

Lat 36° 47' 41.118" N

Long 108° 11' 41.543" W

PROCEDURE

This project requires a NMOCD C-144 CLEZ Closed-Loop System Permit for the use of an A-Plus steel tank to handle waste fluids circulated from the well and cement wash up.

1. Hold pre-job safety meeting. Comply with all NMOCD, BLM, and COPC safety and environmental regulations. Test rig anchors prior to moving in rig.
2. MIRU work over rig. Check casing, tubing, and bradenhead pressures and record them in Wellview.
3. When an existing primary valve (i.e. casing valve) is to be used, the existing piping should be removed and replaced with the appropriate piping for the intended operation.
4. RU blow lines from casing valves and begin blowing down casing pressure. Unseat pump and kill well with water, as necessary, and at least pump tubing capacity of water down tubing.
5. TOOH with rods (per pertinent data sheet) and LD.
6. ND wellhead and NU BOPE. Pressure and function test BOP. PU and remove tubing hanger.
7. TOOH with tubing (per pertinent data sheet).

Rods:	Yes	Size:	3/4"	Set Depth:	1756'
Tubing:	Yes	Size:	2-3/8"	Set Depth:	1775'

Round trip 4 1/2", 10.5#, J-55 casing scraper to top perforation @ 1594' or as deep as possible.

All cement volumes use 100% excess outside pipe and 50' excess inside pipe. The stabilizing wellbore fluid will be 8.3 ppg, sufficient to balance all exposed formation pressures. All cement will be ASTM Type II mixed at 15.6 ppg with a 1.18 cf/sk yield.

8. Plug 1 (Fruitland Coal perforations and formation top, 1023-1544', 44 Sacks Class B Cement)

PU 4-1/2" CR and set at 1544'. Load casing and circulate well clean. Pressure test tubing to 1000 psi, and casing to 800 psi. If casing does not test, then spot or tag subsequent plugs as appropriate. Mix 44 sxs Class B cement and spot a plug inside casing above CR to isolate the Fruitland Coal perforations and formation top. PUH.

9. Plug 2 (Kirtland, Ojo Alamo and Surface Plug, 0-423', 36 Sacks Class B Cement)

Connect the pump line to the bradenhead valve and attempt to pressure test the BH annulus to 300 PSI; note the volume to load. If the BH annulus holds pressure, then establish circulation out casing valve with water. Mix 36 sx Class B cement and spot a balanced cement plug inside casing from 423' to surface. Circulate good cement out casing valve. TOH and LD tubing.

Shut in well and WOC. If the BH annulus does not test, then perforate at the appropriate depth and attempt to circulate cement to surface filling the 4 1/2 casing and the BH annulus to surface. Shut well in and WOC.

10. Nipple down BOP and cut off casing below the casing flange. Install P&A marker with cement to comply with regulations. Rig down, move off location, cut off anchors, and restore location.


Current Schematic

ConocoPhillips

Well Name: MCCORD #104S

API/UVI 3004534289	State Legal Location 022-030N-013W-N	Field Name BASIN FRUITLAND COAL	License No.	State/Province NEW MEXICO	Well Configuration Type VERTICAL	Edit
Ground Elevation (ft) 5,741.00	Original KB/RT Elevation (ft) 5,752.00	KB-Ground Distance (ft) 11' 00"	KB-Casing Flange Distance (ft)	KB-Tubing Hanger Distance (ft)		

Well Config: VERTICAL - Original Hole, 8/8/2012 1:07:08 PM



Proposed Schematic

ConocoPhillips

Well Name: MCCORD #104S

API/UVI 3004534289	Surface Legal Location 022-030N-013W-N	Field Name BASIN FRUITLAND COAL	License No	State/Province NEW MEXICO	Well Configuration Type VERTICAL	Edr
Ground Elevation (ft) 5,741.00	Original BPT Elevation (ft) 5,752.00	HS-Graded Distance (ft) 11.00	HS-Casing Flange Distance (ft)	HS-Tubing Hanger Distance (ft)		

Well Config VERTICAL - Original Hole, 1/1/2020

