Record Clean Up

RECEIVED

UNITED STATES Form 3160-5 FORM APPROVED DEPARTMENT OF THE INTERIOR JUL 31 2012 (August 2007) OMB No 1004-0137 **BUREAU OF LAND MANAGEMENT** Expires July 31,2010 Farmington Field Of S-Lease Serial No SUNDRY NOTICES AND REPORTS ON WELL Sand Managemeintract 459 Do not use this form for proposals to drill or to re-enter an If Indian, Allottee, or Tribe Name abandoned well. Use Form 3160-3 (APD) for such proposals. Jicarilla Apache Tribe If Unit or CA Agreement Name and/or No SUBMIT IN TRIPLICATE - Other Instructions on page 2. Type of Well Oil Well Well Name and No ✓ Gas Well Jicarilla 459-17 #11 Name of Operator Black Hills Gas Resources, Inc. API Well No 30-039-25906 3b Phone No (include area code) 3200 N 1st St, Bloomfield, NM 87413 (505) 634-5104 10 Field and Pool, or Exploratory Area Location of Well (Footage, Sec., T., R., M., or Survey Description) East Blanco Pictured Cliffs 1,188' FSL & 1,603' FEL, Sec. 17, T30N R3W (UL: O) 11 County or Parish, State 2223' FSL & 1207' FWL, Sec. 17, T30N R3W (UL: L) Rio Arriba County, New Mexico 12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Acidize Deeper Production (Start/Resume) Water Shut-off Well Integrity Altering Casing Fracture Treat CMT SQZ, Subsequent Report Casing Repair New Construction Recomplete Other Horiz Re-entry, Change Plans Plug and abandon Temporarily Abandon Final Abandonment Notice Water Disposal Run Prod. Tbg Convert to Injection Plug back 13 Describe Proposed or Completed Operation Clearly state all pertinent details including estimated starting date of any proposed work and approximate duration thereof If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones Attach the Bond under which the work will performed or provide the Bond No on file with the BLM/ BIA Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notice shall be filed only after all requirements, including reclamantion, have been completed, and the operator has determined that the site is ready for final inspection) Black Hills Gas Resources is filing the following subsequent sundry to provide details of recompletion done in 2004. This is a continuation of the permit clean-up program done in 2007. Black Hills Gas Resources performed the following work: (See attachment) RCVD AUG 2'12 OIL CONS. DIV. DIST. 3 14 I hereby certify that the foregoing is true and correct Name (Printed/ Typed) **Daniel Manus** Regulatory Techician Signatur THIS SPACE FOR FEDERAL OR STATE OFFICE USE

entitle the applicant to conduct operations thereon

Title 18 U S C Section 1001 AND Title 43 U S C Section 1212, make it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Title

Office

(Instructions on page 2)

Conditions of approval, if any are attached Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would

Approved by

SHGTON FIELD OFFICE



Jicarilla 459-17 #11

Surface Location: 1,188' FSL 1,603' FEL (SW/SE) Bottom Hole Location: 2,542' FSL 89' FWL (NW/SW) Sec. 17 T30N R3W, Rio Arriba County, New Mexico

Lease: Contract 459

8/25/04 - MIRU SU. POH with 2 3/8" prod tbg. Make scraper trip.. Set cmt retainer at 3274'.

8/26/04 - Cement squeeze Ojo Alamo perfs 3304-3354' 100 sx class B cement + .075 gps CFL-7L, 15.6 ppg, 1.18 yield, 118 cuft. FSP 1100 psi. TOH. TIH with pkr. Set at 1530'. Cement squeeze San Jose perfs 1668-1805' with 75 sx class B cement + .075 gps CFL-7L, 15.6 ppg, 1.18 yield, 88.5 cuft. FSP 2000 psi. TOH.

8/27/04 - Drill out SJ sqz. Pressure test to 500 psi, ok.

8/28/04 – Drill out cmt ret & OA sqz. Pressure test to 500 psi, ok. Clean out to 3910'.

8/29/04 - Release SU.

9/3/04 - MIRU drilling rig. TOH with 2 3/8" tbg.

9/4/04 - PU drill string. Cut window in 5 ½" casing from 3826' to 3839'. Orient whipstock.

9/5/04- 9/12/04 - Drill 4 3/4" PC lateral to 6558' MD. Reach TD 9/11/04. Release drlg rig.

9/17/04 - MIRU SU.

9/21/04 - TIH with 2 3/8", 4.7#, J-55 prod tbg and SN and land tbg at 4062' MD.

9/22/04 - Flow back well.

9/24/04 - Release SU.