Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

RECEIVED

FORM APPROVED OMB NO. 1004-0137 Expires July 31, 2010

ALIC 13 2012 5. Lease Serial No.

	SUNDRY NOTICES AND REPORTS ON WELLS					
Do not use this form for	proposals to drill o	r to re-enter anarmin		carilla Con If Indian, Allottee		
Do not use this form for proposals to drill or to re-enter ਕੁਸੈਕrmington Field Of abandoned well. Use Form 3160-3 (APD) for such propesalsau of Land Manag				emen. Jicarilla Apacho Tribo		
SUBMIT IN TRIPLICATE - Other instructions on page 2				7. If Unit or CA/Agreement, Name and/or No.		
SUBMIT IN TRIFLICATE - Other Instructions on page 2				om- or or or or	To them, Name and/or No.	
1. Type of Well				***************************************		
Oil Well X Gas Well Other				Well Name and N carilla 155		
2. Name of Operator			01		41 CM	
Enervest Operating, LLC		9. API Well No.				
3a. Address	•			039-29995		
1001 Farnin St. Ste 800 Houst 4. Location of Well (Footage, Sec., T., R., M., or Survey	713-495-1563	10	10. Field and Pool, or Exploratory Area			
4. Location of Well (Poolage, Sec., 1., K., M., or Survey	Description)			BINCO MV/B	•	
760' FNL & 2570' FWL			11	11. County or Parish, State		
Sec. 10 T26N R05W (ULC)		1	71 - 3			
36 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REP					NM_	
36 12. CHECK APPROPRIAT	E BOX(ES) TO IND	ICATE NATURE OF N	OTICE, REPORT,	OROTHERD	ATA	
TYPE OF SUBMISSION		TY	TYPE OF ACTION			
Notice of Intent	Acidize	Deepen	Production (Sta	art/Resume)	Water Shut-Off	
	Alter Casing	Fracture Treat	Reclamation	ion Well Integrity		
Subsequent Report						
	Casing Repair	New Construction	Recomplete	.	Other	
Final Abandonment Notice	Change Plans	Plug and Abandon	Plug and Abandon Temporarily Abandon Surf Csq to		rf Csq to TD	
Br	Convert to Injection	n Plug Back	Water Disposal		_	
Attach the Bond under which the work will be perfollowing completion of the involved operations. testing has been completed. Final Abandonment determined that the final site is ready for final insp. Spud thru Surf Csg reported on St. 07-24-12 Notified BIM, Jicaril 07-25-12 Test surf csg to 1000 07-26-12 Notified BIM, Jicaril Drill 8 3/4" hole from 07-27-12 Drill 8 3/4" hole from 0.75 degrees; WIS @ 307-28-12 Circ and WIS @ 3226' 07-29-12 Rum 7" 23# J-55 ITSC 07-30-12 Finish running csg; Complete Compl	If the operation results in Notices shall be filed only ection.) Indry dated 06/27 La BIM, and NMOCO psi for 30 min. La BIM, and NMOCO m 515' to 1500'; 3265'; WLS @ 155 1075' 0.75 degrees 0.75 degrees; RU csg; set @ 3265'	a multiple completion or rey after all requirements, income and the property of the property o	E Csg tests. Ey reps on local and cmt jobs; gree. ILS @ 2060' 0.	nterval, a Form a have been comple RCUD (OIL (ation for to [75 degrees;	olfo-4 shall be filed once sted, and the operator has all of 22'12 cons. DIU. Solution of the operator has all once the operator has all of the operator has all ope	
45.54 cu.ft. (33 sxs between stages; cmt 2 69 cu.ft. (50 sxs Typ test pipe rams 250 ps	and stage w/lead the III cmt, 1.38 ti low, 2000 psi	457.95 cu.ft. (215 yield); circ <u>22 b</u>	sxs Premium :	Lite, 2.13 o o surf; WOC	yield); tail ; Pressure	
BIM on loc for tests. Cont'd on page 2						
14. I hereby certify that the foregoing is true and correct		1				
Name (Printed/Typed)		Title Ass		S		
7.55						
Signature Sunday		Date 08/09/20	12	Α		
THIS	S SPACE FOR FEDE	ERAL OR STATE OF	ICE USE		CANCELLE ACTUE NOW	
Approved by		Title		Date	AU6 7 (1 2012	

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would

entitle the applicant to conduct operations thereon.

Office

Jicarilla 155 # 16M API 30-039-29995

Continuation of Sundry page 2 of 2

- 7-31-12 Drill 6 1/4" hole to 4000'; Circ & WLS @ 3570' 0.5 degrees; WLS @3884' @ 2.5 degrees.
- 8-01-12 Drill 6 1/4" hole to 4260'; WLS @ 4066' 3.43 degrees; WLS @ 4159' 0.81 degrees.
- 8-02-12 Drill 6 1/4" hole to 5880'; WLS @ 4373' 0.38 degrees; WLS @ 4557' 0.26 degrees; WLS @ 4742' 0.84 degrees; WLS @ 5233' 0.93 degrees; WLS @ 5702' 0.96 degrees.
- 8-03-12 Drill 6 1/4" hole to 6780'; WLS @ 6198' 1.15 degrees; WLS @ 6664' 0.97 degrees.
- 8-04-12 Drill 6 1/4" hole to 7304'; WLS @ 6818' 0.90 degrees; WLS @ 7223' 0.96 degrees.
- 8-05-12 Notified BLM, Jicarilla BLM, and NMOCD of impending csg and cmt job; Drill <u>6 1/4"</u> hole to 7538'; TD; WLS W 7483' 0.85 degrees; circ for logs.
- 8-06-12 Circ and condition hole for csg; ; run 4 1/2" 11.6# N-80 LT&C csg; set @ 7538'.
- 8-07-12 cont'd csg job; circ and thin mud back; cmt lead w/187.44 cu.ft. (88 sxs Premium Lite, 2.13 yield)' tail w/441.78 cu.ft. (222 sxs Type III cmt, 1.99 yield).

TOC & csg pressure to be reported on first day of completion work;

Fig Release date?