District I

1625 N French Dr., Hobbs, NM 88240

1301 W. Grand Ave., Artesia, NM 88210

District III

State of New Mexico Energy Minerals and Natural Resources

Department Oil Conservation Division 1220 South St. Francis Dr.

Santa Fe NM 87505

Form C-144 July 21, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

1000 Rio Brazos Rd , Aztec, NM 87410	Santa Fe, NM 87505	For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the
District IV 1220 S St Francis Dr., Santa Fe, NM 87505		appropriate NMOCD District Office
Pit, C	Closed-Loop System, Below-Gra	de Tank, or
Proposed A	Alternative Method Permit or Clo	osure Plan Application
Type of action: Peri	mit of a pit, closed-loop system, below-grade	e tank, or proposed alternative method
J X Clo	sure of a pit, closed-loop system, below-grad	le tank, or proposed alternative method
Mo	diffication to an existing permit	
	sure plan only submitted for an existing permow-grade tank, or proposed alternative metho	nitted or non-permitted pit, closed-loop system,
		oop system, below-grade tank or alternative request
	st does not relieve the operator of liability should operations	
environment Nor does approval relieve the oper	rator of its responsibility to comply with any other applicable	e governmental authority's rules, regulations or ordinances
1 Operator: Burlington Resources Oil & Gas	Company, LP	OGRID#: 14538
Address: PO Box 4289, Farmington, NM		
Facility or well name: KESSLER COM 3P		
API Number: 30-045-35	OCD Permit Num	ber:
U/L or Qtr/Qtr: P(SE/SE) Section: 2	25 Township: 30N Range:	11W County: SAN JUAN
Center of Proposed Design. Latitude:	36.7792131 °N Longitude:	107.938085 °W NAD: ☐ 1927 X 1983
Surface Owner: X Federal	State Private Tribal Trust or Indi	ian Allotment
2 X Pit: Subsection F or G of 19.15.17.11 NMA	AC	RCVD NOV 14'12
Temporary: Drilling Workover		OIL CONS. DIV.
Permanent Emergency X Cavitation	P&A (Pre-set)	DIST. 3
Lined Unlined Liner type	Thickness mil LLDPE	HDPE PVC Other
String-Reinforced		
Liner Seams Welded Factory	Other Volume:	bbl Dimensions Lx Wx D
3		
	19.15 17.11 NMAC	
Type of Operation. P&A Drilling	g a new well Workover or Drilling (Applies notice of intent)	to activities which require prior approval of a permit or
Drying Pad Above Ground Steel		
Lined Unlined Liner type:		HDPE PVD Other
Liner Seams. Welded Factory	Other	
4		
Below-grade tank: Subsection I of 19.15	.17.11 NMAC	
Volumebbl	Type of fluid:	
Tank Construction material		
Secondary containment with leak detection	Visible sidewalls, liner, 6-inch lift and au	utomatic overflow shut-off
Visible sidewalls and liner Vi	sible sidewalls onlyOther	
Liner Type: Thicknessmil	HDPE PVC Other	
5 Alternative Method:		
Submittal of an exception request is required. Ex	exceptions must be submitted to the Santa Fe Envir	conmental Bureau office for consideration of approval.

Form C-144

Oil Conservation Division

Page 1 of 5

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify			
Netting: Subsection E of 19 15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)		**************************************	
Signs: Subsection C of 19 15 17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC			
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: X Administrative approval(s). Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration pit for Pre-set) Exception(s) Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval	deration of app	roval.	
Siting Criteria (regarding permitting) 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.			
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells	Yes	No	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	No	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	No	
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)	□NA		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image			
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits)	Yes NA	∐No	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	_		
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	No	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality, Written approval obtained from the municipality	Yes	No	
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	No	
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	No	
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	Yes	No	
Society; Topographic map Within a 100-year floodplain - FEMA map	Yes	No	

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment ChecklistSubsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of
19 15 17 9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API or Permit
12
Closed-loop Systems Permit Application Attachment Checklist:Subsection B of 19.15.17.9 NMAC Instructions Each of the following items must be attached to the application Please indicate, by a check mark in the box, that the documents are attached.
Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19 15.17 11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9
NMAC and 19.15 17 13 NMAC
Previously Approved Design (attach copy of design) API
Previously Approved Operating and Maintenance Plan API
13
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC
String Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC
Dike Protection and Structural Integrity Design based upon the appropriate requirements of 19.15.17.11 NMAC
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC
Quality Control/Quality Assurance Construction and Installation Plan
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Nuisance or Hazardous Odors, including H2S, Prevention Plan
☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization
Monitoring and Inspection Plan
Erosion Control Plan
Closure Plan - based upon the appropriate requirements of Subsection C of 19 15.17.9 NMAC and 19.15.17.13 NMAC
14
Proposed Closure: 19.15 17 13 NMAC
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type: Drilling Workover Emergency X Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative
Proposed Closure Method: Waste Excavation and Removal
Waste Removal (Closed-loop systems only)
On-site Closure Method (only for temporary pits and closed-loop systems)
In-place Burial On-site Trench
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
15
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.
Please indicate, by a check mark in the box, that the documents are attached.
Protocols and Procedures - based upon the appropriate requirements of 19 15.17 13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15.17 13 NMAC
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17 13 NMAC

Form C-144 Oil Conservation Division

Page 3 of 5

16				
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground S Instructions Please identify the facility or facilities for the disposal of liquids, drilling	teel Tanks or Haul-off Bins Only: (19 15.17 13 D NMAC)			
facilities are required	ng jiulas and arui Cultings. Ose allachment ij more than two			
Disposal Facility Name Envirotech / JFJ Landfarm % IEI	Disposal Facility Permit #: NM-01-0011 / NM-01-0	010B		
Disposal Facility Name Basin Disposal Facility	Disposal Facility Permit #: NM-01-005			
Will any of the proposed closed-loop system operations and associated acti		service and		
Required for impacted areas which will not be used for future service and operation		w.c		
Soil Backfill and Cover Design Specification - based upon the appro Re-vegetation Plan - based upon the appropriate requirements of Subs	-	MAC		
Site Reclamation Plan - based upon the appropriate requirements of S	ubsection G of 19 15 17 13 NMAC			
Siting Criteria (Regarding on-site closure methods only: 19 15 17.10 NM/ Instructions Each siting criteria requires a demonstration of compliance in the closure plan certain siting criteria may require administrative approval from the appropriate district office office for consideration of approval Justifications and/or demonstrations of equivalency are re-	Recommendations of acceptable source material are provided below or may be considered an exception which must be submitted to the Si	anta Fe Environmental Bureau		
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search, USGS Data of	btained from nearby wells	∐Yes ∐No □N/A		
· ·	·			
Ground water is between 50 and 100 feet below the bottom of the buried w - NM Office of the State Engineer - tWATERS database search, USGS, Data of		∐Yes ∐No ∏N/A		
		Yes No		
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search, USGS; Data of	btained from nearby wells	□N/A		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other sign	uficant watercourse or lakebed, sinkhole, or playa lake	Yes No		
(measured from the ordinary high-water mark). - Topographic map, Visual inspection (certification) of the proposed site				
Within 300 feet from a permanent residence, school, hospital, institution, or church	in existence at the time of initial application	Yes No		
- Visual inspection (certification) of the proposed site, Aerial photo, satellite image				
		Yes No		
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application. - NM Office of the State Engineer - iWATERS database, Visual inspection (certification) of the proposed site				
Within incorporated municipal boundaries or within a defined municipal fresh water variation to NMSA 1978, Section 3-27-3, as amended		Yes No		
- Written confirmation or verification from the municipality, Written approval	obtained from the municipality			
Within 500 feet of a wetland - US Fish and Wildlife Wetland Identification map, Topographic map, Visual ii	nspection (certification) of the proposed site	L_Yes L_No		
Within the area overlying a subsurface mine.	ispection (certification) of the proposed site			
- Written confirantion or verification or map from the NM EMNRD-Mining and	d Mineral Division	Yes No		
Within an unstable area		☐Yes ☐No		
- Engineering measures incorporated into the design. NM Bureau of Geology &	Mineral Resources; USGS, NM Geological Society.			
Topographic map Within a 100-year floodplain		Yes No		
- FEMA map				
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Ea	ch of the following items must bee attached to the clo	sure plan. Please indicate,		
by a check mark in the box, that the documents are attached.	wints magninoments of 10 15 17 10 NR 4 C			
Siting Criteria Compliance Demonstrations - based upon the approp	,			
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC				
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC				
X Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC				
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15 17.13 NMAC				
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC				
Ste Reclamation Plan - based upon the appropriate requirements of				

Form C-144 Oil Conservation Division Page 4 of 5

19 Operator Application Certification:
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief
Name (Print): Title:
Signature: Date:
e-mail address: Telephone:
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 1/0/2012 Title: Ompliance OCD Permit Number:
Closure Report (required within 60 days of closure completion): Subsection K of 1915 17 13 NMAC Instructions Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed Closure Completion Date: 8/31/2012
22
Closure Method: Waste Excavation and Removal On-site Closure Method X Alternative Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain.
23 Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.
Disposal Facility Name Disposal Facility Permit Number:
Disposal Facility Name. Disposal Facility Permit Number:
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations? Yes (If yes, please demonstrate compliance to the items below)
Required for impacted areas which will not be used for future service and operations: Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (if applicable) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude: Longitude- NAD 1927 1983
25
Operator Closure Certification:
I hereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.
Name (Print): Jamie Goodwin Title: Regulatory Technician
Signature: James (300dww Date: 1111717
e-mail address: Jamie l.goodwin@conocophillips.com Telephone: 505-326-9784

Burlington Resources Oil & Gas Company, LP Cavitation Pit for Closed-Loop Locations

Design:

Burlington Resources Oil & Gas Company, LP will use a cavitation pit plan when the surface casing will be pre-set on closed-loop locations. The drill cuttings will be stockpiled on the surface.

Operations and Maintenance:

The cavitation pit will be operated and maintained as follows:

- 1. Only Fresh water and air will be used in the drilling of the surface casing.
- 2. The Cement used will be: Neat Cement with no additives.
- 3. All of the fluids will be removed within 48hrs after drilling.
- 4. A representative five point composite sample will be taken of the drill cuttings, after the setting of the surface casing is complete, using sampling tools and all samples will be tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the testing criteria is not met, all contents will be dug and hauled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

5. The NMOCD will be notified via email of the test results of the cavitation surface as follows:

Components	Tests Method	Limit (mg/Kg)	Results
Benzene	EPA SW-846 8021B or 8260B	0.2	ND
BTEX	EPA SW-846 8021B or 8260B	50	ND
TPH	EPA SW-846 418.1	2500	14.5
GRO/DRO	EPA SW-846 8015M	500	ND
Chlorides	EPA 300.1	500	16.7

Closure Plan:

- 1. The NMOCD will be notified of the sample results and the intent to start the closure process 3-7 days prior to the drill cuttings being transported, moved, or distributed on location.
- 2. In the event the criteria are not met, all solids and liquids will be removed and disposed of at Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B).
- 3. Testing results will be submitted with the Closure Report of the well locations Closed-Loop Permit on Form C-144.

Burlington Resources is aware that approval of this plan does not relieve Burlington Resources of liability should operations result in pollution of surface water, ground water, or the environment. Nor does approval relieve ConocoPhillips of its responsibility to comply with any other applicable governmental authority's rules and regulations.

The Keesler Com 3P was approved for a Closed Loop permit # 10271 on 7/19/2012. Due to COPC change in plans to Air Pre Set. Pre Set application permit # 10349 was submitted and approved on 8/28/2012. According to Cavitation Pit for a Closed Loop Locations Closure Plan #1 – (The NMOCD will be notified of the sample results and the intent to start the closure process 3-7 days prior to the drill cutting being transported, moved or distributed on location). COPC is notifying the NMOCD after the fact. Pre Set was conducted on 8/31/2012 and Environmental Samples are attached to this closure report. In the future COPC will comply with closure procedure #1 via: e-mail of move on date, environmental test samples and will be followed by the Pre Set closure report.

Thank you,

Jamie Goodwin ConocoPhillips Regulatory Tech.



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	ConocoPhillips	Project #:	96052-1706
Sample ID:	Pre-Set Cuttings	Date Reported:	09-04-12
Laboratory Number:	63132	Date Sampled:	08-31-12
Chain of Custody No:	6292	Date Received:	09-04-12
Sample Matrix:	Soil	Date Extracted:	09-04-12
Preservative:	Cool	Date Analyzed:	09-04-12
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. ∼" Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Kessler Com 3P / Mote 212



EPA Method 8015 Modified Nonhalogenated Volatile Organics **Total Petroleum Hydrocarbons**

Quality Assurance Report

Client:

QA/QC 0904TCAL QA/QC Project #:

N/A

Sample ID:

Date Reported:

09-04-12

Laboratory Number:

63053

Date Sampled:

N/A N/A

Sample Matrix: Preservative:

Methylene Chloride N/A

Date Received: Date Analyzed:

09-04-12

Condition:

N/A

Analysis Requested:

C-Cal RF:

TPH

Gasoline Range C5 - C10

I-Cal Date 09-04-12

9.9960E+02

1.0000E+03 0.04% 0 - 15%

Difference Accept. Range

Diesel Range C10 - C28

09-04-12

9.9960E+02

I-Cal RF

1.0000E+03

0.04%

Detection Limit

0 - 15%

Blank Conc. (mg/L - mg/Kg

Concentration ND

0.2

Gasoline Range C5 - C10 Diesel Range C10 - C28

ND

0.1

Total Petroleum Hydrocarbons

ND

Duplicate Conc. (mg/Kg) Sample Gasoline Range C5 - C10

312

Sample

Duplicate 315

576

0.8%

% Difference: Accept: Range 0 - 30%

Diesel Range C10 - C28

553

Spike Added Spike Result

4.2%

0 - 30%

Spike Conc. (mg/Kg) Gasoline Range C5 - C10 Diesel Range C10 - C28

312 250 553 250 467 799

83.1% 99.4%

Recovery

75 - 125% 75 - 125%

Accept. Range

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Was

SW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 63053-63056, 63123-63124, 63132.

envirotech-inc.com laboratory@envirotech-inc-com



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

10.0

10.0

Client:	ConocoPhillips		Project #:	•	96052-1706
Sample ID:	Pre-Set Cuttings		Date Reported:	(09-04-12
Laboratory Number:	63132		Date Sampled:	(08-31-12
Chain of Custody:	6292		Date Received:	(09-04-12
Sample Matrix:	Soil		Date Analyzed:	(09-04-12
Preservative:	Cool		Date Extracted:		09-04-12
Condition:	Intact		Analysis Requested:		BTEX
-			Dilution:		50
			· ·	Det.	
		Concentration	n	Limit	
Parameter		(ug/Kg)	(ug/Kg)	
Benzene		ND		10.0	
Toluene		ND		10.0	
Ethylbenzene		ND		10.0	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	101 %
	1,4-difluorobenzene	100 %
	Bromochlorobenzene	98.3 %

ND

ND

ND

References:

p,m-Xylene

Total BTEX

o-Xylene

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846.

USEPA, December 1996.

Comments: Kessler Com 3P / Mote 212



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	Project #:	N/A
Sample ID:	0904BCAL QA/QC	Date Reported:	09-04-12
Laboratory Number:	63132	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	09-04-12
Condition:	N/A	Analysis:	BTEX
		Dilution:	50

Calibration: and Detection Limits (ug/L)	I-Cal RE	C-Cal RF:	%Diff:	∠ Blank ⊟ Conc	Detect.
Benzene	3.7326E-05	3.7326E-05	0.000	ND	0.2
Toluene	4.1770E-05	4.1770E-05	0.000	ND	0.2
Ethylbenzene	4.6347E-05	4.6347E-05	0.000	ND	0.2
p,m-Xylene	4.0659E-05	4.0659E-05	0.000	ND	0.2
o-Xylene	4.7106E-05	4.7106E-05 ⁻	0.000	ND	0.2

Duplicate Conc. (ug/Kg)	/ Sample Du	plicate :	i %Diff.	Accept Range	Detect: Limit
Benzene	ND	ND	0.00	0 - 30%	10
Toluene	ND	NĎ	0.00	0 - 30%	10
Ethylbenzene	ND	ND	0.00	0 - 30%	10
p,m-Xylene	ND	ND	0.00	0 - 30%	10
o-Xylene	ND	ND	0.00	0 - 30%	10

Spike Conc. (ug/Kg)	Sample : Amo	unt Spiked, Spik	ed Sample % l	Recovery	Accept Range
Benzene	ND	2500	2400	96.0	39 - 150
Tolueņe	ND	2500	2400	96.0	46 - 148
Ethylbenzene	ND	2500	2440	97.6	32 - 160
p,m-Xylene	ND	5000	4810	96.2	46 - 148
o-Xylene	ND	2500	2440	97.6	46 - 148

ND - Parameter not detected at the stated detection limit.

Dilution: Spike and spiked sample concentration represent a dilution proportional to sample dilution.

References:

Method 5030B, Purge-and-Trap, Test Methods for Évaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using

Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 63132.



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:	ConocoPhillips	Project #:	96052-1706
Sample ID:	Pre-Set Cuttings	Date Reported:	09-04-12
Laboratory Number:	63132	Date Sampled:	08-31-12
Chain of Custody No:	6292	Date Received:	09-04-12
Sample Matrix:	Soil	Date Extracted:	09-04-12
Preservative:	Cool	Date Analyzed:	09-04-12
Condition:	Intact	Analysis Needed:	TPH-418.1

		Det.
	Concentration	Limit
Pärametér	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

14.5

6.6

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Kessler Com 3P / MOTE 212





EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS **QUALITY ASSURANCE REPORT**

Client:

QA/QC

Project #:

N/A

Sample ID:

QA/QC

Date Reported:

09-04-12

Laboratory Number:

09-04-12-TPH.QA/QC 63124 Date Sampled:

N/A

Sample Matrix:

Freon-113

Date Analyzed:

09-04-12

Preservative: Condition:

N/A N/A Date Extracted: Analysis Needed: 09-04-12 **TPH**

Calibration : I-Cal Date

C-Cal Date / I-Cal RF: C-Cal RF: % Difference Accept Range 09-04-12

1.650

1.720

4.3%

+/- 10%

Blank Conc. (mg/Kg)

07-11-12

Concentration

Detection Limit

TPH

TPH

TPH

ND

6.6

Duplicate Conc. (mg/Kg)

Sample : Duplicate % Difference Accept: Range

+/- 30%

37.0

31.7

14.3%

Sample Spike Added Spike Result % Recovery Accept Range 37.0

2,000

1,780

87.4%

80 - 120%

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

QA/QC for Samples 63093-63100, 63103, 63122, 63124, 63127, 63132.





Chloride

96052-1706

09-04-12

08-31-12

09-04-12

ConocoPhillips Project #: Client: **Pre-Set Cuttings** Date Reported: Sample ID: Lab ID#: 63132

Date Sampled: Date Received: Sample Matrix: Soil Preservative: Cool Date Analyzed:

09-04-12 Condition: Intact Chain of Custody: 6292

Concentration (mg/Kg) **Parameter**

Total Chloride 16.7

Reference: U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983.

Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

Kessler Com 3P/ MOTE 212