

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such proposals.

FORM APPROVED  
OMB No. 1004-0135  
Expires July 31, 1996

5. Lease Serial No.

NMNM51014

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Elm Ridge Resources, Inc.

3a. Address

PO Box 156, Bloomfield, NM 87413

3b. Phone No. (include area code)

505-632-3476

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FSL X 2310' FWL

Sec. 25-T25N-R12W

8. Well Name and No.

Tono Hixon #1

9. API Well No.

30-045-26770

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize <input type="checkbox"/> Deepen <input type="checkbox"/> Production (Start/Resume) <input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing <input type="checkbox"/> Fracture Treat <input type="checkbox"/> Reclamation <input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair <input type="checkbox"/> New Construction <input type="checkbox"/> Recomplete <input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans <input checked="" type="checkbox"/> Plug and Abandon <input type="checkbox"/> Temporarily Abandon
	<input type="checkbox"/> Convert to Injection <input type="checkbox"/> Plug Back <input type="checkbox"/> Water Disposal

13. Describe Proposed or Completed Operations (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once Testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Elm Ridge Resources intends to P & A this well using the attached plugging procedure.

14. I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Amy Mackey

Title

Production Assistant

Signature

Date

April 13, 2005

THIS SPACE FOR FEDERAL OR STATE USE

Approved by

Original Signed: Stephen Mason

Title

Date

APR 19 2005

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

NMCCD

### **Plugging Program for Tono Hixon #1:**

Plug 1: Set retainer at 4580'. Pump 27 sack plug below retainer, and spot ~~2~~ sacks above retainer, to cover perforations and top of Gallup.

Plug 2: With end of tubing at 1948', spot 17 sack balanced plug from 1948-1848', to cover top of Cliff House.

Plug 3: With end of tubing at 1164', spot ~~34~~ sack balanced plug from 1164-~~913~~ 804' to cover top of Pictured Cliffs and Fruitland Coal.

Plug 4: With end of tubing at 316', mix and pump 34 sacks, or sufficient cement to bring cement to surface, inside 5-1/2" casing.

Cut off wellhead 3' below surface. Install dry hole marker. Reclaim location.

# Elm Ridge Resources

## Pertinent Data Sheet

**Well Name:** Tono Hixon #1  
**Footage:** 990' FSL and 2310' FWL  
**Location:** Section 25, T25N, R12W  
**County:** San Juan County, NM  
**API#:** 30-039-26770

**Field:** Bisti Lower Gallup

**Elevation:** 6398' KB

**TD:** 4954' KB

**PBTD:** 4906' KB

**Completed:** 4/15/87

### Casing Record:

Hole Size	Casing Size	Wt.	Grade	Depth Set	Cement
12-1/4"	8-5/8"	24#	J-55	266'	189 ft <sup>3</sup> (Circ. to Surface)
7-7/8"	5-1/2"	15.5#	J-55	4952'	1784 ft <sup>3</sup> (Circ to Surface)

### Formation Tops:

Nacimiento	Surface
Ojo Alamo	200'?
Fruitland	963'
Pictured Cliffs	1114'
Cliff House	1898'
Gallup	4630'

**Perforations:** Gallup: 4644-4780'

Wellbore Diagram  
Tono Hixon #1  
SW/4 Sec. 25, T25N, R12W  
San Juan County Co., NM  
API #30-045-26770

