Submit 3 Copies To Appropriate District	State of Ne	w Mexico		Form C-103
Office District I	Energy, Minerals an	d'Natural Resources		May 27, 2004
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.	3: 4
District II OIL CONSERVATION DIVISION		30-045-30822 5/950		
1301 W. Grant Av., Artista, 140 00210		5. Indicate Type of	Lease	
District III 1220 South St. Francis Dr		STATE [FEE 🛛	
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe. 1	NM 87505/	6. State Oil & Gas	
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM			o. State on a ous	Zouse 1 vo.
87505				
SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit				Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A		OR PLUG BACK TO A	Apperson	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH				
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other		8. Well Number #1E		
	Name of Operator		9. OGRID Number	
	San Juan Resources of Colorado		020208	
3. Address of Operator c/o Wal		WILL SERVICE SERVICE	10. Pool name or V	1
7415 East Main Street, Farmington	n, NM 87402		Blanco Mesa Verde	e / Basın Dakota
4. Well Location	1 Total	4 0		
Unit Letter 1: 1964	feet from the South lin	e and 670 feet from th	e Fact line	ļ
	No contract to the second seco	~ \\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \		
Section 30 Township		129	ounty San Juan	
		her DR, RKB, RT, GR, etc.		
	5778' GL			
Pit or Below-grade Tank Application	or Closure 🔲			
Pit type Depth to Groundwater	Distance from nearest fresh wa	ter well Distance fr	om nearest surface water	•
Pit Liner Thickness: mil	Below-Grade Tank: Volun	ne bbis; Construction !	Material	
12. Check	Appropriate Box to Indi	cate Nature of Notice,	Report or Other I	Data
	NTENTION TO:		SEQUENT REP	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	☐ REMEDIAL WOR	K 🔲 /	ALTERING CASING 🔲
				
TEMPORARILY ABANDON	CHANGE PLANS	☐ COMMENCE DR	ILLING OPNS.	P AND A
	-	COMMENCE DR CASING/CEMEN		P AND A
TEMPORARILY ABANDON	·	TT.		P AND A
TEMPORARILY ABANDON	·	TT.		PANDA 🗆
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report	MULTIPLE COMPL	CASING/CEMEN	T JOB	
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or comp	MULTIPLE COMPL pleted operations. (Clearly si	OTHER:	T JOB	, including estimated date
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or compost starting any proposed w	MULTIPLE COMPL	OTHER:	T JOB	, including estimated date
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or comp	MULTIPLE COMPL pleted operations. (Clearly si	OTHER:	T JOB	, including estimated date
TEMPORARILY ABANDON DULL OR ALTER CASING DIFFERMENT DIF	MULTIPLE COMPL pleted operations. (Clearly stork). SEE RULE 1103. For	OTHER: tate all pertinent details, an Multiple Completions: A	d give pertinent dates	i, including estimated date n of proposed completion
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or compof starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S'	pleted operations. (Clearly stork). SEE RULE 1103. For	OTHER: tate all pertinent details, an Multiple Completions: A	d give pertinent dates ttach wellbore diagram	i, including estimated date on of proposed completion accessing and set at 223'KB.
TEMPORARILY ABANDON DULL OR ALTER CASING DIFFERMENT DIF	pleted operations. (Clearly stork). SEE RULE 1103. For	OTHER: tate all pertinent details, an Multiple Completions: A	d give pertinent dates ttach wellbore diagram	i, including estimated date on of proposed completion accessing and set at 223'KB.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or compof starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S'	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230'1 "B" with 2% CaCl ₂ and ¼ # sk	OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl	d give pertinent dates ttach wellbore diagram	i, including estimated date on of proposed completion accessing and set at 223'KB.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or compof starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C: 04/09/05 Nippled up the BOP and press	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230'1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to	OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi.	IT JOB	i, including estimated date in of proposed completion C casing and set at 223 KB. Face. Hole was staying full.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or compof starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230'1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to KB (8-3/4", HTC, S0-09C). R	OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 208	IT JOB In the digite pertinent dates that wellbore diagram 9-5/8", 36#, J-55, ST&C is of good cement to surface. #, J-55, ST&C casing an	including estimated date on of proposed completion accasing and set at 223 KB. Face. Hole was staying full.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: ☑ Drilling Report 13. Describe proposed or compof starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C: 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955 Insert float is at 3906' KB. Cemented	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall	OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 200 liburton Lite 65/35 poz w/2%	IT JOB In the distribution of the distributio	including estimated date on of proposed completion accasing and set at 223°KB. Face. Hole was staying full. and landed at 3951°KB.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or compof starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall	OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 200 liburton Lite 65/35 poz w/2%	IT JOB In the distribution of the distributio	including estimated date on of proposed completion accasing and set at 223°KB. Face. Hole was staying full. and landed at 3951°KB.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: ☑ Drilling Report 13. Describe proposed or compost starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and presson of the starting at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft.)	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of	CASING/CEMEN OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 20stiburton Lite 65/35 poz w/2% of celloflake. Bumped plug to	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C s of good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & o 1500 psi. Circulated 2	including estimated date on of proposed completion and set at 223°KB. Face. Hole was staying full. In the delanded at 3951°KB. It is a staying full.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: ☑ Drilling Report 13. Describe proposed or compost starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and presson of the starting at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft.) 04/19/05 Ran 172 jts (6718.99°) of 4-12	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to X KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of 2", 10.5#, J-55, LT&C casing. I	CASING/CEMEN OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 200 liburton Lite 65/35 poz w/2% of celloflake. Bumped plug to canded casing at 6731'KB. In	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C s of good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & co 1500 psi. Circulated 2 disert float at 6707'KB.	including estimated date on of proposed completion and set at 223°KB. Face. Hole was staying full. In the delanded at 3951°KB. In the was staying full.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: ☑ Drilling Report 13. Describe proposed or compostarting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and presson of the state of th	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to X KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of 2", 10.5#, J-55, LT&C casing. I	CASING/CEMEN OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 200 liburton Lite 65/35 poz w/2% of celloflake. Bumped plug to canded casing at 6731'KB. In	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C s of good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & co 1500 psi. Circulated 2 disert float at 6707'KB.	including estimated date on of proposed completion and set at 223°KB. Face. Hole was staying full. In the delanded at 3951°KB. In the was staying full.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: ☑ Drilling Report 13. Describe proposed or compost starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and presson of the starting at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft.) 04/19/05 Ran 172 jts (6718.99°) of 4-12	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to X KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of 2", 10.5#, J-55, LT&C casing. I	CASING/CEMEN OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 200 liburton Lite 65/35 poz w/2% of celloflake. Bumped plug to canded casing at 6731'KB. In	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C s of good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & co 1500 psi. Circulated 2 disert float at 6707'KB.	including estimated date on of proposed completion and set at 223°KB. Face. Hole was staying full. In the delanded at 3951°KB. In the was staying full.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: ☑ Drilling Report 13. Describe proposed or compostarting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955 Insert float is at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft.) 04/19/05 Ran 172 jts (6718.99') of 4-12 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx 4.00 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx 4.00 cu.ft.)	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to X KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of 2", 10.5#, J-55, LT&C casing. I	CASING/CEMEN OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 200 liburton Lite 65/35 poz w/2% of celloflake. Bumped plug to canded casing at 6731'KB. In	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C s of good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & co 1500 psi. Circulated 2 disert float at 6707'KB.	including estimated date on of proposed completion and set at 223°KB. Face. Hole was staying full. In the delanded at 3951°KB. In the was staying full.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: ☑ Drilling Report 13. Describe proposed or compostarting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955 Insert float is at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft.) 04/19/05 Ran 172 jts (6718.99') of 4-12 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx 4.00 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx 4.00 cu.ft.)	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to X KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of 2", 10.5#, J-55, LT&C casing. I	CASING/CEMEN OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 200 liburton Lite 65/35 poz w/2% of celloflake. Bumped plug to canded casing at 6731'KB. In	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C s of good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & co 1500 psi. Circulated 2 disert float at 6707'KB.	including estimated date on of proposed completion and set at 223°KB. Face. Hole was staying full. In the delanded at 3951°KB. In the was staying full.
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: ☑ Drilling Report 13. Describe proposed or compostarting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955 Insert float is at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft. 04/19/05 Ran 172 jts (6718.99') of 4-12 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx/cement @ 2400'	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230'1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of Class "B" neat with ¼#/sx of Gilsonite & ¼ #/sk of celloflate.	OTHER: Tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. Tan 90 jts (3939.02') of 7", 200 biburton Lite 65/35 poz w/2% of celloflake. Bumped plug to anded casing at 6731'KB. Ir ake. Bumped plug to 1500psi	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C sof good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & D 1500 psi. Circulated 2 asert float at 6707'KB. I. On 04/20/05 ran Tem	is, including estimated date in of proposed completion. C casing and set at 223 KB. face. Hole was staying full. In ad landed at 3951 KB. W/#/sx of celloflake and 6% 5bbls of cement to surface. Mix and pump 385 sx(562 aperature Survey, top of
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: ☑ Drilling Report 13. Describe proposed or compostarting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955 Insert float is at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft.) 04/19/05 Ran 172 jts (6718.99') of 4-12 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx 4.00 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx 4.00 cu.ft.)	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of Class "B" neat with ¼#/sx of Gilsonite & ¼ #/sk of celloflate above is true and complete to the complete	OTHER: Tate all pertinent details, an Multiple Completions: A TKB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. Tan 90 jts (3939.02') of 7", 200 biburton Lite 65/35 poz w/2% of celloflake. Bumped plug to anded casing at 6731'KB. Ir take. Bumped plug to 1500psi to the best of my knowledge.	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C sof good cement to surful to the surful to	including estimated date of proposed completion of proposed completion of casing and set at 223°KB. Sace. Hole was staying full. In ad landed at 3951°KB. See 1/4#/sx of celloflake and 6%. 5bbls of cement to surface. Mix and pump 385 sx(562 aperature Survey, top of the certify that any pit or below-
PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or composition of starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955' Insert float is at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft. 04/19/05 Ran 172 jts (6718.99') of 4-12 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx cement @ 2400' I hereby certify that the information grade tank has been/will be constructed of	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to X KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of Cache Cach	CASING/CEMEN OTHER: Tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. Tan 90 jts (3939.02') of 7", 200 liburton Lite 65/35 poz w/2% of celloflake. Bumped plug to anded casing at 6731'KB. In take. Bumped plug to 1500psi to the best of my knowledge idelines , a general permit	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C sof good cement to surful to the surful to	including estimated date of proposed completion of proposed completion of casing and set at 223°KB. Sace. Hole was staying full. In ad landed at 3951°KB. See 1/4#/sx of celloflake and 6%. 5bbls of cement to surface. Mix and pump 385 sx(562 aperature Survey, top of the certify that any pit or below-
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: ☑ Drilling Report 13. Describe proposed or composition of starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955' Insert float is at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft. 04/19/05 Ran 172 jts (6718.99') of 4-12 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx cement @ 2400' I hereby certify that the information	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to X KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of Cache Cach	CASING/CEMEN OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 200 liburton Lite 65/35 poz w/2% of celloflake. Bumped plug to anded casing at 6731'KB. In take. Bumped plug to 1500psi to the best of my knowledge idelines , a general permit	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C sof good cement to surful to the surful to t	including estimated date of proposed completion of proposed completion of casing and set at 223°KB. Sace. Hole was staying full. In ad landed at 3951°KB. See 1/4#/sx of celloflake and 6%. 5bbls of cement to surface. Mix and pump 385 sx(562 aperature Survey, top of the certify that any pit or below-
PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or composition of starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955 Insert float is at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx cement @ 2400' I hereby certify that the information grade tank has been/will be constructed of SIGNATURE	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of Class "B" neat with ¼#/sx of Gilsonite & ¼ #/sk of celloflating to NMOCD guidance.	CASING/CEMEN OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 200 liburton Lite 65/35 poz w/2% of celloflake. Bumped plug to anded casing at 6731'KB. In take. Bumped plug to 1500psi to the best of my knowledge idelines , a general permit	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C sof good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & D 1500 psi. Circulated 2 asert float at 6707'KB. In the control of the	i, including estimated date m of proposed completion casing and set at 223 KB. face. Hole was staying full. Indicated at 3951 KB. While Was staying full. Indicated at 3951 KB. While Was staying full. Indicated at 3951 KB. While While Staying full. Indicated at 3951 KB. While Sta
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or composition of starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955 Insert float is at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx cement @ 2400' I hereby certify that the information grade tank has been/will be constructed of SIGNATURE Type or print name Paul C. Thomp	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of Class "B" neat with ¼#/sx of Gilsonite & ¼ #/sk of celloflating to NMOCD guidence.	CASING/CEMEN OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 200 liburton Lite 65/35 poz w/2% of celloflake. Bumped plug to anded casing at 6731'KB. In take. Bumped plug to 1500psi to the best of my knowledge idelines , a general permit	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C sof good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & D 1500 psi. Circulated 2 asert float at 6707'KB. In the control of the	i, including estimated date m of proposed completion casing and set at 223 KB. face. Hole was staying full. Indicated at 3951 KB. While Was staying full. Indicated at 3951 KB. While Was staying full. Indicated at 3951 KB. While While Staying full. Indicated at 3951 KB. While Sta
PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or composition of starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955 Insert float is at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx cement @ 2400' I hereby certify that the information grade tank has been/will be constructed of SIGNATURE	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of Class "B" neat with ¼#/sx of Gilsonite & ¼ #/sk of celloflating to NMOCD guidence.	CASING/CEMEN OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 206 liburton Lite 65/35 poz w/2% of celloflake. Bumped plug to anded casing at 6731'KB. Ir take. Bumped plug to 1500psi to the best of my knowledge delines , a general permit TLE ress: paul@walsheng.ne	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C sof good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & D 1500 psi. Circulated 2 asert float at 6707'KB. In the control of the	i, including estimated date m of proposed completion casing and set at 223 KB. face. Hole was staying full. Indicated at 3951 KB. While Was staying full. Indicated at 3951 KB. While Was staying full. Indicated at 3951 KB. While While Staying full. Indicated at 3951 KB. While Sta
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or composition of starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955 Insert float is at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx cement @ 2400' I hereby certify that the information grade tank has been/will be constructed of SIGNATURE Type or print name Paul C. Thomp	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to KB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of Class "B" neat with ¼#/sx of Gilsonite & ¼ #/sk of celloflating to NMOCD guidence.	OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 200 diburton Lite 65/35 poz w/2% of celloflake. Bumped plug to anded casing at 6731'KB. In take. Bumped plug to 1500psi detailes , a general permit TLE	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C sof good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & D 1500 psi. Circulated 2 asert float at 6707'KB. In the control of the	including estimated date of proposed completion of proposed completion of casing and set at 223 KB. Face. Hole was staying full. In the definition of the case of
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: Drilling Report 13. Describe proposed or composition of starting any proposed wor recompletion. 04/08/05 Spud surface hole (12-1/4", S' Cemented with 150 sx (177 cu.ft.) of C' 04/09/05 Nippled up the BOP and press 04/12/05 TD intermediate hole at 3955 Insert float is at 3906' KB. Cemented gel, followed by with 100 sx (118 cu.ft.) of 50/50 poz w/ 2% SMS, 5#/sx cement @ 2400' I hereby certify that the information grade tank has been/will be constructed of SIGNATURE Type or print name Paul C. Thomp	pleted operations. (Clearly stork). SEE RULE 1103. For TC, DSJC-RR). Drilled to 230°, 1 "B" with 2% CaCl ₂ and ¼ # sk sure tested the casing and BOP to TKB (8-3/4", HTC, S0-09C). R with 550 sx (1078cu.ft.) of Hall.) of Class "B" neat with ¼#/sx of Cacing. It of Gilsonite & ¼ #/sk of celloflating above is true and complete to closed according to NMOCD guides. The pson P.E. E-mail additional and the complete to	CASING/CEMEN OTHER: tate all pertinent details, an Multiple Completions: A KB and ran 5jts (209.48') of celloflake. Circulated 12bbl to 600 psi. an 90 jts (3939.02') of 7", 206 liburton Lite 65/35 poz w/2% of celloflake. Bumped plug to anded casing at 6731'KB. Ir take. Bumped plug to 1500psi to the best of my knowledge delines , a general permit TLE ress: paul@walsheng.ne	d give pertinent dates ttach wellbore diagram 9-5/8", 36#, J-55, ST&C sof good cement to surf #, J-55, ST&C casing an CaCl ₂ , 5#/sk gilsonite & D 1500 psi. Circulated 2 asert float at 6707'KB. It on 04/20/05 ran Temes and belief. I further for an (attached) alternation of the Carlotte of the Carlot	i, including estimated date m of proposed completion casing and set at 223 KB. face. Hole was staying full. Indicated at 3951 KB. While Was staying full. Indicated at 3951 KB. While Was staying full. Indicated at 3951 KB. While While Staying full. Indicated at 3951 KB. While Sta