Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

					5. Lease Serial No. NMSF079381	
	is form for proposals to ell. Use Form 3160-3 (API			6. If Indian,	, Allottee or Tribe Name	
	PLICATE - Other instru	ctions on reverse.	SIDEVED	3	r CA/Agreement, Name and/or No.	
1. Type of Well Gas Well	8. Well Name and No. San Juan 32-8 Unit #256A					
2. Name of Operator ConocoPhillips Co.					9. API Well No. 30-045-31669 10. Field and Pool, or Exploratory Area Basin Fruitland Coal	
3a. Address 3b. Phone No. (include area code) P.O. Box 2197, WL3-6081 Houston Tx 77252 (832)486-2463 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)						
Sec. 25 T32N R8W SESE	730FSL 1240FÉL			11. County of San Juan NM	or Parish, State	
12. CHECK AP	PROPRIATE BOX(ES) T	O INDICATE NATUI	RE OF NOTICE, RI	EPORT, OR	OTHER DATA	
TYPE OF SUBMISSION TYPE OF ACTION						
□ Notice of Intent □ Subsequent Report	☐ Acidize ☐ Alter Casing ☐ Casing Repair	☐ Deepen ☐ Fracture Treat ☐ New Construction	Production (Start Reclamation Recomplete	/ Resume)	☐ Water Shut-Off ☐ Well Integrity ☑ Other Installed	
☐ Final Abandonment Notice	Casing Repair Change Plans Convert to Injection	☐ Plug and Abandon ☐ Plug Back	☐ Temporarily Aba ☐ Water Disposal	ndon	Pumping Unit	
If the proposal is to deepen dire Attach the Bond under which t following completion of the in- testing has been completed. Fir determined that the site is read;	ed Operation (clearly state all pertectionally or recomplete horizonta he work will be performed or provolved operations. If the operational Abandonment Notices shall be y for final inspection.)	inent details, including estinully, give subsurface location vide the Bond No. on file with a results in a multiple completified only after all requirements.	mated starting date of an ns measured and true ve ith BLM/BIA. Required etion or recompletion in nents, including reclama	rtical depths of I subsequent re a new interval tion, have been	ports shall be filed within 30 days I, a Form 3160-4 shall be filed once a completed, and the operator has	
Pumping Unit installed eff	ective 3/28/2005. 2.375"	tubing now lands @	3810'. Daily Sum	mary is atta	ached.	
	0011112	BTOR				



ACCEPTED FOR RECORD MAY 1 0 2005 FARMINGTON FIELD OF FICE BY

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)	Title				
Christina Gustartis	As Agent for Conoc	s Agent for ConocoPhillips Co			
Signature Chris Quitantes	Date 04/26/2005				
THIS SPACE FOR FEDERA	L OR STATE OFFICE	USE			
Approved by	Title	Date			
Conditions of approval, if any, are attached. Approval of this notice does not warracertify that the applicant holds legal or equitable title to those rights in the subject leads which would entitle the applicant to conduct operations thereon.		Office			
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfu	lly to make to any departm	ent or agency of the United States any false, fictitious or			



Regulatory Summary

SAN JUAN 32 8 UNIT #256A

11	tunotai iiig oota	4/2005 00:00						
30	PI/UWI	County	State/Province	Surface Legal Location	N/S Dist (ft)	N/S Ref	E/W Dist (ft)	E/W Ref
11	00453166900	SAN JUAN	NEW MEXICO	NMPM-32N-08W-25-P	730.0	S ´	1,240.0	E
Gr	round Elevation (fi	t) La	ititude (DMS)	Longitude (DMS)	Spuc	d Date	Rig Release	Date
	6,922.0	00 36	6° 56' 56.004" N	107° 37' 18.84" W	<u> </u>	07/22/2003	09	/20/2003

03/24/2005 11:00 - 03/24/2005 18:00

Last 24hr Summary

PRE MOVE SAFETY MEETING. MOVE KEY # 29 & SUPPORT EQUIPTMENT TO SJ 32-8 #256A LOCATION. RU RIG & SUPPORT EQUIPTMENT.

03/25/2005 07:00 - 03/25/2005 15:00

Last 24hr Summary

SAFETY MEETING. BLEED DN 590PSI CSG CSG PRESSURE. ND TREE & INSTALL TBG PLUG. NU BOPS STACK. PRESSURE TEST BOPS AS PER CP REQUIREMENTS. UNSEAT & PULL TBG HANGER. PULL TBG PLUG. TIH & TAG BOTTOM @ 3810'. BREAK CIRCULATION W/ 925 CFM AIR-MIST. CIRCULATE HOLE CLEAN. POOH LAYING DN 2 7/8" PRODUCTION TBG. NOTE: TBG PINS BAD ON 50-60- JTS.SWI.

03/28/2005 07:00 - 03/28/2005 17:00

Last 24hr Summary

SAFETY MEETING. BLEED DN 590PSI CSG PRESSURE. MU 2 3/8" x 1.78" F NIPPLE ON TOP OF A 2 3/8" x 30' SLOTTED MUD ANCHOR W/ 2 3/8" x 10' BULL PLUGGED TBG SUB ON BOTTOM. STRAP IN HOLE PICKING UP 119-JTS OF 2 3/8" EUE TBG. SPACED OUT ON SURFACE W/ 22' OF SUBS. LAND TBG HANGER IN TBG HEAD W/ EOT- 3810'KB. TOP OF F NIPPLE @ 3766'. ND BOPS & NU B-1 FLANGE. INSTALL COLLAR & PUMPING T. RU TO RUN PUMP & RODS. PU A 2" x 1 1/4" x 12' RHAC-ZDV ROD PUMP(CP-224) & CHECK ACTION. OK. TIH PICKING UP 3- 25' x 1 1/4" SINKER BARS & 147- 25' x 3/4" RODS. SPACE OUT ON SURFACE & SEAT ROD PUMP W/ 6'- 3/4" ROD SUB & 22' x 1 1/4" POLISH ROD. PRESSURE TEST TBG W/ H2O TO 500PSI. MANUALLY STROKE PUMP UP TO 750PSI. OK. INSTALL ROD CLAMP & HANG OFF ROD STRING W/ PUMP STROKE ON LT TAG. SWI, JOB COMPLETE. RIG DN RIG TO MOVE.