Form 3160-5 (August 1999)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135 Expires: November 30, 2000

Lease Serial No. SF-077952 A

SUNDRY NOTICES AND REPORTS ON WELLS				2 A
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			6. If Indian, All	lottee or Tribe Name
			15/67) 7. If Unit or 2/	V/Agreement, Name and/or No.
SUBMIT IN TRIPLICATE - Other instructions on reverse stills				
1. Type of Well		(0 , P)	2005 8. Well Name	and No.
☐ Oil Well ☐ Gas W	/ell Other	- VE 6		ık 24 #14S
2. Name of Operator Kukui Operating Company			9 API Well No 30-045-32	
3a. Address c/o Walsh Engineering & Prod. Corp. 3b. Phone No. (include area code) 10. Field and Pool, or Exploratory Area				
7415 East Main St. Farmington, NM 87402 (505) 327-4892 Basin Fruitland Coal				
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  11. County or Parish, State  Sec. Live. New Moving				
2000' FSL & 660' FEL Sec. 24, T27N, R10W  San Juan, New Mexico				
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA				
TYPE OF SUBMISSION TYPE OF ACTION				
✓ Notice of Intent	☐ Acidize ☐	•	Production (Start/Resume)	☐ Water Shut-Off
	Alter Casing	Fracture Treat	Reclamation	☐ Well Integrity
Subsequent Report	Casing Repair Change Plans	New Construction [ Plug and Abandon [	Recomplete Temporarily Abandon	Other SEE BELOW
Final Abandonment Notice	Convert to Injection		Water Disposal	
shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)  03/15/05 Spud 8 3/4" surface hole. Drilled to 145' and ran 3jts (133.75') of 7", 20#, J-55, ST & C casing and set at 143'KB.  Cemented with 68 sx (84 cu. ft.) of Type III with 3% CaCl <sub>2</sub> and 1/4 #/sk celloflake. Circulated 5.0 bbls of good cement to surface.  03/17/05 Nippled up the BOP and pressure tested the casing and BOP to 600 psi  03/21/05 TD 6 1/4" hole at 2633'KB  03/22/05 Ran 63 jts (2602.12') of 4 1/2", 10.5#, J-55, ST&C casing. Landed casing at 2607.12' KB. Insert float at 2584.50' KB. Cemented with 300 sx (699cu. Ft.) of Type III , 1/4 #/sk celloflake, and 5#/sk gilsonite, 2% sodium metasillicate, tailed with 100 sx (140 cu. ft.) of Type III , 1/4 # celloflake, 5#/sk gilsonite, 2% CaCl <sub>2</sub> . Did not circulate cement to surface.				
<ol> <li>I hereby certify that the foregoing is Name (Printed/Typed)</li> </ol>	true and correct	1	3	
Paul C. Thompson, P.E.	·	Title	Agent	
Signature Pan (C. )	has -	Date	May 4, 2005	CAN NECADA
THIS SPACE FOR FEDERAL OR STATE OFFICE USE ACCUPIED FURTHER THE				
Approved by		Title		Date MAY 1 3 2005
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operation thereon.				FARMINGTON FIELD OFFICE
Title 18 U.C.S. Section 1001 and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.				