Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
✓OMB NO. 1004-0137
Expires March 31, 2007

Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

NMSF079232
6. If Indian, Allottee or Tribe Name

abandoned well. Use Form 3160-3 (APD) for s	IIN 6 PM 12 25	
SUBMIT IN TRIPLICATE - Other instructions of	n reverse side RECEIVED	7. If Unit or CA/Agreement, Name and/or No.
Oil Well X Gas Well Other	FARMINGTON NM	8. Well Name and No. BOLACK C #10A
2. Name of Operator XTO Energy Inc.	707777	O ADVIVIN
	b. Phone No! (include area code)	9. API Well No. 30-045-29241
2700 Farmington Ave., Bldg. K. Ste 1 Farmington,	505-324-1090	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	100 m	BLANCO MESAVERDE
1640' FSL & 1410' FEL 28-27パー 8い (こう)	3	11. County or Parish, State
12. CHECK APPROPRIATE BOX(ES) 10-4NDI		SAN JUAN NM
12. CHECK APPROPRIATE BOX(ES) TQ-INDIC		ORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
X Notice of Intent	Deepen Production	(Start/Resume) Water Shut-Off
Alter Casing	Fracture Treat Reclamatio	n Well Integrity
Subsequent Report Casing Repair	New Construction Recomplet	e Other
Final Abandonment Notice Change Plans	X Plug and Abandon Temporaril	y Abandon
Convert to Injection	Plug Back Water Disp	osal
1) MIRU CT unit. Latch onto 1-1/4" CT. Spool the plugging operations. 3) MIRU PU. MI 143 jts (40 41) Blow well dwn & KW w/fresh wtr. 5) ND WH. NI RIH w/2-7/8" CIEP to 4420'. POH. 7) PU & TIH w/2 csg to 500 psig. 8) Spot a 20x type II cmt plug 2588'. 9) Spot a 14 sx Type II cmt plug inside formation. 10) TOH w/tbg. 11) Perf 3 sqz holes holes & circ to surf. Pmp 75 sx Type II cmt plug inside csg to cover Freitland, Kirtland & Ojo Alam then set 2-7/8" cmt retainer @ 1900' & use tbg to If EH annulus tsts, then perf 3 sqz holes through annulus vlv w/wtr. Mix & pmp approx 70 sx Type II good cmt out csg annulus yly. SWI & WOC. If EH annulus csg annulus yly. SWI & WOC. If EH annulus csg annulus yly. SWI & WOC. If EH annulus csg annulus yly. SWI & WOC. If EH annulus csg annulus yly.	500') 1-1/4" IG tbg. Check & J&PT BOP. 6) RIH w/2-7/8" 1-1/4" tbg & tag CTBP. Circ fr/4420'-3754' to isolate M 2-7/8" csg to cover intermed through 2-7/8" csg @ 1940'. , sqz 55, sx cmt outside 2-7/8 mo tops. Displace cmt to 100 set plug. TOH w/tbg. 12) 2-7/8" csg 2 610'. Estab circ cmt dwn 2-7/8" csg to fill	record csg & EH press. gauge ring to 4420'. POH. wellbore w/fresh wtr. PT formation. TOH w/tbg to csg shoe & top of PC (LEGG-LIV) Establish rate into sqz 3" csg & leave 20 sx cmt 00'. If csg didn't tst, PT EH annulus to 300 psig. irc out 2-7/8" x 5-1/2" csg csg annulus to surf, circ
covering Nacimiento top (610'-510'), surf csg sho	e fr/159'-79' & fr/50'-surf.	13) ND BOP & cut off WH
Name (Printed/Typied) HOLLAY C. PERKINS	REGULATORY COMPLI	
LOVE Clarkin	Date 6/1/2005	a contract de de Principal
THIS SPACE FOR FEDE	RAL OR STATE OFFICE USE	
Approved by	Title	Date
Original Signed: Stephen Mason: Conditions of approval, if any, are attached. Approval of this induce does not wan		JUN 1 3 2005
conditions of approval, if any, are attached. Approval of this notice does not wan certify that the applicant holds legal or equitable title to those rights in the subjective which would entitle the applicant to conduct operations thereon.		

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.