

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
OMB No. 1004-0135  
Expires: January 31, 2004

**SUNDRY NOTICES AND REPORTS ON WELLS**

*Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.*

**SUBMIT IN TRIPLICATE- Other instructions on reverse side.**

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator **Lance Oil & Gas Company, Inc.**

3a. Address  
**P. O. Box 70, Kirtland, NM 87417**

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
**910' FNL & 1,065' FWL  
Section 30, T29N - R13W, NMPM**

3b. Phone No. (include area code)  
**505-598-5601**

5. Lease Serial No.

**NMSF - 079065**

6. If Indian, Allottee or Tribe Name

**N / A**

7. If Unit or CA/Agreement, Name and/or No.

**N / A**

8. Well Name and No.

**FRPC 30#2**

9. API Well No.

**30 - 045 - 32738**

10. Field and Pool, or Exploratory Area

**W. Kutz PC / Basin Fruitland Coal**

11. County or Parish, State

**San Juan County, NM**

**12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Spud & Csg Sundry
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

The FRPC 30#2 was spud at 12:00 hrs, 05/15/05. Drill 12-1/4" hole down to casing point at 231' KB. Circulate and condition hole. TOO. Run 5 joints 8-5/8", 24 ppg, J-55, STC and land casing at 231' KB. Cement 8-5/8" casing with 155 sxs Halliburton PRB II cement containing 1/4 #/sx flocele and 5 #/sx gilsonite (Weight - 13.5 ppg, Yield - 1.81 ft3/sx and Water - 8.86 gals/sx). Displace cement with 12.1 bbls fresh water. Bumped plug to 250 psig at 09:00 hrs, 05/16/05. Plug held. Circulate 19 bbls cement to surface. WOC - 5 hrs. NU WH and BOP's.

Pressure test BOP's, blind rams and pipe rams to 250 psig (low) and 2,000 psig (high). Pressure test casing shoe to 600 psig. Pressure tests - Good. Tag cement at 175' KB. Drill cement to 231' KB. Drill new 7-7/8" hole to total depth on 05/17/05. Driller's TD - 1,395' KB. Circulate and condition hole. TOO. Run 32 joints 5-1/2", 15.5 ppg, J-55, LTC and land casing at 1,389' KB.

Cement 5-1/2" casing with 175 sxs as follows: Lead - 110 sxs Halliburton PRB II containing 2% Econolite, 2% calseal, 6% BWC salt, 0.3% versaset, 1/4 #/sx flocele, 5 #/sx gilsonite and 0.1% Super CBL (Weight - 12.0 ppg, Yield - 2.55 ft3/sx and Water - 14.4 gals/sx). Tail - 65 sxs Halliburton PRB II containing 2% Econolite, 2% calseal, 6% BWC salt, 0.3% versaset, 1/4 #/sx flocele, 5 #/sx gilsonite and 0.1% Super CBL (Weight - 13.0 ppg, Yield - 2.00 ft3/sx and Water - 10.31 gals/sx).

Displaced cement with 31.1 bbls fresh water. Full returns throughout. Bumped plug to 430 psig at 11:45 hrs, 05/18/05. Plug held. Circulated 19 bbls cement to surface. Rig released at 20:00 hrs, 05/18/05.

14. I hereby certify that the foregoing is true and correct  
Name (Printed/Typed)

**Thomas M. Erwin, P.E.**

Title **Senior Production Engineer**

Signature

*Thomas M. Erwin*

Date

**05/25/2005**

**ACCEPTED FOR RECORD**

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title

Date

Office

**FARMINGTON FIELD OFFICE**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

**NMOC**