SUNDRY	UNITED STATES DEPARTMENT OF THE BUREAU OF LAND MANA NOTICES AND REP is form for proposals to ell. Use Form 3160-3 (A	AGEMENT JUN	LS	5. Letse Serial 1 NMNM -	
SUBMIT IN TRIPLICATE- Other instructions on reverse side.					CA/Agreement, Name and/or No.
1. Type of Well Oil Well			N/A 8. Well Name	e and No	
2. Name of Operator Lance Oil &	8733	1977	WF Federal 12 #1		
3a. Address	3b. Phone No. (include	area code)	9. API Well 30 - 045		
P. O. Box 70, Kirtlan	505-598-5601			Pool, or Exploratory Area	
4. Location of Well (Footage, Sec.,	T., R., M., or Survey Description)	fri Od			r Parish, State
980' FNL & 1,420' FWL Section 12, T30N - R14W, NM	IPM				n County, NM
12. CHECK AI	PPROPRIATE BOX(ES) TO	INDICATE NATUR	E OF NOTICE, R	EPORT, OR	OTHER DATA
TYPE OF SUBMISSION		im	PE OF ACTION		
	Acidize	Deepen	Production (Sta	art/Resume)	Water Shut-Off
Notice of Intent	Alter Casing	Fracture Treat	Reclamation		Well Integrity Other Spud & Surface Csg
✓ Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete Temporarily Al	handon	Sundry
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal		
Attach the Bond under which the following completion of the intesting has been completed. Find determined that the site is read. This Sundry Notice amount and the WF Federal 12 #1 was TOOH. Run 3 joints 8-5/"B" cement containing 2'bbls fresh water. Bumper KB. RU to pump 1" top job.	ectionally or recomplete horizontall he work will be performed or provivolved operations. If the operation nal Abandonment Notices shall be y for final inspection.) ends previously submitted notices spud at 09:00 hrs, 11/11/04. 8°, 24 ppf, J-55, ST & C and le % CaCl2 and 1/4 #/sx flocele (dd plug to 600 psig at 17:30 hrs,	y, give subsurface location de the Bond No. on file versults in a multiple compfiled only after all require dece dated 12/01/04 and Drill 12-1/4" hole down and casing at 185' KB. Weight – 15.6 ppg, Yie, 11/14/04. Plug held." casing backside) with	ns and measured and trovith BLM/BIA. Required to the second ments, including reclans "Accepted for Recorm to casing point at Cement 8-5/8" casid — 1.18 ft3/sx and VDid not circulate cement 25 sxs Halliburton	ne vertical depths red subsequent re in a new interval nation, have been rd" by the BLM 190' KB. Circ ing with 135 sx Water - 5.20 g ment to surface	s of all pertinent markers and zones. eports shall be filed within 30 days a Form 3160-4 shall be filed once a completed, and the operator has of on 12/21/04. Fullate and condition hole. Its Halliburton Standard Class als/sx). Displace cement with 9.5 e. WOC - 18 hrs. TOC at 31 ment containing 2% CaCl2 and
14. I hereby certify that the fore Name (Printed/Typed)	egoing is true and correct				

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)				
Thomas M. Erwin, P.E.		Senior Production Engineer		
Signature Thomas Ma Samin Harles	Date	06/03/2005	ACCEPTED FOR RECORD	
ZHS SPACE FOR FEDERAL				
Approved by	Tic	le	JUN 0 8 2005 Pate	
Conditions of approval, if any, are attached. Approval of this notice does not warrar certify that the applicant holds legal or equitable title to those rights in the subject lear which would entitle the applicant to conduct operations thereon.		fice	FAMMING OUR FIELD OFFICE	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.