

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0135
Expires November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
CONOCOPHILLIPS CO.

3a. Address
5525 HIGHWAY 64, FARMINGTON, NM 87401

3b. Phone No. (include area code)
(505)599-3419

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
2236 SOUTH 2387 EAST
UL: J, Sec: 28, T: 32N, R: 7W

5. Lease Serial No.
SF078472

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.
SAN JUAN 32-7 UNIT 236A

9. API Well No.
30-045-32448

10. Field and Pool, or Exploratory Area
BASIN FRUITLAND COAL

11. County or Parish, State
SAN JUAN
NEW MEXICO

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/ Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Casing Report
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Casing was set in this well as per attached wellbore schematic.



14. I hereby certify that the foregoing is true and correct

Name (Printed/Typed)
JUANITA FARRELL

Title
REGULATORY ANALYST

Signature

Date
08/05/2005

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

ACCEPTED FOR RECORD

Approved by	Title	Date
		AUG 16 2005
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		FARMINGTON FIELD OFFICE BY <i>JB</i>

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

NWCCD

Well Name: San Juan 32-7 #236A
 API #: 30-045-32448-00-X1
 Location: 2236' FSL & 2387' FEL
Sec. 28 - T32N - R7W
San Juan County, NM
 Elevation: 6645' GL (above MSL)
 Drl Rig RKB: 13' above Ground Level
 Datum: Drl Rig RKB = 13' above GL

Patterson Rig: #747
 Spud: 17-Jul-05
 Spud Time: 23:30
 Release Drl Rig: 25-Jul-05
 Time Release Rig: 12:00
 Move In Cav Rig: _____
 Release Cav Rig: _____

9-5/8" 8 RD x 11" 3M Casing Head

Surface CasingDate set: 18-Jul-05
☒ New
☐ Used

Size 9 5/8 in
 Set at 232 ft # Jnts: 5
 Wt. 32.3 ppf Grade H-40
 Hole Size 12 1/4 in Conn STC
 Excess Cmt 125 %
 T.O.C. SURFACE

Csg Shoe 232 ft
 TD of 12-1/4" hole 244 ft

Notified BLM @ 8:50 hrs on 16-Jul-05
 Notified NMOCD @ 8:50 hrs on 16-Jul-05

Intermediate CasingDate set: 25-Jul-05
☒ New
☐ Used

Size 7 in 84 jts
 Set at 3569 ft 0 pups
 Wt. 23 ppf Grade J-55
 Hole Size 8 3/4 in Conn LTC
 Excess Cmt 160 %
 T.O.C. SURFACE
 Pup @ _____ ft
 Pup @ _____ ft

Top of Float Collar 3525 ft
 Bottom of Casing Shoe 3569 ft
 TD of 8-3/4" Hole 3575 ft

Notified BLM @ 20:45 hrs on 23-Jul-05
 Notified NMOCD @ 20:45 hrs on 23-Jul-05

Production Liner

Date set: _____

☐ New
☐ Used

Size _____ in
 Nominal Wt. _____ ppf
 Grade _____ Connections: _____
 # Jnts: _____
 Hole Size _____ inches
 Underreamed 6-1/4" hole to 9.5"
 Top of Liner _____ ft
 PBTB _____ ft
 Bottom of Liner _____ ft set in 4 ft of fill on bottom

Surface CementDate cmt'd: 18-Jul-05

Lead : 150 sx Class G Cement
 + 3% BWOC Calcium Chloride
 + 0.25 lb/sx Flocele
1.21 cuft/sx, 181.0 cuft slurry at 15.6 ppg
 Displacement: 15.0 bbls fresh wtr
 Bumped Plug at: 14:00 hrs w/ 250 psi
 Final Circ Press: 80 psi @ 2.0 bpm
 Returns during job: YES
 CMT Returns to surface: 8 bbls
 Floats Held: No floats used
 W.O.C. for 6.00 hrs (plug bump to start NU BOP)
 W.O.C. for 8.00 hrs (plug bump to test csg)

Intermediate CementDate cmt'd: 25-Jul-05

Lead : 420 sx Standard Cement
 + 3% Econolite
 + 0.25 lb/sx Flocele
 + 10 lb/sk Gilsonite
2.91 cuft/sx, 1222.2 cuft slurry at 11.5 ppg
 Tail : 100 sx 50/50 POZ : Standard cement
 + 2% Bentonite
 + 2% Calcium Chloride
 + 5 lb/sx Gilsonite
 + 0.25 lb/sx Flocele
1.33 cuft/sx, 133 cuft slurry at 13.5 ppg
 Displacement: 138.7 bbls
 Bumped Plug at: 05:15 hrs w/ 950 psi
 Final Circ Press: 640 psi @ 2 bpm
 Returns during job: YES
 CMT Returns to surface: 37 bbls
 Floats Held: X Yes ___ No

Schematic prepared by:
 Aaron Fuhr, Development Engineer
 01-Aug-2005

COMMENTS:

9-5/8" Surf:	No float equipment was run. Ran a guide shoe and an aluminum baffle plate 1 jt above the guide shoe @ 188'. Displaced top wiper plug with water. Shut in casing head and WOC before backing out landing jt. CENTRALIZERS @ 222', 144', 100' & 57'. Total: 4
7" Intermediate	DISPLACED W/ 138.7 BBLs. FRESH WATER TANDEM RISE CENTRALIZERS @ 3559', 3480', 3393', 3305', 3221', 3134', 3047', 2965', 2885', 421', 336', 252', 166', 80', & 38'. TURBOLIZERS @ 2843', 2800', 2757', 2714', & 2671' Total: 15
	Total: 5