Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OM B No. 1004-0137
Expires: March 31, 2007

	UREAU OF LAND MANAGEMENT	2005 JUL 25	5. I Pase Serial No. 25	ō		
Do not use the	NOTICES AND REPORTS OF is form for proposals to drill or a II. Use Form 3160-3 (APD) for su	to re-enter an RE(6. Windian, Allottee	or Tribe Name		
aballuolleu we		FARA	INGTON NM			
SUBMIT IN TRIPLICATE- Other instructions on reverse side.			7. If Unit or CA/Agreement, Name and/or No. Northeast Blanco Unit			
1. Type of Well Oil Well	Gas Well Other	2345	8. Well Name and N	0.		
2. Name of Operator Devon Energy	A. S	NEBU 234 API Well No.				
3a. Address PO Box 6459, Navajo Dam, NM	3b. Phone No 87419 505-632-0	o. (include area code) 705	30-045-32779 10. Field and Pool, o	r Exploratory Area		
4. Location of Well (Footage, Sec., 7	C., R., M., or Survey Description)		S Los Pinos Ft	Sd Pictured Cliffs		
1,440' FSL & 660' FEL, NE SE	J. Unit I, Sec. 23-T31N-R7W	. John Jak	Life. County or Parish	, State		
	100		San Juan, NM			
12. CHECK AP	PROPRIATE BOX(ES) TO INDICATE	NATURÊ OF NOMCE R	EPORT, OR OTHE	R DATA		
TYPE OF SUBMISSION	YPE OF SUBMISSION TYPE OF ACTION					
	Acidize Deepen	Production (Sta	rt/Resume) W	ater Shut-Off		
Notice of Intent	Alter Casing Fracture Tr	eat Reclamation		ell Integrity		
Subsequent Report	Casing Repair New Cons	truction Recomplete	✓ Ot	her Casing and Cement		
Final Abandonment Notice	Change Plans Plug and A	bandonTemporarily At	oandon _			
	Convert to Injection Plug Back	Water Disposal		<u> </u>		
determined that the site is ready Drilled 12 1/4" hole to 286 CaC1 and 1/4# PSX Floses Drilled 6 1/4" hole to 3,595 Gel, 2/10% Veraset, 1/10%	al Abandonment Notices shall be filed only after a for final inspection.) Spud on U on 6/25/05, set 8 jts of 9 5/8", H-40, ST&C all. Circulated 12 bbls of cement to surface. S' on 6/27/05, set 84 jts 4 1/2", J-55, LT&C, b Diacel LWL and tail w/75 sx (19 bbls) 50/2 face, top of cement @ 830'. Landed 2 3/8" in the state of the sta	24/05, 32.3# casing at 280'. Ceme Test casing to 1500 psi. 11.6# casing at 3,583'. Ceme 50 POZ, 3% Gel, 1 4/105 Hal	nted w/175 sx (37 bb ented lead w/275 sx (is) "B" cement w/2% 71 bbls) 50/50 POZ w/2%		
14. I hereby certify that the fore Name (Printed/Typed)	going is true and correct	1				
Melisa Zimmern	nan	Title Senior Operations Te	chnician			
Signature ///S. \$		Date 7-20-	05			
	THIS SPACE FOR FEDERAL	OR STATE OFFICE	USE	ACCEPTED FOR RECORD		
Approved by Conditions of approval, if any, are attached. Approval of this notice does not warra		Title	Date	AUG 0 3 2005		
	or equitable title to those rights in the subject le			FARMINGTUN FIELD OFFICE		
Title 18 U.S.C. Section 1001 and Title States any false, fictitious or fraudu	e 43 U.S.C. Section 1212, make it a crime for any lent statements or representations as to any matte	person knowingly and willfully rwithin its jurisdiction.	to make to any depart	nent or again. Fifthe United		

(Instructions on page 2)