UNITED STATES 1897777 DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENTS		5. Lease NMNM-03733
300 F		6. If Indian, Allottee or Tribe Name
SUNDRY NOTICES AND REPORTS ON WELLS		7. Unit Agreement Name
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for swift first form for proposals to drill or to deepen or plug back to a different 2 12		
1. Oil Well [] Gas Well [] Other []	ERMIT - (for sugalified posses) 0-3	8. Well Name and No.
GAS WELL	COPPOSIBLE CEIVE	BREECH 382
2. Name of Operator: 070 FARMING TO API Well No.		
Caulkins Oil Company		30-039-20912-00C1
3. Address of Operator: (505) 334-4323		10. Field and Pool, Exploratory Area
1409 W. Aztec Blvd. Ste B7, Aztec, NM 87410		CHACRA, PICTURED CLIFFS
4. Location of Well (Footage, Sec., Twp., Rge.)		11. Country or Parish, State
1190' F/S 1580' F/W SEC. 24-26N-7W		Rio Arriba Co., New Mexico
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
[X] Notice of Intent	[] Abandonment	[] Change of Plans
5301	[]Recompletion	[] New Construction
[] Subsequent Report	[X] Plugging Back	[] Non-Routine Fracturing [] Water Shut-Off
[] Final Abandonment Notice	[] Casing Repair [] Altering Casing	[] Conversion to Injection
	Other	Dispose Water
17. Describe Proposed or Completed Operations:		
0.4.04 Cardida Oil Carraman and the back to Oten Observation in this well by the fellowing many days		
8-4-04 Caulkins Oil Company requests to plug back the Otero Chacra zone in this well by the following procedure:		
Rig up.		
T. O. H. laying down 1" tubing.		
T. I. H. with cast iron bridge plug on 2 3/8" tubing – set bridge plug at 3425'.		
Chacra perforations, 3585' – 3637'.		
Spot 10 sacks (13.6 cu. ft.) on top of cast iron bridge plug, 3425' to 3269'.		
T. O. H. with setting tool.		
T. I. H. with 2 3/8" production tubing.		
Clean out to PBTD at 3269' with air package.		
Land 2 3/8" tubing on doughnut at approximately 2680'.		
Rig down and move		
SEE ATTACHED FAD		
NOTE: Temperature survey shows top of cement at 1650'. CONDITIONS OF APPROVAL		
CONDITIONS OF APPROVAL		
Adhere to previously issued stipulations.		
NOTE: The format is issued in lieu of U.S. BLM Form 3160-5		
18. I HEREBY CERTIFY THE FOREGOING IS TRUE AND CORRECT		
SIGNED: Heart I Vergue TITLE: Superintendent DATE: August 4, 2005		
ROBERT L. VERQUER		
APPROVED BY:		
CONDITIONS OF APPROVAL, IF ANY		

Bureau of Land Management Conditions of Approval:

- 1) If this well is located in a Specially Designated Area (SDA), compliance with the appropriate <u>seasonal closure</u> requirements will be necessary.
- 2) Pits must be lined with an impervious material at least 12 mils thick. The pit must be fenced on three (3) sides during workover operations and on the 4th side after the rig moves off location. Pits must be closed within 90 days of completion of the workover operations. Prior to closing the pit the liner must be cut off at mud level.