<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
<u>District II</u>
1301 W. Grand Avenue, Artesia, NM 88210
<u>District III</u>
1000 Rio Brazos Road, Aztec, NM 87410
<u>District IV</u>
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144 June 1, 2004

For drilling and production facilities, submit to appropriate NMOCD District Office. For downstream facilities, submit to Santa Fe

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes 🗵 No

Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank ⊠

	(50.7) 20.7 20.11		
Operator: <u>Burlington Resources</u> Tele Address: 3401 East 30th Street, Farmington, New Mexico, 87402	e-mail a	address: <u>LHasely@br-ir</u>	nc.com
Facility or well name: Garrett Federal Com 2 1E API #:		M Sec <u>13</u> T <u>029N</u>	R <u>011W</u>
•	71 Longitude <u>W107 56.903</u> NAD: 1927 ⊠ 198	33	
Surface Owner: Federal State Private ⊠ Indian			
Pit Type: Drilling Production Disposal Workover Emergency Lined Unlined Liner type: Synthetic Thicknessmil Clay Pit Volumebbl	Below-grade tank Volume: 40 bbl Type of fluid: Produced water and incidental oil. Construction material: Fiberglass Double-walled, with leak detection? Yes If not, explain why not. No – Tank was installed prior to Rule 50.		
Depth to ground water (vertical distance from bottom of pit to	Less than 50 feet	(20 points)	
seasonal high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)	
Sectional Ing. Trace Section of Branch	100 feet or more	(0 points)	10
Wallband protection area. (Less than 200 feet from a private	Yes	(20 maints)	
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other	No	(20 points) (0 points)	0
water sources.)		(o ponio,	O
Distance to surface water: (horizontal distance to all wetlands,	Less than 200 feet	(20 points)	
playas, irrigation canals, ditches, and perennial and ephemeral	200 feet or more, but less than 1000 feet	(10 points)	
watercourses.)	1000 feet or more	(0 points)	10
	Ranking Score (Total Points)		20
If this is a pit closure: (1) Attach a diagram of the facility showing onsite box if your are burying in place) onsite offsite If offsite,			
remediation start date and end date. (4) Groundwater encountered:			_
(5) Attach soil sample results and a diagram of sample locations and			thach sample results.
Additional Comments:			A. 3 (2)
Pit Location - 145 feet , 45degrees from the wellhead.		(O)	AUG 200
			CO
Soil sample collected 3 feet below bottom of tank. Soils tested cle	ean and no soil remediation was required. Lab ana	alysis attached	Mar On
		10 m	2,00
I hereby certify that the information above is true and complete to below-grade tank has been/will be constructed or closed according to the closed according to the closed according to the closed according to the	o the best of my knowledge and belief. I further or rding to NMOCD guidelines ⊠, a general pern	certify that the above d nit , or an (attached)	estimate pit at
Date:	ignature 2776 The operator of liability should to ent. Nor does it relieve the operator of its responsi	the contents of the pit or ibility for compliance w	tank contaminate
Approval: APPLIT OR & GAS INSPECTOR, DIST. &	Signature Deny To	Date: A	UG 17. 200



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Burlington Resources	Project #:	92115-001-001
Sample ID:	Garret Com 21E	Date Reported:	10-04-04
Laboratory Number:	30761	Date Sampled:	09-30-04
Chain of Custody No:	13005	Date Received:	09-30-04
Sample Matrix:	Soil	Date Extracted:	10-01-04
Preservative:	Cool	Date Analyzed:	10-04-04
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Area 2.

PID=(),8

Analyst P. Que

Mistine m Walter