UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on We			
-	lls		
	- ···	5.	Lease Number
Type of Well		<i>c</i>	NMSF-078717
GAS		6.	If Indian, All. or Tribe Name
Name of Operator 2005 AUG 25	9 PM 4 G	6 7.	Unit Agreement Name
BUDI INCTON			
RESOURCES OIL & GAS COMPANY	CEIVED MINGTON I		
Address & Phone No. of Operator		8.	Well Name & Number Grenier B 5M
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.		
Logation of Woll Feetage Cos M D W	_	1.0	30-045-3 370 1 3320
4. Location of Well, Footage, Sec., T, R, M 1005'FSL,1880'FWL, Sec.6, T-29-N, R-10-W, NMPM		10.	Field and Pool Blanco MV/Basin DK
	11,	County and State San Juan, NM	
CHECK I PRODUCTION DOWNERS OF THE PRODUCTION OF			-
. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE Type of Submission Type of A		OTHER	DATA
	Change of	Plans	
$_$ Recompletion $_$	New Cons	tructi	
	Non-Rout		
Casing Repair Final Abandonment Altering Casing	water sn Conversi	ut off on to	Injection
_X_Other Well Spud	001110151	011 00	11170001011
_A_Other well Spud			
13.Describe Proposed or Completed Operations			
	32.3#, H-40 y) w/3.00% The casing	Csg s Cacl2,	et @ 333'. .25 pps
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC.	32.3#, H-40 y) w/3.00% The casing	Csg s Cacl2,	et @ 333'. .25 pps
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC. Tested with the drilling rig before proceeding with	32.3#, H-40 y) w/3.00% The casing	Csg s Cacl2,	et @ 333'. .25 pps
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC. Tested with the drilling rig before proceeding with	32.3#, H-40 y) w/3.00% The casing	Csg s Cacl2,	et @ 333'. .25 pps e pressure
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC. Tested with the drilling rig before proceeding with	32.3#, H-40 y) w/3.00% The casing	Csg s Cacl2,	et @ 333'. .25 pps e pressure
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC. Tested with the drilling rig before proceeding with	32.3#, H-40 y) w/3.00% The casing	Csg s Cacl2,	et @ 333'25 pps e pressure SEP 2005
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC. Tested with the drilling rig before proceeding with	32.3#, H-40 y) w/3.00% The casing	Csg s Cacl2,	et @ 333'25 pps e pressure SEP 2005
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC. Tested with the drilling rig before proceeding with APD Row Related	32.3#, H-40 y) w/3.00% The casing	Csg s Cacl2,	et @ 333'25 pps e pressure
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC. Tested with the drilling rig before proceeding with APD Row Related	32.3#, H-40 y) w/3.00% The casing	Csg s Cacl2,	et @ 333'25 pps e pressure SEP 2005
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC. Ttested with the drilling rig before proceeding with APD Row Related 1. Thereby certify that the foregoing is true and correct.	32.3#, H-40 y) w/3.00% The casing h drilling.	Csg s Cacl2, will b	et @ 333'25 pps e pressure SEP 2005 OU CONS. DIV.
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC. Ttested with the drilling rig before proceeding with APD Row Related APD Row Related Title Regulator Chis space for Federal or State Office use)	32.3#, H-40 y) w/3.00% The casing h drilling.	Csg s Cacl2, will b	e 8ACCEPTED FOR RECOR
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC. Itested with the drilling rig before proceeding with APD Row Related 1. Thereby certify that the foregoing is true and correct. 2. Independent Correct of the Regulator of State Office use) 2. Proved by Title	32.3#, H-40 y) w/3.00% The casing h drilling.	Csg s Cacl2, will b	et @ 333'25 pps e pressure SEP 2005 OU CONS. DIV.
13.Describe Proposed or Completed Operations 8/24/05 MIRU Mote #1. Spud 12-1/4" surface hole @ 337'. Circ hole clean. TOOH. TIH w/11 Jts 9-5/8", Cmt w/246 sxs Type III cmt (335 Cu Ft-59 bbl slurry celloflake. Circ 22 bbls cmt to surface. RD. WOC. Tested with the drilling rig before proceeding with APD Row Related APD Row Related Title Regulator Chis space for Federal or State Office use)	32.3#, H-40 y) w/3.00% The casing h drilling. ry Speciali	Csg s Cacl2, will b	et @ 333'25 pps e pressure SEP 2005 OU CONS. DIV. e 8ACCEPTED FOR RECOR