

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-039-27811
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Casaus
8. Well No. #1
9. Pool name or Wildcat Basin Fruitland /Gavilan PC

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator

Benson-Montin-Greer Drilling Corporation

3. Address of Operator

4900 College Blvd. Farmington, NM 87401

4. Well Location

Unit Letter O : 885' Feet From The SOUTH Line and 1945' Feet From The EAST Line

Section 20 Township 25N Range 2W NMPM Rio Arriba County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

100 GR

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

11. **NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: Drilling ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent date, including estimated date of starting any proposed work) SEE RULE 1103.

Spud well on 6-23-05. Drilled 8-3/4" hole to 365' KB. Ran 8-jts, 7", 17#, J-55 casing set @ 352' KB. Cemented with 160 sks cement, 2" KCL, 1/4# Celloflake. Circulated cement to surface. Drilled 6-1/4" to 3575' KB. TD reached on 7-27-05. Ran 85-jts., 4-1/2", 10.5#, J-55 casing set @ 3570' KB. DV tool set @ 3256' KB. Cemented 1st stage w/50 sks 50/50 POZ, 2% gel, 5# Gilsonite, 1/4# Flocele, 4/10% Halad-9. Cemented 2nd stage with 200 sks Econolite, 10# Gilsonite, 1/4# Flocele. Good returns throughout. Rig down cementers. Set slips. Cut off casing. Release rig. Install wellhead.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Trudy Grubelnik TITLE Production Clerk DATE 08/08/05
TYPE OR PRINT NAME Trudy Grubelnik TELEPHONE NO. 505-325-8874

(This space for State Use)

APPROVED BY Chad Lerr SUPERVISOR DISTRICT # 3 DATE AUG 29 2005

CONDITIONS OF APPROVAL, IF ANY: