

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2005 SEP 8 AM 9 30

1. Type of Well

Oil Well

2. Name of Operator


Central Resources, Inc.

3. Address & Phone No. of Operator

1775 Sherman St., Denver, CO 80203-4313

4. Location of Well, Footage, Sec., T, R, M

1980' FSL and 660' FEL, Section 19, T-31-N, R-16-W

RECEIVED
070 FARMINGTON NM**5. Lease Number**

BIA #14-20-600-3531

6. Indian, All. or**Tribe Name**

Navajo

7. Unit Agreement Name

Horseshoe Gallup

8. Well Name & Number

HSGU #104

9. API Well No.

30-045-10558

10. Field and Pool

Horseshoe Gallup

11. County & State

San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**Type of Submission**☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment**Type of Action**☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☒ Other - Final Abandonment☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut off☐ Conversion to Injection**13. Describe Proposed or Completed Operations**

Plug and abandon the above well as follows:

7/5/05 MOL and RU rig. Check well pressures: 0# on BH, 0# on casing, 0# on tubing. Pull on rods and unseat pump. Hot oil rods and tubing with water. TOH and LD 51 - 5/8" rods and rod pump. Shut in well.

7/6/05 ND wellhead. NU BOP and companion flange. TOH and LD 42 joints tubing. Shut in well.

7/7/05 TIH with 4.5" casing scraper and A+ workstring to 695'. Unable to get deeper; TOH and LD scraper. TIH open-ended with 2.375" tubing to 1342'. Circulate casing clean with 22 bbls of water. Plug #1 with 54 sxs Type III cement (71 cf), with 2% CaCl₂ inside the 4.5" casing from 1342' to 600' to isolate the Gallup interval. TOH and LD tubing. Shut in well and WOC. Load casing with 3 bbls of water and pressure test to 500#, held OK. RIH with wireline and tag cement at 561'. Perforate 3 holes at 145'. Establish circulation out the BH valve with 20 bbls of water. Plug #2 with 54 sxs Type III cement (71 cf) pumped down the 4.5" casing from 145' to surface, circulate good cement out the bradenhead. Shut in well and WOC. ND BOP. Dig out and cut off wellhead. Found cement at the surface in both the 4.5" casing and the annulus. Mix 15 sxs cement to fill casing and install P&A marker. RD and MOL.

G. Shay, Navajo Nation Minerals, was on location.

SIGNATURE

Contractor

July 8, 2005

William F. Clark

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

SEP 08 2005

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

BY DATE

NMOCD