

**OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO**

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFICE

OPERATOR:
FARMINGTON, NM 87401
PHONE: 599-3400

LOCATION INFORMATION

API NUMBER:

WELL NAME OR PIPELINE SERVED:

LEGAL LOCATION:

INSTALLATION DATE:

PPCO. RECTIFIER NO.:

ADDITIONAL WELLS:

TYPE OF LEASE:

LEASE NUMBER:

GROUND BED INFORMATION

TOTAL DEPTH: CASING DIAMETER: TYPE OF CASING: CASING DEPTH: CASING CEMENTED ☐

TOP ANODE DEPTH:

BOTTOM ANODE DEPTH:

ANODE DEPTHS:

AMOUNT OF COKE:

WATER INFORMATION

WATER DEPTH (1):

WATER DEPTH (2):

GAS DEPTH:

CEMENT PLUGS:

RCVD FEB 20 '13
OIL CONS. DIV.
DIST. 3

OTHER INFORMATION

TOP OF VENT PERFORATIONS:

VENT PIPE DEPTH:

REMARKS:

COKE DEPTH 150"

IF ANY OF THE ABOVE INFORMATION IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE. UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED.

*- LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

Wednesday, Nov

ca

COMPANY: CONOCO PHILLIPS
 COMPANY REP.: JOHN TAFOYA
 LOCATION: KESSLER COM 3P
 JOB NO.: 340140400
 FOREMAN: RON LUNA
 DRILLER: DARREL FERRIER

DATE: 2/7/2013
 DIA. HOLE: 7 7/8
 DEPTH: 300'
 COKE TYPE: SW
 # OF COKE: 50 BAGS
 # OF BENTONITE: 0

CASING: SCH40 PVC
 DIAMETER: 8"
 CASING DEPTH: 40'
 # OF ANODES: 10
 ANODE TYPE: 2284Z
 ANODE LEAD: HWMPE #8

corrpro®

RECTIFIER MFG: _____
 MODEL: _____
 SERIAL #: _____
 V-DC: _____ A-DC: _____

WELL LOG										ANODE PLACEMENT			
DEPTH FT.	DRILLERS LOG - SOIL TYPE	VOLTS	AMPS	COMMENTS / ANODE #	DEPTH FT.	DRILLERS LOG - SOIL TYPE	VOLTS	AMPS	COMMENTS / ANODE #	ANODE NO.	ANODE DEPTH	AMPS W/O COKE	AMPS W/ COKE
0	SAND	13.10		CASING	250	SANDY SHALE	4.60		#3-251	1	275	4.60	9.20
5	SAND			CASING	255	SANDY SHALE	4.30			2	263	4.10	10.70
10	SAND			CASING	260	SANDY SHALE	4.30			3	251	4.70	12.10
15	SAND			CASING	265	SANDY SHALE	4.40		#2-263	4	239	4.60	13.00
20	SAND			CASING	270	SANDY SHALE	4.70			5	227	5.00	13.10
25	SAND			CASING	275	SANDY SHALE	4.60		#1-275	6	215	3.60	9.10
30	SAND			CASING	280	SANDY SHALE	5.00			7	203	2.60	7.20
35	SAND			CASING	285	SANDSTONE	5.40			8	191	2.80	9.60
40	SAND			CASING	290	SANDSTONE				9	179	3.80	11.40
45	SANDSTONE				295	SANDSTONE				10	167	4.20	11.50
50	SANDSTONE				300	SANDSTONE				11			
55	SHALE				305					12			
60	SHALE				310				TD: 292'	13			
65	SHALE				315				VENT PIPE DEPTH: 303'	14			
70	SHALE				320					15			
75	SHALE				325					16			
80	SHALE		3.80		330					17			
85	SHALE		3.90		335					18			
90	SHALE		3.60		340					19			
95	SHALE		3.80		345					20			
100	SHALE		3.60		350					21			
105	SANDSTONE		4.10		355					22			
110	SANDSTONE		4.10		360					23			
115	SANDSTONE		3.80		365					24			
120	SANDSTONE		3.70		370					25			
125	SHALE		3.70		375								
130	SHALE		3.60		380								
135	SHALE		3.40		385								
140	SHALE		3.60		390								
145	SHALE		3.90		395								
150	SHALE		3.70		400								
155	SHALE		3.60		405								
160	SHALE		3.80		410								
165	SHALE		3.60	#10-167	415								
170	SHALE		3.70		420								
175	SANDSTONE		3.80		425								
180	SANDSTONE		3.70	#9-179	430								
185	SANDSTONE		4.00		435								
190	SANDSTONE		3.10	#8-191	440								
195	SANDSTONE		2.70		445								
200	SANDSTONE		3.00		450								
205	SANDSTONE		2.80	#7-203	455								
210	SANDSTONE		3.40		460								
215	SANDSTONE		3.30	#6-215	465								
220	SANDSTONE		2.80		470								
225	SANDSTONE		3.00	#5-227	475								
230	SANDSTONE		4.20		480								
235	SANDSTONE		4.40		485								
240	SANDSTONE		4.40	#4-239	490								
245	SANDSTONE		4.60		495								
										GROUND BED RESISTANCE TOTAL VOLTS: 13.10 TOTAL AMPS: 39.00 0.34 OHMS			
										SITE ELEVATION: 6002 WATER CONDUCTIVITY: COKE LEVEL: 150' EXTRA CASING USED: 20' ADDITIONAL COMMENTS: INJECT WATER 10' TO 40'			
										PP 7.5.1.24 Effective 11/13/12			