Culturals 1 Community District		. PAME	indentanon	E C 102
Submit 1 Copy To Appropriate District Office	State of New Me Energy, Minerals and Natu	10000000		Form C-103 Revised August 1, 2011
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240	Energy, Minierals and Natu	rai Resources	WELL API NO.	Tevisoa Hagast 1, 2011
District II - (575) 748-1283 811 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION		30-045-35362 5. Indicate Type of	Lassa	
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	1–(505) 334-6178 1220 South St. Francis Dr.		STATE \(\sigma\)	
<u>District IV</u> – (505) 476-3460	Santa Fe, NM 87505		6. State Oil & Gas	Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505				
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A		7. Lease Name or Unit Agreement Name Escrito 116-2409		
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				
1. Type of Well: Oil Well Gas Well Other		8. Well Number		
2. Name of Operator			9. OGRID Number	•
Encana Oil & Gas (USA) Inc.			282327	
3. Address of Operator 370 17 th Street, Suite 1700 Denver, CO 80202		10. Pool name or Wildcat Bisti Lower - Gallup		
4. Well Location			Disti Lowel - Gailu	ρ
	rom the SOUTH line and 300 feet fr	om the EAST line		
	from the SOUTH line and 330 feet f			
Section 16	Township 24N Ran		NMPM	County San Juan
	11. Elevation <i>(Show whether DR</i> , 6821 GR	RKB, RT, GR, etc.)		
	1 0021 GR	······································		
12. Check	Appropriate Box to Indicate N	ature of Notice, F	Report or Other D	D ata
NOTICE OF IN	ITENTION TO:	l cubc	EQUENT REP	ODT OE:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK		ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRIL		AND A
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT	JOB 🛛	
DOMAINOLE COMMINICLE				
DOWNHOLE COMMINGLE				
OTHER:		OTHER:	aire marking at Actor	
OTHER: 13. Describe proposed or comp	oleted operations. (Clearly state all pork). SEE RULE 19.15.7.14 NMAC	pertinent details, and		
OTHER: 13. Describe proposed or comp	ork). SEE RULE 19.15.7.14 NMAC	pertinent details, and		
OTHER: 13. Describe proposed or composed or starting any proposed we	ork). SEE RULE 19.15.7.14 NMAC	pertinent details, and	pletions: Attach we	llbore diagram of
OTHER: 13. Describe proposed or composed or starting any proposed we	ork). SEE RULE 19.15.7.14 NMAC completion.	pertinent details, and C. For Multiple Com	pletions: Attach we	llbore diagram of
OTHER: 13. Describe proposed or compostarting any proposed we proposed completion or recultive transfer of the synthetic oil-base mud systems.	ork). SEE RULE 19.15.7.14 NMAC completion. em from intermediate casing point (pertinent details, and C. For Multiple Com	pletions: Attach we R 1 al.	OVD MAR 4'13 IL CONS. DIV. DIST. 3
OTHER: 13. Describe proposed or compof starting any proposed we proposed completion or recomposed completion.	ork). SEE RULE 19.15.7.14 NMAC completion. em from intermediate casing point (1) 1/13. Landed lateral at 5795' on 2/1	pertinent details, and c. For Multiple Com 5960°) to TD of later 7/13. Length of late	pletions: Attach we R 1 al.	OVD MAR 4'13 IL CONS. DIV. DIST. 3
OTHER: 13. Describe proposed or composed was proposed completion or recurrence. Utilized synthetic oil-base mud system Kicked off lateral 4898'MD on 2/1 reached 2/24/13. Set whipstock at 4	ork). SEE RULE 19.15.7.14 NMAC completion. em from intermediate casing point (1/13. Landed lateral at 5795' on 2/1/858'. Milled window in 7" casing f	pertinent details, and C. For Multiple Com 5960') to TD of later 7/13. Length of late from 4858-4845'.	pletions: Attach we R al. ral 4033'. <u>TD</u> of <u>98</u>	OVD MAR 4'13 IL CONS. DIV. DIST. 3
OTHER: 13. Describe proposed or composed we proposed completion or recurrence Utilized synthetic oil-base mud syst Kicked off lateral 4898'MD on 2/1	ork). SEE RULE 19.15.7.14 NMAC completion. em from intermediate casing point (1/13). Landed lateral at 5795' on 2/1/858'. Milled window in 7" casing fring diameter: 4 1/2", production string.	pertinent details, and c. For Multiple Com 5960') to TD of later 7/13. Length of late from 4858-4845'.	pletions: Attach we R al. al. TD of 98	Ilbore diagram of CVD MAR 4'13 IL CONS. DIV. DIST. 3 28'MD/5444'TVD Depth of 6 1/8" hole from
OTHER: 13. Describe proposed or compof starting any proposed we proposed completion or reculous transfer of starting any proposed we proposed completion or reculous transfer of the starting any proposed we proposed completion or reculous transfer of the starting and proposed with the starting and proposed we proposed completion or reculous transfer of the starting and proposed we proposed we proposed we proposed with the starting any proposed or completion or reculous transfer of the starting any proposed or completion or reculous transfer of the starting any proposed or completion or reculous transfer of the starting any proposed we proposed completion or reculous transfer of the starting any proposed we proposed completion or reculous transfer of the starting any proposed we proposed completion or reculous transfer of the starting and the st	ork). SEE RULE 19.15.7.14 NMAC completion. em from intermediate casing point (1/13). Landed lateral at 5795' on 2/1/858'. Milled window in 7" casing fring diameter: 4 ½", production strict 9825'MD and float collar at 9809'	pertinent details, and C. For Multiple Com 5960') to TD of later 7/13. Length of late from 4858-4845'. Ing weight and grade: MD. Casing is not com to the comparison of the c	pletions: Attach we Ral. al. ral 4033'. TD of 98 11.6# SB80 LTC. Demented and is tied	Opposed to surface.
OTHER: 13. Describe proposed or composed we proposed completion or recurrence. Utilized synthetic oil-base mud system with the synthetic oil-base mud system. Which is sometimed and the system of the synthetic oil-base mud system. Which is synth	completion. em from intermediate casing point (1) 1/13. Landed lateral at 5795' on 2/1 858'. Milled window in 7" casing for diameter: 4 ½", production string to 9825'MD and float collar at 9809' kers for isolation of production string.	pertinent details, and C. For Multiple Com 5960') to TD of later 7/13. Length of late from 4858-4845'. In weight and grade: MD. Casing is not cong at the following details.	pletions: Attach we Ral. al. 11.6# SB80 LTC. Demented and is tied epths: (1) 9576' (2) 9	CVD MAR 4'13 IL CONS. DIV. DIST. 3 28'MD/5444'TVD Depth of 6 1/8" hole from back to surface.
OTHER: 13. Describe proposed or compof starting any proposed we proposed completion or reculous transfer of starting any proposed we proposed completion or reculous transfer of the starting any proposed we proposed completion or reculous transfer of the starting and proposed with the starting and proposed we proposed completion or reculous transfer of the starting and proposed we proposed we proposed we proposed with the starting any proposed or completion or reculous transfer of the starting any proposed or completion or reculous transfer of the starting any proposed or completion or reculous transfer of the starting any proposed we proposed completion or reculous transfer of the starting any proposed we proposed completion or reculous transfer of the starting any proposed we proposed completion or reculous transfer of the starting and the st	completion. em from intermediate casing point (1) 1/13. Landed lateral at 5795' on 2/1 858'. Milled window in 7" casing for diameter: 4 ½", production string to 9825'MD and float collar at 9809' kers for isolation of production string.	pertinent details, and C. For Multiple Com 5960') to TD of later 7/13. Length of late from 4858-4845'. In weight and grade: MD. Casing is not cong at the following details.	pletions: Attach we Ral. al. 11.6# SB80 LTC. Demented and is tied epths: (1) 9576' (2) 9	CVD MAR 4'13 IL CONS. DIV. DIST. 3 28'MD/5444'TVD Depth of 6 1/8" hole from back to surface.
OTHER: 13. Describe proposed or composed we proposed completion or recursive describing any proposed we proposed completion or recursive described and systems. Which is a second systems of the diameter of	completion. em from intermediate casing point (1) 1/13. Landed lateral at 5795' on 2/1 858'. Milled window in 7" casing for diameter: 4 ½", production string to 9825'MD and float collar at 9809' kers for isolation of production string.	pertinent details, and C. For Multiple Com 5960') to TD of later 7/13. Length of late from 4858-4845'. In weight and grade: MD. Casing is not cong at the following details.	pletions: Attach we Ral. al. 11.6# SB80 LTC. Demented and is tied epths: (1) 9576' (2) 9	CVD MAR 4'13 IL CONS. DIV. DIST. 3 28'MD/5444'TVD Depth of 6 1/8" hole from back to surface.
OTHER: 13. Describe proposed or composed we proposed completion or recurrence. Utilized synthetic oil-base mud system of lateral 4898'MD on 2/1 reached 2/24/13. Set whipstock at 4. Hole diameter: 6.1/8", production st 5257'MD to 9828'MD. Float shoe at Set 18 external swellable casing pact (5) 8630' (6) 8393' (7) 8160' (8) 792	completion. em from intermediate casing point (1) 1/13. Landed lateral at 5795' on 2/1 858'. Milled window in 7" casing for diameter: 4 ½", production string to 9825'MD and float collar at 9809' kers for isolation of production string.	pertinent details, and C. For Multiple Com 5960') to TD of later 7/13. Length of late from 4858-4845'. In weight and grade: MD. Casing is not cong at the following details.	pletions: Attach we Ral. al. 11.6# SB80 LTC. Demented and is tied epths: (1) 9576' (2) 9	CVD MAR 4'13 IL CONS. DIV. DIST. 3 28'MD/5444'TVD Depth of 6 1/8" hole from back to surface.
OTHER: 13. Describe proposed or composed we proposed completion or recursive describing any proposed we proposed completion or recursive described and systems. Which is a second systems of the diameter of	completion. em from intermediate casing point (1) 1/13. Landed lateral at 5795' on 2/1 858'. Milled window in 7" casing for diameter: 4 ½", production string to 9825'MD and float collar at 9809' kers for isolation of production string.	pertinent details, and C. For Multiple Com 5960') to TD of later 7/13. Length of late from 4858-4845'. In weight and grade: MD. Casing is not cong at the following details.	pletions: Attach we Ral. al. 11.6# SB80 LTC. Demented and is tied epths: (1) 9576' (2) 9	CVD MAR 4'13 IL CONS. DIV. DIST. 3 28'MD/5444'TVD Depth of 6 1/8" hole from back to surface.
OTHER: 13. Describe proposed or composed starting any proposed we proposed completion or reculous tracks of the second systems. Which is the second systems of the second syste	ork). SEE RULE 19.15.7.14 NMAC completion. em from intermediate casing point (19.13). Landed lateral at 5795' on 2/1858'. Milled window in 7" casing for the first diameter: 4 ½", production strint 19825'MD and float collar at 9809' kers for isolation of production strint (19) 7687' (10) 7451' (11) 7183' (11)	pertinent details, and C. For Multiple Com 5960') to TD of later 7/13. Length of later arom 4858-4845'. In gweight and grade: MD. Casing is not com g at the following de 2) 6950' (13) 6678' (pletions: Attach we al.	CVD MAR 4'13 IL CONS. DIV. DIST. 3 28'MD/5444'TVD Depth of 6 1/8" hole from back to surface.
OTHER: 13. Describe proposed or composed we proposed completion or recursive describing any proposed we proposed completion or recursive described and systems. Which is a second systems of the diameter of	completion. em from intermediate casing point (1) 1/13. Landed lateral at 5795' on 2/1 858'. Milled window in 7" casing fring diameter: 4 ½", production strint 19825'MD and float collar at 9809' kers for isolation of production strint 197 (19) 7687' (10) 7451' (11) 7183' (11) above is true and complete to the beautiful for the second of the seco	pertinent details, and c. For Multiple Com 5960') to TD of later 7/13. Length of later arom 4858-4845'. In weight and grade: MD. Casing is not c. g at the following de 2) 6950' (13) 6678' (13) 6678' (14)	pletions: Attach we al. al. 11.6# SB80 LTC. Emented and is tied epths: (1) 9576' (2) 914) 6407' (15) 6170 and belief.	OPPTH OF STREET
OTHER: 13. Describe proposed or composed starting any proposed we proposed completion or reculous tracks of the second systems. Which is the second systems of the second syste	completion. em from intermediate casing point (1) 1/13. Landed lateral at 5795' on 2/1 858'. Milled window in 7" casing fring diameter: 4 ½", production strint 19825'MD and float collar at 9809' kers for isolation of production strint 197 (19) 7687' (10) 7451' (11) 7183' (11) above is true and complete to the beautiful for the second of the seco	pertinent details, and C. For Multiple Com 5960') to TD of later 7/13. Length of later arom 4858-4845'. In gweight and grade: MD. Casing is not com g at the following de 2) 6950' (13) 6678' (pletions: Attach we al. al. 11.6# SB80 LTC. Emented and is tied epths: (1) 9576' (2) 914) 6407' (15) 6170 and belief.	CVD MAR 4'13 IL CONS. DIV. DIST. 3 28'MD/5444'TVD Depth of 6 1/8" hole from back to surface.
OTHER: 13. Describe proposed or compof starting any proposed we proposed completion or red Utilized synthetic oil-base mud system of starting any proposed we proposed completion or red Utilized synthetic oil-base mud system of system	above is true and complete to the beauty of the form of the structure of t	bertinent details, and c. For Multiple Com 5960') to TD of later 7/13. Length of later rom 4858-4845'. In gweight and grade: MD. Casing is not com g at the following dec 2) 6950' (13) 6678' (13) 6678' (14) (15) (15) (15) (15) (15) (15) (15) (15	pletions: Attach we Ral. al. 11.6# SB80 LTC. Demented and is tied pths: (1) 9576' (2) 9(14) 6407' (15) 6170 and belief.	CVD MAR 4'13 IL CONS. DIV. DIST. 3 28'MD/5444'TVD Depth of 6 1/8" hole from back to surface. 2339' (3) 9103' (4) 8866' ' (16) 5939' (17) 5525'
OTHER: 13. Describe proposed or composed was proposed completion or red Utilized synthetic oil-base mud system Kicked off lateral 4898'MD on 2/1 reached 2/24/13. Set whipstock at 4. Hole diameter: 6.1/8", production st 5257'MD to 9828'MD. Float shoe at Set 18 external swellable casing pact (5) 8630' (6) 8393' (7) 8160' (8) 792 (18) 4974'. Rig Released 2/25/13.	bork). SEE RULE 19.15.7.14 NMAC completion. em from intermediate casing point (state of the completion). 1/13. Landed lateral at 5795' on 2/1858'. Milled window in 7" casing for the case of the complete of the complete to the beautiful of the complete of the comp	bertinent details, and c. For Multiple Com 5960') to TD of later 7/13. Length of later rom 4858-4845'. In gweight and grade: MD. Casing is not com g at the following dec 2) 6950' (13) 6678' (13) 6678' (14) (15) (15) (15) (15) (15) (15) (15) (15	pletions: Attach we al. al. 11.6# SB80 LTC. Demented and is tied expths: (1) 9576' (2) 9 (14) 6407' (15) 6170 and belief. t	OPPTH OF STREET
OTHER: 13. Describe proposed or compof starting any proposed we proposed completion or red Utilized synthetic oil-base mud system of starting any proposed we proposed completion or red Utilized synthetic oil-base mud system of system	bork). SEE RULE 19.15.7.14 NMAC completion. em from intermediate casing point (state of the completion). 1/13. Landed lateral at 5795' on 2/1858'. Milled window in 7" casing for the case of the complete of the complete to the beautiful of the complete of the comp	bertinent details, and C. For Multiple Com 5960') to TD of later 7/13. Length of later at 4858-4845'. In gweight and grade: MD. Casing is not com g at the following de 2) 6950' (13) 6678' (13) 6678' (14) 6678' (15) 6678'	al. II.6# SB80 LTC. Demented and is tied epths: (1) 9576' (2) 9714) 6407' (15) 6170 and belief. t	CVD MAR 4'13 IL CONS. DIV. 28'MD/5444'TVD Depth of 6 1/8" hole from back to surface. 2339' (3) 9103' (4) 8866' (16) 5939' (17) 5525'