

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE
(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐		2005 SEP 20 AM 8 56	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐		RECEIVED	
2. NAME OF OPERATOR BURLINGTON RESOURCES OIL & GAS COMPANY		070 FARMINGTON NM	
3. ADDRESS AND TELEPHONE NO. PO Box 4289, Farmington, NM 87499 (505) 326-9700		9. API WELL NO. 30-039-20880-82357 C.2	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface Unit K (NESW), 1850' FSL & 1450' FWL At top prod. interval reported below SAME At total depth SAME		10. FIELD AND POOL, OR WILDCAT BASIN DK & BLANCO MV 11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Section 5, T27N, R5W, NMPM	
14. PERMIT NO.		DATE ISSUED	
12. COUNTY OR PARISH Rio Arriba		13. STATE New Mexico	
15. DATE SPUDDED 8-12-1962	16. DATE T.D. REACHED 9/1/1962	17. DATE COMPL. (Ready to prod.) 9/12/2005	18. ELEVATIONS (DF, RKB, RT, BR, ETC.) 6630' GL
20. TOTAL DEPTH, MD & TVD 7925'	21. PLUG, BACK T.D., MD & TVD 7868'	22. IF MULTIPLE COMPL., HOW MANY? 2	23. INTERVALS DRILLED BY ROTARY TOOLS CABLE TOOLS X
24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* Blanco Mesaverde 5725' - 4392'			25. WAS DIRECTIONAL SURVEY MADE NO
26. TYPE ELECTRIC AND OTHER LOGS RUN Gr/CBL/CCL			27. WAS WELL CORED No
28. CASING RECORD (Report all strings set in well)			
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE
9-5/8", H-40	32.3#	324'	12-1/4"
4-1/2"	10.5 & 11.6#	7920'	8-3/4"
29. LINER RECORD			
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*
			SCREEN (MD)
30. TUBING RECORD			
SIZE	DEPTH SET (MD)	PACKER SET	
2-3/8", 4.7# J-55	7746'	NONE	
31. PERFORATION RECORD (Interval, size and number)			
PTL-5424'-5725' = 25 holes CLH-5105'-5388' = 25 holes Lewis-4392' - 4620' = 25 holes total 75 holes			
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.			
DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED	
5424'-5725'		Acidiz'd; Frac'd w/10K gal 60% Slick & 100K# 20/40 sand	
5105'-5388'		Acidiz'd; Frac'd w/10K gal 60% Slick & 99K# 20/40 sand	
4392' - 4620'		Acidiz'd; Frac'd w/10K gal 75% slick & 200K# 20/40 sand	
33. PRODUCTION			
DATE FIRST PRODUCTION Not yet		PRODUCTION METHOD (Flowing, gas lift, pumping--size and type of pump) Flowing	
WELL STATUS (Producing or shut-in) SI			
DATE OF TEST 9/16/05	HOURS TESTED 1 hr	CHOKE SIZE 2"	PROD'N FOR TEST PERIOD OIL--BBL 0
GAS--MCF 36 MCF		WATER--BBL 0	
GAS-OIL RATIO			
FLOW. TUBING PRESS. SI - 364	CASING PRESSURE SI - 329	CALCULATED 24-HOUR RATE OIL--BBL 0	GAS--MCF 869 MCF/D
WATER--BBL 0		OIL GRAVITY-API (CORR.)	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold			TEST WITNESSED BY
35. LIST OF ATTACHMENTS This is a commingled MV/DK well being DHC'd per DHC 1848AZ			
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records			

SIGNED Patsy Christ TITLE Senior Regulatory Specialist

DATE 9/16/05

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

SEP 21 2005

FARMINGTON FIELD OFFICE

NMOCD

Ojo Alamo	2834'	2924'	White, cr-gr ss.	Ojo Alamo	2387'
Kirtland	2924'	3155'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	2504'
Fruitland	3155'	3426'	Dk gry-gr carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	3126'
Pictured Cliffs	3426'	3497'	Bn-Gry, fine grn, tight ss.	Pic. Cliffs	3357'
Lewis	3497'	5100'	Shale w/siltstone stringers	Lewis	3464'
Huerfanito Bentonite			White, waxy chalky bentonite	Huerfanito Bent.	3923'
Chacra			Gry fn grn silty, glauconitic sd stone w/drk gry shale	Chacra	4340'
Mesa Verde			Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	4946'
Menefee	5271'	5592'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	5188'
Point Lookout	5592'	5755'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	5537'
Mancos	5755'	6379'	Dark gry carb sh.	Mancos	5906'
Gallup	6379'	7519'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg. interbed sh	Gallup	6530'
La Ventana	XXXX	XXXX	Wt to lt buff to med grn sl carb bent	Greenhorn	7474'
Greenhorn	77519'	7573'	Highly calc gry sh w/thin lmst.	Graneros	7537'
Graneros	7573	7725'	Dk gry shale, fossil & carb w/pyrite incl.	Dakota	7562'
Dakota	7725'		Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks		