

OPERATOR [REDACTED]
FARMINGTON, NM 87401
PHONE: 599-3400

LOCATION INFORMATION

API NUMBER: 3003930889

TYPE OF LEASE:		LEASE NUMBER:	E-291-49
-----------------------	--	----------------------	-----------------

AMOUNT OF COKE: 50 BAGS

REV DMR 13 '12
OIL CONS. DIV.
DIST. 3

REMARKS:	
	COKE DEPTH 151'

Ca

COMPANY: CONOCO PHILLIPS
 COMPANY REP.: JOHN TAFOYA
 LOCATION: JOHNSTON A COM 7
 JOB NO.: 340140412
 FOREMAN: RON LUNA
 DRILLER: DARREL FERRIER

DATE: 2/28/2013
 DIA. HOLE: 7 7/8
 DEPTH: 300'
 COKE TYPE: SW
 # OF COKE: 50 BAGS
 # OF BENTONITE: 0

CASING: SCH40 PVC
 DIAMETER: 8"
 CASING DEPTH: 20'
 # OF ANODES: 10
 ANODE TYPE: 2284Z
 ANODE LEAD: HWMPE #8

corrpro®

RECTIFIER MFG: _____
 MODEL: _____
 SERIAL #: _____
 V-DC: _____ A -DC: _____

WELL LOG										ANODE PLACEMENT			
DEPTH FT.	DRILLERS LOG - SOIL TYPE	VOLTS	AMPS	COMMENTS / ANODE #	DEPTH FT.	DRILLERS LOG - SOIL TYPE	VOLTS	AMPS	COMMENTS / ANODE #	ANODE NO.	ANODE DEPTH	AMPS W/O COKE	AMPS W/ COKE
0	SANDSTONE	14.20		CASING	250	SHALE		1.80		1	277	3.70	5.60
5	SANDSTONE			CASING	255	SHALE		1.30	#3-257	2	267	1.70	4.80
10	SANDSTONE			CASING	260	SHALE		1.10		3	257	1.20	4.80
15	SHALE			CASING	265	SANDSTONE		1.30	#2-267	4	247	2.10	5.40
20	SHALE			CASING	270	SANDSTONE		2.80		5	237	1.60	5.50
25	TAN SANDSTONE				275	SANDSTONE		3.80	#1-277	6	227	1.70	5.40
30	TAN SANDSTONE				280	SANDSTONE		3.50		7	217	0.70	4.10
35	TAN SANDSTONE				285	SHALE		2.40		8	207	2.30	6.00
40	TAN SANDSTONE				290	SHALE				9	197	2.80	6.10
45	TAN SANDSTONE				295	SANDSTONE				10	187	1.00	3.80
50	TAN SANDSTONE				300	SANDSTONE				11			
55	TAN SANDSTONE				305					12			
60	TAN SANDSTONE				310				TD: 294'	13			
65	TAN SANDSTONE				315				VENT PIPE DEPTH: 300'	14			
70	TAN SANDSTONE				320					15			
75	TAN SANDSTONE				325					16			
80	TAN SANDSTONE		2.30		330					17			
85	SHALE		2.50		335					18			
90	SHALE		2.00		340					19			
95	SHALE		1.30		345					20			
100	SHALE		0.90		350					21			
105	TAN SANDSTONE		0.80		355					22			
110	TAN SANDSTONE		1.50		360					23			
115	TAN SANDSTONE		1.50		365					24			
120	TAN SANDSTONE		0.70		370					25			
125	TAN SANDSTONE		0.60		375								
130	TAN SANDSTONE		0.80		380								
135	TAN SANDSTONE		1.70		385								
140	TAN SANDSTONE		1.90		390								
145	SHALE		2.20		395								
150	SHALE		1.70		400								
155	TAN SANDSTONE		0.90		405								
160	TAN SANDSTONE		0.60		410								
165	TAN SANDSTONE		0.60		415								
170	TAN SANDSTONE		0.60		420								
175	TAN SANDSTONE		0.60		425								
180	TAN SANDSTONE		0.80		430								
185	TAN SANDSTONE		1.00	#10-187	435								
190	TAN SANDSTONE		1.70		440								
195	SANDY SHALE		2.90	#9-197	445								
200	SANDY SHALE		3.00		450								
205	SHALE		2.70	#8-207	455								
210	SHALE		1.90		460								
215	SHALE		1.10	#7-217	465								
220	SHALE		0.60		470								
225	SANDSTONE		1.10	#6-227	475								
230	SANDSTONE		1.80		480								
235	SHALE		1.50	#5-237	485								
240	SHALE		2.00		490								
245	SHALE		2.40	#4-247	495								

GROUND BED RESISTANCE

TOTAL VOLTS: 14.20
 TOTAL AMPS: 15.60
 0.91 OHMS

SITE ELEVATION: 6754
 WATER CONDUCTIVITY:
 COKE LEVEL: 151'
 EXTRA CASING USED:
 ADDITIONAL COMMENTS: