

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**CONFIDENTIAL**

FORM APPROVED  
OMB No. 1004-0137  
Expires: July 31, 2010

**SUNDRY NOTICES AND REPORTS ON WELLS**  
**Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.**

**SUBMIT IN TRIPLICATE - Other instructions on page 2.**

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		MAR 25 2013	5. Lease Serial No. NMNM 42059
2. Name of Operator Encana Oil & Gas (USA) Inc.		Farmington Field Office	6. If Indian, Allottee or Tribe Name N/A
3a. Address 370 17th Street, Suite 1700 Denver, CO 80202	3b. Phone No. (include area code) 720-876-5353	10. Field and Pool or Exploratory Area South Bisti-Gallup	7. If Unit of CA/Agreement, Name and/or No. N/A
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) SHL: 341' FSL and 837' FEL Sec 36, T24N, R10W BHL: 330' FSL and 730' FEL Sec 1, T23N, R10W		11. Country or Parish, State San Juan, NM	8. Well Name and No. Good Times P36A-2410 03H
		9. API Well No. 30-045-35450	

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other _____
	<input checked="" type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Encana Oil & Gas (USA) Inc. (Encana) would like to revise the hole sizes, casing sizes, and cement plans for the Good Times P36A-2410 03H well. Encana would like to change the intermediate hole size from 8 1/2" to 8 3/4" and change the cementing program to accommodate the hole size changes. Please see attached 10 point drilling plan and wellbore diagram. Drilling is estimated to commence on May 17, 2014.

**RCVD APR 10 '13**  
**OIL CONS. DIV.**  
**DIST. 3**

**BLM'S APPROVAL OR ACCEPTANCE OF THIS ACTION DOES NOT RELIEVE THE LESSEE AND OPERATOR FROM OBTAINING ANY OTHER AUTHORIZATION REQUIRED FOR OPERATIONS ON FEDERAL AND INDIAN LANDS**

**CONDITIONS OF APPROVAL**  
Adhere to previously issued stipulations.

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) Amie Weis	Title Drilling Engineer
Signature <i>Amie Weis</i>	Date 3/22/2013

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved by <i>Troy L. Salyers</i>	Title Petroleum Engineer	Date 4/2/2013
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office FFO	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**NMOCD A**

LOC: Sec 36-T24N-R10W County: San Juan WELL: Good Times P36A-2410 03H		Encana Natural Gas WELL SUMMARY						ENG: J. Fox/ A. 3/22/13 RIG: GLE: 6866 RKBE: 6879	
MWD LWD	OPEN HOLE LOGGING	FORM	DEPTH		HOLE SIZE	CASING SPECS	MW MUD TYPE	DEVIATION INFORMATION	
			TVD	MD					
			60	60'		20" 94# 100sx Type I Neat 48.8ppg cmt	Fresh wtr 8.3-9.2		
Surveys After csg is run	None		500	500		9 5/8" 36ppf J55 STC  TOC @ surface 178 sks Type III Cmt	Fresh wtr 8.4-8.6	Vertical <1°	
Surveys every 500'	No OH logs  Mud logger onsite	Ojo Alamo Kirtland  Fruitland Coal  Pictured Cliffs Ss Lewis Shale  Cliffhouse Ss Menefee Fn  Point Lookout Ss Mancos Sh  KICK OFF PT  Mancos Silt  Gallup Top	559 697  1009  1302 1461  2036 2599  3717 3899  4289  4429  4699 4950	5284	Stage tool @1350'	7" 26ppf J55 LTC  TOC @ surface 30% OH excess: 543 sks Total Stage 1 Lead: 253 sks Stage 1 Tail: 173 sks Stage 2 Lead: 117 sks	Fresh Wtr 8.5-8.8	Vertical <1°  KOP 4289 10 deg/100'	
Surveys every 500' Gyro at CP MWD Gamma Directional	No OH Logs	horz target  Base Gallup	4957 5034	5295		200' overlap at liner top  4712' Lateral  4 1/2" 11.6ppf SB80 LTC  Running external swellable csg packers for isolation of prod string Plan on setting top packer within 100' of intermediate casing shoe	8.6-9.0 OBM Switch to OBM 8.6-9.0	.25deg updip 4876' TVD TD = 10007' MD	

**NOTES:**

- 1) Drill with 30" bit to 60', set 20" 94# conductor pipe
- 2) Drill surface to 500', R&C 9 5/8" casing
- 3) N/U BOP and surface equipment
- 4) Drill to KOP of 4289', 8 3/4" hole size,
- 5) PU directional tools and start curve at 10deg/100' build rate
- 6) Drill to casing point of 5284' MD
- 7) R&C 7" casing, circ cmt to surface, switch to OBM
- 8) Land at 90deg, drill 4712' lateral to 10007', run 4 1/2" liner with external swellable csg packers

**Good Times P36A-2410 03H**  
**SHL: SESE Section 36, T24N, R10W**  
**341 FSL and 837 FEL**  
**BHL: SWSW Section 1, T23N, R10W**  
**330 FSL and 730 FEL**  
**San Juan County, New Mexico**  
**Lease Number: NM 42059**

**Encana Oil & Gas (USA) Inc.**  
**Drilling Plan**

**1. ESTIMATED TOPS OF GEOLOGICAL MARKERS (TVD)**

The estimated tops of important geologic markers are as follows:

<u>Formation</u>	<u>Depth (TVD)</u>
Ojo Alamo Ss.	559'
Kirtland	697'
Fruitland Coal	1009'
Pictured Cliffs	1302'
Lewis	1461'
Cliffhouse	2036'
Menefee	2599'
Point Lookout	3717'
Mancos Shale	3899'
Mancos Silt	4429'
Gallup	4699'

The referenced surface elevation is 6866', KB 6879'

**2. ESTIMATED DEPTH OF POTENTIAL WATER, OIL, GAS, & OTHER MINERAL BEARING FORMATIONS**

<u>Substance</u>	<u>Formation</u>	<u>Depth (TVD)</u>
Gas	Fruitland Coal	1009'
Gas	Pictured Cliffs	1302'
Gas	Cliffhouse	2036'
Gas	Point Lookout	3717'
Oil/Gas	Mancos	3899'

All shows of fresh water and minerals will be reported and protected.

**3. PRESSURE CONTROL**

- a) Pressure control equipment and configuration will be designed to meet 2M standards.
- b) Working pressure on rams and BOPE will be 3,000 psi
- c) Function test and visual inspection of the BOP will be conducted daily and noted in the IADC Daily Drilling Report.
- d) The Annular BOP will be pressure tested to a minimum of 50 percent of its rated working pressure.
- e) Blind and Pipe Rams/BOP will be tested against a test plug to 100 percent of rated working pressure.
- f) Pressure tests are required before drilling out from under all casing strings set and cemented in place.
- g) BOP controls must be installed prior to drilling the surface casing plug and will remain in use until the well is completed or abandoned.
- h) BOP testing procedures and testing frequency will conform to Onshore Order No. 2.

**Good Times P36A-2410 03H**

**SHL: SESE Section 36, T24N, R10W  
341 FSL and 837 FEL**

**BHL: SWSW Section 1, T23N, R10W  
330 FSL and 730 FEL**

**San Juan County, New Mexico**

**Lease Number: NM 42059**

- i) BOP remote controls shall be located on the rig floor at a location readily accessible to the driller. Master controls shall be on the ground at the accumulator and shall have the capability to function all preventers.
- j) The kill line shall be 2-inch minimum and contain two kill line valves, one of which shall be a check valve.
- k) The choke line shall be a 2-inch minimum and contain two choke line valves (2-inch minimum).
- l) The choke and manifold shall contain two adjustable chokes.
- m) Hand wheels shall be installed on all ram preventers.
- n) Safety valves and wrenches (with subs for drill string connections) shall be available on the rig floor at all times.
- o) Inside BOP or float sub shall also be available on the rig floor at all times.

Proposed BOP and choke manifold arrangements are attached.

**4. CASING & CEMENTING PROGRAM**

The proposed casing and cementing program has been designed to protect and/or isolate all usable water zones, potentially productive zones, lost circulation zones, abnormally pressured zones, and any prospectively valuable deposits of minerals. Any isolating medium other than cement shall receive approval prior to use. The casing setting depth shall be calculated to position the casing seat opposite a competent formation which will contain the maximum pressure to which it will be exposed during normal drilling operations. All indications of useable water shall be reported.

a) The proposed casing design is as follows:

Casing	Depth	Hole Size	Csg Size	Weight	Grade
Conductor	0-60'	30"	20"	94#	H40, STC New
Surface	0'-500'	12 1/4"	9 5/8"	36#	J55, STC New
Intermediate	0'-5284'MD	8 3/4"	7"	26#	J55, LTC New
Production Liner	5084'-10007'MD	6 1/8"	4 1/2"	11.6#	B80*, LTC New

Casing String				Casing Strength Properties			Minimum Design Factors		
Size	Weight (lb/ft)	Grade	Connection	Collapse (psi)	Burst (psi)	Tensile (1000lb)	Collapse	Burst	Tension
9 5/8"	36	J55	STC	2020	3520	394	1.125	1.1	1.5
7"	26	J55	LTC	4320	4980	367	1.125	1.1	1.5
4 1/2"	11.6	B80	LTC	6350	7780	201	1.125	1.1	1.5

\*B80 pipe specifications are attached

Casing design is subject to revision based on geologic conditions encountered.

All casing strings below the conductor shall be pressure tested to 0.22 psi per foot of casing string length or 1,500 psi, whichever is greater, but not to exceed 70 percent of the minimum internal yield. If pressure declines more than 10 percent in 30 minutes, corrective action shall be taken.

b) The proposed cementing program is as follows:

Top plugs shall be used to reduce contamination of cement by displacement fluid. A bottom plug or other acceptable technique, such as a pre-flush fluid, inner string cement method, etc. shall be utilized to help isolate the cement from contamination by the mud fluid being displaced ahead of the cement slurry.

**Good Times P36A-2410 03H**  
**SHL: SESE Section 36, T24N, R10W**  
**341 FSL and 837 FEL**  
**BHL: SWSW Section 1, T23N, R10W**  
**330 FSL and 730 FEL**  
**San Juan County, New Mexico**  
**Lease Number: NM 42059**

Casing	Depth	Cement Volume (sacks)	Cement Type&Yield	Designed TOC	Centralizers
Conductor	60'	100sk	Type I Neat 14.8 ppg	Surface	None
Surface	500'	178sk	Type III Cement + 1% CaCl + 0.25lb/sk Cello Flake + 0.2% FL, 14.6ppg, 1.38cuf/sk	Surface	1 per joint on bottom 3 joints
Intermediate	5284'MD	30% open hole excess Stage 1 Lead: 253sk Stage 1 Tail: 173sk Stage 2 Lead: 117sk	<b>Lead</b> (Stages 1 and 2): PremLite + 3% CaCl + 0.25lb/sk CelloFlake + 5lb/sk LCM, 12.1ppg 2.13cuf/sk <b>Tail</b> (Stage 1): Type III Cmt + 1% CaCl + 0.25lb/sk Cello Flake 14.5ppg 1.38cuf/sk	Surface	1 per joint for bottom 3 joints, 1 every 3 joints for remaining joints
Production Liner*	5084'-10007'	None – External casing packers	N/A	N/A	N/A

\*Production liner clarification: Utilizing external swell casing packer system for zonal isolation will not use cement in the production liner.

Actual volumes will be calculated and determined by conditions onsite. All cement slurries will meet or exceed minimum BLM and New Mexico Oil Conservation Division requirements. Slurries used will be the slurries listed above or equivalent slurries depending on service provider selected. Cement yields may change depending on slurries selected.

All waiting on cement times shall be a minimum of 8 hours or adequate to achieve a minimum of 500 psi compressive strength at the casing shoe prior to drilling out.

#### 5. WELL PLAN & DIRECTIONAL DRILLING PROGRAM

The proposed horizontal well will have a kick off point of 4289'. Directional plans are attached.

Description	Proposed Depth (TVD/MD)	Formation
Horizontal Lateral TD	4876'/10007'	Gallup

**Good Times P36A-2410 03H**

**SHL: SESE Section 36, T24N, R10W  
341 FSL and 837 FEL**

**BHL: SWSW Section 1, T23N, R10W  
330 FSL and 730 FEL**

**San Juan County, New Mexico**

**Lease Number: NM 42059**

**6. DRILLING FLUIDS PROGRAM**

a) Surface through Intermediate Casing Point:

Hole Size (in)	Depth (ft)	Mud Type	Density (lb/gal)	Viscosity (sec/qt)	Fluid Loss (cc)
30"	0-60' TVD	Fresh Water	8.3-9.2	38-100	4-28
12 1/4"	0-500' TVD	Fresh Water	8.4-8.6	60-70	NC
8 3/4"	500'TVD- 4950'TVD/5284'MD	Fresh Water LSND	8.5-8.8	40-50	8-10

b) Intermediate Casing Point to TD:

Hole Size (in)	MD (ft)	Mud Type	Density (lb/gal)	Viscosity (sec/qt)	Fluid Loss (cc)
6 1/8"	5284'-10007'	Synthetic Oil Based Mud	8.6-9.0	15-25	<15

- c) There will be sufficient mud on location to control a blowout should one occur. Mud flow and volume will be monitored both visually and with electronic pit volume totalizers. Mud tests shall be performed every 24 hours after mudding up to determine, as applicable: density, viscosity, gel strength, filtration, and pH.
- d) A closed-loop system will be used to recover drilling fluid and dry cuttings in both phases of the well and on all hole intervals, including fresh water and oil-based operations. Above-ground tanks will be utilized to hold cuttings and fluids for rig operations. A frac tank will be on location to store fresh water. Waste will be disposed of properly at an EPA-approved hazardous waste facility. Fresh water cuttings will be disposed of at Basin Disposal, Inc. and/or Industrial Ecosystems, Inc. The location will be lined in accordance with the Surface Use Plan of Operations.

**7. TESTING, CORING and LOGGING**

- a) Drill Stem Testing – None anticipated
- b) Coring – None anticipated.
- c) Mud Logging – Mud loggers will be on location from kick off point to TD.
- d) Logging – See Below

Cased Hole:

CBL/CCL/GR/VDL will be run as needed for perforating control

**8. ABNORMAL PRESSURES & HYDROGEN SULFIDE**

The anticipated bottom hole pressure is +/- 2320 psi based on a 9.0 ppg at 4957' TVD of the landing point of the horizontal lateral. No abnormal pressure or temperatures are anticipated.

No hydrogen sulfide gas is anticipated, however, if H<sub>2</sub>S is encountered, the guidelines in Onshore Order No. 6 will be followed.

**Good Times P36A-2410 03H**

**SHL: SESE Section 36, T24N, R10W  
341 FSL and 837 FEL**

**BHL: SWSW Section 1, T23N, R10W  
330 FSL and 730 FEL**

**San Juan County, New Mexico**

**Lease Number: NM 42059**

**9. ANTICIPATED START DATE AND DURATION OF OPERATIONS**

Drilling is estimated to commence on May 17, 2014. It is anticipated that completion operations will begin within 30 days after the well has been drilled depending on fracture treatment schedules with various pumping service companies.

It is anticipated that the drilling of this well will take approximately 25 days.