

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised August 1, 2011

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-043-21125
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Encana Oil & Gas (USA) Inc.		6. State Oil & Gas Lease No.
3. Address of Operator 370 17 th Street, Suite 1700 Denver, CO 80202		7. Lease Name or Unit Agreement Name Lybrook I32-2306
4. Well Location SHL: Unit Letter I: 1298 feet from the SOUTH line and 358 feet from the EAST line BHL: Unit Letter M: 400 feet from the SOUTH line and 330 feet from the WEST line Section 32 Township 23N Range 6W NMPM Sandoval County		8. Well Number 02H
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 282327
10. Pool name or Wildcat Lybrook Gallup		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE

OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

RCVD APR 22 '13
 OIL CONS. DIV.
 DIST. 3

Set surface casing string and cemented 4/15/13. Gelled freshwater system.

Hole diameter: 12.25", casing diameter: 9.625", casing weight and grade: 36ppf J55 LTC. Depth of 12.25" hole from 0' to 545'. Casing set from surface to 529'TVD/MD.

On 4/15/13 pumped 227 sks Type III Cement + 25#/sk Celloflake + 1% CaCl2 + 0.2% FL52A. Yield 1.38 cuft/sk. Mixed at 14.6 ppg. 10 bbls circ to surface. WOC 17 hours for surface casing.

Float collar at 482'. TOC at surface and BOC at 529'.

Tested BOP and casing 4/16/13. BOP pressure held to 3000# for 30 minutes. No pressure drop. Tested casing to 1500# for 30 minutes. No pressure drop. Started drilling out cement at 473'TVD/MD on 4/16/13.

Spud Date: 4/14/13

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robynn Haden TITLE Engineering Technologist DATE 4/18/13

Type or print name: Robynn Haden E-mail address: robynn.haden@encana.com PHONE: 720-876-3941

For State Use Only

APPROVED BY: Bob Bell TITLE Deputy Oil & Gas Inspector, District #3 DATE 4/26/13
 Conditions of Approval (if any): Av