

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-043-21125
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Encana Oil & Gas (USA) Inc.		6. State Oil & Gas Lease No.
3. Address of Operator 370 17 th Street, Suite 1700 Denver, CO 80202		7. Lease Name or Unit Agreement Name Lybrook 132-2306
4. Well Location SHL: Unit Letter I: 1298 feet from the SOUTH line and 358 feet from the EAST line BHL: Unit Letter M: 400 feet from the SOUTH line and 330 feet from the WEST line Section 32 Township 23N Range 6W NMPM Sandoval County		8. Well Number 02H
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 282327
		10. Pool name or Wildcat Lybrook Gallup

RCVD MAY 9 '13
OIL CONS. DIV.
DIST. 3

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Utilized synthetic oil-based mud system from intermediate casing point 5778' to TD of lateral.

Kicked off lateral at 4656' MD on 4/20/13. Landed lateral at 6417' on 4/26/13. Length of lateral 3787'. TD of 10,204' MD/5434' TVD reached 4/28/13. Set production liner 4/30/13.

Hole diameter: 6 1/8" production string diameter, 4 1/2" production string weight and grade: 11.6# SB80 LTC. Depth of 6 1/8" hole from 5858' MD to 10,204' MD Float shoe at 10,201' MD and float collar at 10,185' MD. Production liner set from 5578' MD to 10,201' MD.

Set 17 external swellable casing packers for isolation of production string at the following depths: (1) 9969' (2) 9707' (3) 9445' (4) 9224' (5) 8961' (6) 8700' (7) 8439' (8) 8217' (9) 7954' (10) 7691' (11) 7466' (12) 7200' (13) 6976' (14) 6709' (15) 6443' (16) 6177' (17) 5896'

Spud Date: 4/14/13

Rig Release Date: 4/30/13 ✓

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robynn Haden TITLE Engineering Technologist DATE 5/7/13

Type or print name: Robynn Haden

E-mail address: robynn.haden@encana.com

PHONE: 720-876-3941

For State Use Only

APPROVED BY: [Signature] TITLE Deputy Oil & Gas Inspector,
Conditions of Approval (if any) District #3 DATE 5/15/13
fv