



Spud – Set & PT Surface Casing Summary Report
Sullivan A #1F
API: 30-045-35372

- 7/31/13:** NOTE: Called NMOCD @ 7:00 p.m. and left a voice mail message notifying of intent to Spud.
- 8/1/13:** MIRU. RU Top Drive.
- 8/2/13:** Spud 12-1/4" surf hole @ 6:00 a.m. Drlg surf f/14.6'-810'. RU to run 8-5/8" csg. NOTE: Called Brandon Powell w/NMOCD w/csg & cmt notice @ 8:30 a.m.
- 8/3/13:** Ran 8-5/8", 24#, J-55 csg and set @ 803'. RD csg crew. RU cmt'rs. Cemented w/580 sx Premium cmt, (mixed @ 15.8 ppg & 1.17 cu/ft). Good initial returns. TD cementers. Cut off 8-5/8" collar, welded on csg head.
- 8/4/13:** Drlg cmt in 8-5/8" csg fr/25'-770'. RU WLU. Ran CBL. Located cmt top at 70'. RU Cmt'rs for 1" top off. NOTE: Called Brandon Powell w/NMOCD @ 8:30 p.m. w/press test & 1" cmt top off job.
- 8/5/13:** Ran 1" tbg dwn hole, tag @ 30'. Mix & pmp 100 sx Premium cmt, class G cmt. Cmt returns to surface. RD cementers. PT surface csg to 1500 psi, 30 min, tested OK. ✓ Cont to drill ahead.