Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

Lease Serial No. NMSF078902

☐ Temporarily Abandon ■ Water Disposal

SUNDRY N	OTICES AND REPORTS ON WELLS	
Do not use this	form for proposals to drill or to re-enter a	n
	Use form 3160-3 (APD) for such proposa	

Do not use the abandoned we SUBMIT IN TRI	EASTERN NA	6. If Indian, Allottee or Tribe Name EASTERN NAVAJO 7. If Unit or CA/Agreement, Name and/or No. 892000844F			
1. Type of Well Oil Well So Gas Well Ott 2. Name of Operator BP AMERICA PRODUCTION	GALLEGOS CAI 9. API Well No.	8. Well Name and No. GALLEGOS CANYON UNIT 147E 9. API Well No. 30-045-26283-00-S1			
3a. Address 200 ENERGY COURT FARMINGTON, NM 87401		3b. Phone No. (include area code Ph: 281-366-7148		10. Field and Pool, or Exploratory BASIN DAKOTA	
4. Location of Well (Footage, Sec., 7 Sec 4 T27N R12W NESW 18 36.601990 N Lat, 108.119660	1	11. County or Parish, and State SAN JUAN COUNTY, NM			
12. CHECK APP	ROPRIATE BOX(ES)	TO INDICATE NATURE OF	NOTICE, REPORT, OR OTH	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
☐ Notice of Intent Subsequent Report	☐ Alter Casing ☐ Frac		☐ Production (Start/Resume) ☐ Reclamation ☐ Recomplete	☐ Water Shut-Off ☐ Well Integrity ☑ Other	
Final Abandanment Notice	C'hanne Plans	□ Phys and Abandan	Tampararily Abandan	Workover Operations	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof.

If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

☐ Plug Back

□ Plug and Abandon

BP America Production Company would like to submit the revised daily operation summaries for the subject well. The document attached has the details of the workover operations for June 2013.

☐ Change Plans

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

☐ Convert to Injection

Please see attached revised document.

☐ Final Abandonment Notice

RCVD JUL 29'13 OIL CONS. DIV. DIST. 3

14. I hereby certify that the	e foregoing is true and correct. Electronic Submission #214828 verifie For BP AMERICA PRODUCTIO Committed to AFMSS for processing by ST	N ĆO,	sent to the Farmington					
Name (Printed/Typed)	TOYA COLVIN	Title	REGULATORY ANALYST					
Signature	(Electronic Submission)	Date	07/25/2013					
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								
Approved By ACCEPTED			STEPHEN MASON PETROLEUM ENGINEER	Date 07/25/2013				
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office	Farmington					
Title 18 II C Caction 100	Land Title 43 H S.C. Section 1212, make it a crime for any ne	rean kno	wingly and willfully to make to any departmen	at or agency of the United				

** BLM REVISED **

Recompletion Activities for the GCU 147E - June 2013

June 2013

06/05/2013- MOVE IN, SPOT IN EQUIPMENT, INSTALL DHB

06/06/2013- RIG UP UNIT, NIPPLE DOWN WELL HEAD, NIPPLE UP BOP, PRESSURE TEST BOP, PULL TBG HANGER AND 2WC, TAG FOR FILL

06/07/2013- TRIP OUT OF HOLE WITH PRODUCTION, TRIP IN HOLE WITH 7" CSG SCRAPER, LAY DOWN TBG, NIPPLE UP FRAC VALVE

06/10/2013- RIG UP E-LINE AND TEST, RUN CIBP IN HOLE AND SET 5880', LOAD HOLE WITH 230 BBLS OF CLAY TREAT AND PRESSURE TEST, RUN SEGMENTED BOND LOG F/5880' TO SURFACE.

06/11/2013- NIPPLE DOWN BOP, CHANGE OUT TBG HEAD, NIPPLE UP FRAC STACK AND TEST, MIT CSG, RIG DOWN AND PREP TO MOVE.

06/12/2013- MIT CSG, INSTALL TBG HANGER WITH 2WC, NIPPLE DOWN FRAC STACK, NIPPLE UP BOP, PRESSURE TEST BOP, PULL TBG HANGER AND 2WC.

06/13/2013- M/U PKR AND TRIP IN HOLE TO 2933' AND TEST, TRIP IN HOLE TO 5264' AND TEST BOTH SIDES

06/14/2013- HUNTING THE HOLE IN CASING FOUND THERE TO BE A LEAK (+/-3.3 PSI/MIN) BETWEEN +/-5264 AND +/- 2933' THAT WAS SUSPECTED TO BE THE DV TOOL OR POSSIBLY A COLLAR, NOT THE CASING. THERE WAS ALSO AN ADDITIONAL LEAK (+/-2 PSI/MIN) BETWEEN +/-5,800' AND THE CIBP AT +/-5880' SUSPECTED TO BE THE CIBP, LAY DOWN TBG AND PKR.

06/17/2013- RUN IN HOLE AND SET 7" CIBP @ 5470' (150' BELOW THE BOTTOM PLANNED PERFORATION FOR THE RECOMPLETION), PRESSURE TEST CSG AND CIBP, THE CASING DID NOT PASS THE PRESSURE TEST TO FRAC PRESSURE (3500 PSI) HOWEVER IT DID PASS THE PRESSURE TEST TO MAXIMUM EXPECTED RESERVOIR PRESSURE PLUS A SAFETY FACTOR (2000 PSI). THEREFORE, A SQUEEZE WAS NOT NECESSARY. INSTALL FRAC VALVE AND 3 ½ PIPE RAMS & TEST, RUN IN HOLE AND PERFORATE MANCOS 5307'-5325'.

06/18/2013- WAIT ON MAGNUM DISK, M/U FRAC BHA AND PICK UP FRAC STRING

06/19/2013- PICK UP FRAC STRING, SET PKR @ 5223' AND LAND FRAC STRING, WAS RUN AND SET AT +/-5,250 TO PROTECT THE CASING ABOVE THE FRAC INTERVAL FROM FRAC PRESSURES, PRESSURE TEST FRAC STRING AND CSG, NIPPLE DOWN BOP, NIPPLE UP FRAC STACK, PRESSURE TEST FRACK STACK

06/20/2013- PULL 2WC, PRESSURE TEST FRAC STRING, RUN SLICK LINE AND KNOCK OUT MAGNUM DISK, RIG DOWN, MOVE OFF LOCATION

06/21/2013- MI SPOT FRAC TANKS & FILL FRAC TANKS WITH WATER. MI SPOT SAFETY EQUIP. MO LOCATION