

RCVD OCT 23 '13

OIL CONS. DIV.

DIST. 9

API#: 30-043-20499

Form 9-331  
Dec. 1973Form Approved  
Budget Bureau No. 42UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☒ gas ☐ well ☐ other ☐2. NAME OF OPERATOR  
SUPERIOR OIL COMPANY3. ADDRESS OF OPERATOR  
P.O. DRAWER 'G', CORTEZ, COLO. 81321

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1753' FSL, 1883' FWL SEC. 35

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) ☐

SUBSEQUENT REPORT OF:

☒☐☐☐☐☐☐☐☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- Spudded 1-4-81. Drilled 16" hole to 83'. Ran 13-3/8", 48#, H-40 ST to 83'.
- 1-5-81: Drilled 12-1/4" hole to 306'. Ran 8 jts 9-5/8" csg. 36#, K-55, STC w/Davis Lynch float shoe and collar. Cemented w/177 sx Class 'B', 2% CaCl<sub>2</sub>, 1/4#/sk D-29 slurry 15.6#. Bump plug of mud at 500#. 4 BPM rate. Installed 9-5/8" slip on X 3000# FMC casing head. Tested to 1000#. Held OK. Circ good cement. DA.
- 1-16-81: Drilled 7-7/8" hole to 7335'. Ran GR-FDC-CNL, SP D to 7335'. Ran 172 5-1/2", 15.5#, K-55 LT&C, w/Davis Lynch shoe and collar. Dowell DV tool set at 8019'. Cemented w/405 sx of 50-50 lite pozmix, 2% gel, 6-1/4#/sx Gilsonite. Slurry wt 12.6#. Bump plug 1500#. OK. 2nd stage load slurry 235 sx, 65-35 lite pozmix w/6% gel and 6-1/4#/sx Gilsonite. Slurry wt 12.7#. Tailed in w/50 sx class 'B' neat 15.6#. Bump plug 700# 5-1/2 BPM rate. Tested plug to 2300#. Held OK. Had full returns thru out job.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Henry W. Haven TITLE Prod. Geologist DATE Jan 20, 1981

H. W. Haven

JAN 27 1981 (This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY

ORIG + 5 - USGS, Fmg, R. D. JOHNSON, G. A. BANNANTINE, J. E. HARRISON, G. D. JOHNSON,  
CENTRAL FILE - H, W, C, REG. GROUP

\*See Instructions on Reverse Side

FARMINGTON COPY