

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**
Sundry Notices and Reports on Wells

1. **Type of Well**
Oil Well

2. **Name of Operator**
Central Resources, Inc. c/o NMOCD Aztec District Office

3. **Address & Phone No. of Operator**
1000 Rio Brazos Road, Aztec, NM 87410 505-334-6178

4. **Location of Well, Footage, Sec., T, R, M**
1980' FSL and 740' FEL, Section 5, T-30-N, R-16-W,

5. **Lease Number**
BIA #14-20-603-733

6. **If Indian, All. or
Tribe Name**
Navajo

7. **Unit Agreement Name**
Horseshoe Gallup

8. **Well Name & Number**
HSGU #138

9. **API Well No.**
30-045-09890

10. **Field and Pool**
Horseshoe Gallup

11. **County & State**
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -


☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection



13. Describe Proposed or Completed Operations

A-Plus Well Service Plugged and Abandoned the above well NMSA 1978, Section 13-1-127, Purchase Agreement: 415210700028; Purchase Document: 05-199-000320.

1/5/05 MOL and RU rig. Well pressures: 0# tubing, 0# casing, 0# bradenhead. LD two rods. Shut in well.
1/6/05 NU BOP. ND wellhead. Hot oil rods and tubing. TOH and LD 41 - 5/8" rods. TOH and LD 34 joints 2.375" tubing. Round-trip 5.5" casing scraper to 988'. TIH with tubing and attempt to set 5.5" cement retainer at 988'. Unable to set CR; PU 1 joint of tubing and attempt to set CR again. PU 3 joints of tubing and push CR to bottom; release from CR at 1108'. Procedure change approved by H. Villanueva, NMOCD and BLM. Load casing with 30 bbls water and circulate well clean. Plug #1 with CR at 1108', spot 53 sxs Type III cement (70 cf) inside casing above CR up to 583' to isolate the Gallup interval. TOH and LD tubing. WOC.

1/7/05 RIH with wireline and tag cement at 648'. Pressure test to 500#; held OK. Perforate 3 holes at 185'. Establish circulation out bradenhead with water. Circulate BH annulus clean with 8 bbls of water. Plug #2 with 35 sxs Type III cement (42 cf), pump down the 5.5" casing from 185' to surface, circulate good cement out bradenhead. Shut in well and WOC. ND BOP. Dig out and cut off wellhead. Found cement at the surface in both the 5.5" casing and the annulus. Mix 5 sxs cement to fill casing and install P&A marker. RD and MOL.
H. Villanueva, NMOCD was on location.

SIGNATURE William F. Clark Contractor

January 15, 2005

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

OCT 03 2005

APPROVED BY _____ Title _____
CONDITION OF APPROVAL, if any:

Date _____
BY _____

NMOCD