State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.
For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

	Pit, Below-Grade Tank, or	
`	TALL AS INCIDENCE OF THE	

Propos	sed Alternative Method Pe	ermit or Closure Plar	Application
or proposed alter	Below grade tank registration □ Permit of a pit or proposed alter □ Closure of a pit, below-grade ta □ Modification to an existing perm □ Closure plan only submitted for native method See Submit one application (Form C-144)	ink, or proposed alternative m mit/or registration r an existing permitted or non	-permitted pit, below-grade tank,
			lution of surface water, ground water or the mental authority's rules, regulations or ordinances.
	T DREMATING, L.L.C.	OGRID#:	143199 77002
Facility or well name:	CARILLA CONTRACT 14	16 # 17E	
			ounty: NO ARRIBA
			3 € 7 . NAD: ☐1927 🗷 1983
	Private I Tribal Trust or Indian All	•	,
<u> </u>			DOUB CED C 14 O
☐ Pit: Subsection F, G or J of 19. Femporary: ☐ Drilling ☐ Workov			bil cons. bio.
• • •	vitation P&A Multi-Well Fluid	Management Low C	hloride Drilling Fluid ves no
	Thicknessmil LLDPE		· · · · · · · · · · · · · · · · · · ·
☐ String-Reinforced			
Liner Seams: Welded Factory	/ Other	Volume:bbl Di	mensions: Lx Wx D
I. X Below-grade tank: Subsection Volume:bt Fank Construction material:	of Type of fluid:		RCVD JAN 6'14 OIL CONS. DIV. DIST. 3
	detection Visible sidewalls, liner,	6-inch lift and automatic overflo	ow shut-off
☐ Visible sidewalls and liner 🗵 \	Visible sidewalls only 🗵 Other	EE CLOSURE PUAN	
Liner type: Thickness	mil 🔲 HDPE 🗌 PVC 🔣	Other BLT TO BE CL	osed per New Ruis
l.			
Alternative Method:			
Submittal of an exception request is r	equired. Exceptions must be submitted	to the Santa Fe Environmental	Bureau office for consideration of approval.
Fencing: Subsection D of 19.15.17.1	11 NMAC (Applies to permanent pits, te	emporary pits, and below-grade	(anks)
Chain link, six feet in height, two institution or church)	strands of barbed wire at top (Required	if located within 1000 feet of a p	permanent residence, school, hospital.
Four foot height, four strands of b	arbed wire evenly spaced between one a	and four feet	

Alternate. Please specify

4' HOG WIRE

6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other Macthematical (Knowling and approximation of the property of the propert	•
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
Signed in compnance with 15.15.10.6 NAVIAC	
8. Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acce	ntable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	piable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	☐ Yes 🗷 No
- MM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	li
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	
from the ordinary high-water mark).	Yes 🗷 No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes 🔀 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map, Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NM Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docu attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 N Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15 and 19.15.17.13 NMAC	nments are
11.	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following Items must be attached to the application. Please indicate, by a check mark in the box, that the documentation in the specific plan - based upon the appropriate requirements of 19.15.17.11 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanen't Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Feators Assessment	
 Climatological Factors Assessment □ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC □ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC □ Quality Control/Quality Assurance Construction and Installation Plan □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Nuisance or Hazardous Odors, including H₂S, Prevention Plan □ Emergency Response Plan □ Oil Field Waste Stream Characterization 	
Monitoring and Inspection Plan	
☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Falternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	Fluid Management Pit
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	:
is. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	rce material are Please refer to
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal fect of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incomposted municipal houndaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No								
Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No							
Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No							
Within a 100-year floodplain. FEMA map	☐ Yes ☐ No							
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC							
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with the	57							
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Genditions (see attachment) OCD Representative Signature: OCD Permit Number:	13							
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:	the closure report. complete this							
20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-log If different from approved plan, please explain.	op systems only)							
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicated in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude NAD: 1927								

I hereby certify that the information and attachments submitted with this closure report belief. I also certify that the closure complies with all applicable closure requirements	
Name (Print): WUBERL GARONER	Title: JR HSE SPECIALIST
Signature: WWW. J January	Date: 1-2-14
e-mail address: WEARONER RENERVESTONET	Telephone: 505-320-7924



New Mexico Office of the State Engineer Water Column/Average Depth to Water

No records found.

PLSS Search:

Section(s): 2, 3, 4, 9, 10, 11 Township: 25N Range: 05W

EnerVest Operating, LLC (EV)

BELOW-GRADE TANK CLOSURE PLAN

Rule 19.15.17.13

Well Name – Jicarilla Contract 146-17E API # 30-039-22175 Location UL- J, Sec 3, T-25N, R-5W Lat: N 36.42662 Lat: W -107.34387

Before June 15, 2013, EV shall close, retrofit, or replace an existing below-grade tank that has not demonstrated integrity.

EV shall close a below-grade tank within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the division requires because of imminent danger to fresh water, public health or the environment.

A. EV shall close an existing below-grade tank that does not meet the requirements of Subsection I, paragraphs (1) through (4), of 19.15.17.11 NMAC if not retrofitted to comply with said requirements prior to any sale or change of operator to 19.15.9.9 NMAC.

Any below-grade tank installed prior to June 16, 2008 that is single walled and where any portion of the tank sidewall is below the ground surface and not visible shall equip or retrofit the below-grade tank to comply with paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, or close it, within 5 years after June 16, 2008.

Within 60 days of cessation of the permitted below-grade tanks operation or as required by Subsection B of 19.15.17.17 NMAC, EV shall close the below-grade tank in accordance with a closure plan that the appropriate division district office approves.

Below grade tank was removed on or about August 16, 2013

B. Prior to implementing any closure operations EV shall research county tax records to determine the name and address of the surface owner of the properties involved. EV shall notify this surface owner via Certified U.S. Mail, return receipt requested, of their intent to close said below-grade tank.

Upon determination, EV will notify the appropriate district office verbally and in writing at least 72 hours but not more than one week prior to beginning work. Such notice shall contain at a minimum the following:

Operators Name Unit letter, Section, Township, & Range of well Well name and well number API Number of well Enervest Operating provided 72 hour notification to the state of New Mexico and the Jicarilla Tribal Environmental Protection Officer per regulations. See attached notification and responses

- C. Within 60 days of completion of closure operations, EV will file Form C-144, with attachments, outlining the detailed operations of the closing operations. Such attachments shall include, but not limited to, proof of surface owner and division notifications, confirmation of sampling analysis, disposal facility names and permit numbers, soil backfilling and cover installation, re-vegetation application rates and seeding techniques, and photo documentations.
- D. All free standing liquids and sludge will be removed at the start of the below-grade tank closure process from the below-grade tank and disposed of in one of the below division-approved facility as indicated below:

TNT Land Farm Permit # NM-01-0008 Liquids & Sludge Environtech Land Farm Permit # NM-01-0011 Solids AguaMoss Permit # 247130 Liquids

EV will obtain prior approval from the division to dispose, recycle, reuse, or reclaim the below-grade tanks and provide documentation of the final disposition of the below-grade tank in the closure report.

All material in the below grade tank was removed and disposed of at the T-N-T Land Farm (#NM-01-008). The interior of the tank was steam cleaned prior to removal. The tank was transported to the Enervest Jicarilla yard where it was inspected and recoated. The tank will be utilized at another location in the future.

Existing liners that are removed as a result of closure will be wiped cleaned and disposed of at a solid waste facility listed below in compliance with Subparagraph (M) of Paragraph (I) of Subsection C 19.15.35.8 NMAC..

San Juan Regional Landfill Permit # SWM 052426 or Special Waster Permit # SWM052433 "sp"

If there is any on-site equipment associated with a below grade tank, EV shall remove the equipment, unless the equipment is required for some other purpose.

Upon removal of the below-grade tank, EV will take, at a minimum, a five point composite sample from where the tank was sitting. EV shall collect individual grab samples will be taken from any area that is wet, discolored or showing other evidence of a release. All samples will be analyzed for the following:

Constituent	Method	Groundwater 51-100 FT	Test Results
		10,000	13.2
Chloride	EPA 300.0	mg/kg	mg/kg
	EPA SW-846		2270
TPH	Method 418.1	2,500 mg/kg	mg/kg
	EPA SW-846		
	Method 8021B		!
BTEX	or8260B	50 mg/kg	.15 mg/kg
	EPA -SW-846		
	Method 8021B or		
Benzene	8015M	10 mg/kg	.05 mg/kg
	EPA SW-846		
GRO/DRO	Method 8015B	1,000 mg/kg	300 mg/kg

The sample was analyzed by Envirotech Analytical Laboratory in Aztec NM. See attached laboratory report.

EV will insure that the results of all sampling shall be reported to the division on approved form C-141. EV understands that the division may require additional delineation upon review of the results.

If sampling demonstrates that concentrations specified above have NOT been exceeded, or that a release has NOT occurred, EV will backfill the excavation with compacted, non-waste containing, earthen material, construct a division prescribed soil cover, and recontour and re-vegetate the site. The division prescribed soil cover, recontouring, and re-vegetation shall comply with 19.15.17.13.

The excavation was back filled by Costilla Oil Field Services on November 6, 2013 utilizing soil that was already on location. The location was contoured to match the existing terrain. See attached photographs

If EV or the division determines that a release has occurred, EV shall fully comply with 19.15.29 NMAC and 19.15.30 NMAC as appropriate.

No release was observed. See the attached C-141 for details

E. Once EV has closed a below-grade tank, we shall reclaim the site to a safe and stable condition that blends with the surrounding undisturbed area. When possible, EV will restore the impacted surface area to the condition that existed prior to oil and gas operations by the placement of soil cover.

If the closed area is within the confines of the pad location EV will blend the site to match the pad location as much as possible. Such activities shall prevent erosion, protect fresh water, human health and the environment. EV will obtain written agreement from the surface owner for any alternate re-vegetation proposals and submit to the division for final approval.

The soil cover design will be consistent with the requirements of 19.15.17.13(H)(1) and (3). The soil cover will consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and prevent ponding of water and erosion of the cover material.

EV will seed the disturbed areas the first growing season after closing the below grade tank. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

EV shall notify the division when it has seeded or planted and when it successfully achieves re-vegetation.



Analytical Report

Report Summary

Client: Enervest Operating

Chain Of Custody Number: 15790

Samples Received: 8/22/2013 4:31:00PM

Job Number: 05123-0002 Work Order: P308069

Project Name/Location: 146-17E Separator Pit

Entire Report Reviewed By:

Date: 8/29/13

Tim Cain, Laboratory Manager

The results in this report apply to the samples submitted to Envirotech's Analytical Laboratory and were analyzed in accordance with the chain of custody document supplied by you, the client, and as such are for your exclusive use only. The results in this report are based on the sample as received unless otherwise noted. Partial or incomplete reproduction of this report is prohibited, unless approved by Envirotech, Inc. If you have any questions regarding this analytical report, please don't hesitate to contact Envirotech's Laboratory Staff.



Project Name:

146-17E Separator Pit

2700 Farmington Ave.

Project Number: Project Manager: 05123-0002

Reported:

Farmington NM, 87401

W Gardner

29-Aug-13 08:42

Analyical Report for Samples

Client Sample ID	Lab Sample ID	Matrix	Sampled	Received	Container
146-17E Separator Pit	P308069-01A	Soil	08/22/13	08/22/13	Glass Jar, 4 oz.





Project Name:

146-17E Separator Pit

2700 Farmington Ave. Farmington NM, 87401

Project Number:

05123-0002

Reported: 29-Aug-13 08:42

Project Manager:

W Gardner

146-17E Separator Pit P308069-01 (Solid)

		Reporting							
Analyte	Result	Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
Volatile Organics by EPA 8021									
Benzene	0.05	0.05	mg/kg	1	1334034	23-Aug-13	26-Aug-13	EPA 8021B	
Toluene	ND	0.05	mg/kg	1	1334034	23-Aug-13	26-Aug-13	EPA 8021B	
Ethylbenzene	ND	0.05	mg/kg	l	1334034	23-Aug-13	26-Aug-13	EPA 8021B	
p,m-Xylene	0.10	0.05	mg/kg	1	1334034	23-Aug-13	26-Aug-13	EPA 8021B	
o-Xylene	ND	0.05	mg/kg	1	1334034	23-Aug-13	26-Aug-13	EPA 8021B	
Total Xylenes	0.10	0.05	mg/kg	1	1334034	23-Aug-13	26-Aug-13	EPA 8021B	
Total BTEX	0.15	0.05	mg/kg	1	1334034	23-Aug-13	26-Aug-13	EPA 8021B	
Surrogate: Bromochlorobenzene		97.9 %	80-	120	1334034	23-Aug-13	26-Aug-13	EPA 8021B	
Surrogate: 1,4-Difluorobenzene		91.9%	80-	120	1334034	23-Aug-13	26-Aug-13	EPA 8021B	
Surrogate: Fluorobenzene		92.1 %	80-	120	1334034	23-Aug-13	26-Aug-13	EPA 8021B	
Nonhalogenated Organics by 8015									
Gasoline Range Organics (C6-C10)	10.0	4.99	mg/kg	1	1334033	23-Aug-13	27-Aug-13	EPA 8015D	
Diesel Range Organics (C10-C28)	290	4.99	mg/kg	1	1334033	23-Aug-13	27-Aug-13	EPA 8015D	
GRO and DRO Combined Fractions	300	4.99	mg/kg	1	1334033	23-Aug-13	27-Aug-13	EPA 8015D	
Total Petroleum Hydrocarbons by 418.1									
Total Petroleum Hydrocarbons	2270	20.0	mg/kg	1	1335008	27-Aug-13	27-Aug-13	EPA 418.1	- -
Cation/Anion Analysis									
Chloride	13.2	9.99	mg/kg	1	1335009	27-Aug-13	27-Aug-13	EPA 300.0	





Project Name:

146-17E Separator Pit

Spike

Source

2700 Farmington Ave.

Project Number:

Reporting

05123-0002

Reported:

%REC

Farmington NM, 87401

Project Manager: W Gardner

29-Aug-13 08:42

RPD

Volatile Organics by EPA 8021 - Quality Control

Envirotech Analytical Laboratory

		reporting		Opino					, u D	
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1334034 - Purge and Trap EPA 5030	Α									
Blank (1334034-BLK1)				Prepared: 2	23-Aug-13	Analyzed:	26-Aug-13			
Benzene	ND	0.05	mg/kg							
Toluene	ND	0.05	н							
Ethylbenzene	ND	0.05	n							
p,m-Xylene	ND	0.05	11							
o-Xylene	ND	0.05	"							
Total Xylenes	ND	0.05	н							
Total BTEX	ND	0.05	"							
Surrogate: Bromochlorobenzene	48.8		ug/L	50.0		97.6	80-120			
Surrogate: 1,4-Difluorobenzene	50.9		"	50.0		102	80-120			
Surrogate: Fluorobenzene	50.4		"	50.0		101	80-120			
Duplicate (1334034-DUP1)	Sour	ce: P308068-	-01	Prepared: 23-Aug-13 Analyzed: 26-Aug-13						
Benzene .	ND	0.05	mg/kg		ND				30	
Toluene	ND	0.05	и		ND				30	
Ethylbenzene	ND	0.05	и		ND				30	
o,m-Xylene	ND	0.05	"		ND				30	
o-Xylene	ND	0.05			ND				30	
Surrogate: Bromochlorobenzene	48.9		ug/L	50.0		97.7	80-120			
Surrogate: 1,4-Difluorobenzene	48.6		"	50.0		97.3 .	80-120			
Surrogate: Fluorobenzene	48.6		"	50.0		97.1	80-120			
Matrix Spike (1334034-MS1)	Sour	ce: P308068-	01	Prepared: 23-Aug-13 Analyzed: 26-Aug-13						
Benzene	2.45	0.05	mg/kg	2.50	ND	98.2	39-150			
Toluene	2.46	0.05	"	2.50	ND	98.5	46-148			
Ethylbenzene	2.45	0.05	**	2.50	ND	97.8	32-160			
p,m-Xylene	4.90	0.05	+	5.00	ND	98.1	46-148	•		
o-Xylene	2.46	0.05		2.50	ND	98.4	46-148			
Surrogate: Bromochlorobenzene	46.4		ug/L	50.0		92.8	80-120			
Surrogate: 1,4-Difluorobenzene	46.6		"	50.0		93.1	80-120			
Surrogate: Fluorobenzene	46.8		"	50.0		93.5	80-120			

Partial or incomplete reproduction of this report is prohibited, unless approved by Envirotech, Inc.

5796 US Highway 64, Farmington, NM 87401

Ph (505) 632-0615 Fx (505) 632-1865

Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301

Ph (970) 259-0615 Fr (800) 362-1879





Project Name:

146-17E Separator Pit

Spike

Source

%REC

2700 Farmington Ave. Farmington NM, 87401

Project Number: Project Manager:

Reporting

05123-0002 W Gardner **Reported:** 29-Aug-13 08:42

RPD

Nonhalogenated Organics by 8015 - Quality Control

Envirotech Analytical Laboratory

Analyte .	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1334033 - GRO/DRO Extraction	on EPA 3550C									
Blank (1334033-BLK1)				Prepared:	23-Aug-13	Analyzed:	27-Aug-13			
Gasoline Range Organics (C6-C10)	ND	4.99	mg/kg							
Diesel Range Organics (C10-C28)	ND	4.99	*							
GRO and DRO Combined Fractions	ND	4.99	**							
Duplicate (1334033-DUP1)	Source	e: P308068-	-01	Prepared:	23-Aug-13	Analyzed:	27-Aug-13			
Gasoline Range Organics (C6-C10)	ND	4.98	mg/kg		ND				30	
Diesel Range Organics (C10-C28)	ND	4.98	"		ND				30	
Matrix Spike (1334033-MS1)	Source	e: P308068-	-01	Prepared:	23-Aug-13	Analyzed:	27-Aug-13			
Gasoline Range Organics (C6-C10)	264	5.26	mg/kg	263	ND	100	75-125			
Diesel Range Organics (C10-C28)	269	5.26		263	ND	102	75-125			





Project Name:

146-17E Separator Pit

2700 Farmington Ave. Farmington NM, 87401

Project Number: Project Manager: 05123-0002

W Gardner

Reported:

29-Aug-13 08:42

Total Petroleum Hydrocarbons by 418.1 - Quality Control

Envirotech Analytical Laboratory

		Reporting		Spike	Source		%REC		RPD	
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1335008 - 418 Freon Extraction	···							-		
Blank (1335008-BLK1)				Prepared &	Analyzed:	27-Aug-13	.			
Total Petroleum Hydrocarbons	ND	20.0	mg/kg							
Duplicate (1335008-DUP1)	Sou	rce: P308068-	01	Prepared &	Analyzed:	27-Aug-13				
Total Petroleum Hydrocarbons .	24.0	20.0	mg/kg	·	ND				30	
Matrix Spike (1335008-MS1)	Sou	rce: P308068-	01	Prepared & Analyzed: 27-Aug-13						
Total Petroleum Hydrocarbons	1970	20.0	mg/kg	2000	ND	98.6	80-120			





Project Name:

146-17E Separator Pit

2700 Farmington Ave.

Project Number:

05123-0002

Reported:

Farmington NM, 87401

Project Manager:

W Gardner

29-Aug-13 08:42

Cation/Anion Analysis - Quality Control

Envirotech Analytical Laboratory

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch 1335009 - Anion Extraction EPA 300.0								<u></u>		
Blank (1335009-BLK1)				Prepared &	Analyzed:	27-Aug-13	1			
Chloride	ND	9.99	mg/kg		_					
Duplicate (1335009-DUP1)	Source	e: P308068-	01	Prepared &	Analyzed:	27-Aug-13	3			
Chloride	105	10.0	mg/kg		108			2.60	30	





Project Name:

146-17E Separator Pit

2700 Farmington Ave.

Project Number: Project Manager: 05123-0002

Reported: 29-Aug-13 08:42

Farmington NM, 87401

W Gardner

Notes and Definitions

DET

Analyte DETECTED

ND

Analyte NOT DETECTED at or above the reporting limit

NR

Not Reported

dry

Sample results reported on a dry weight basis

RPD

Relative Percent Difference



CHAIN OF CUSTODY RECORD

15790

Client:	17 1 N C		Project Name / Locat			n Q	 о Т		ANALYSIS / PARAMETERS													
Email results to:	71 11 18	_	Sampler Name:		 	<u>v (~)</u>	, , ,			£	<u> </u>											T
WGARDNER @ EN	ERVEST	NE	L. GAR	DNE	R				3015	802	826(ွ				-						
Client Phone No.: 505-320-7924			Client No.: 05 123 - 0002			TPH (Method 8015)	BTEX (Method 8021)	VOC (Method 8260)	RCRA 8 Metals	Cation / Anion		TCLP with H/P	CO Table 910-1	18.1)	3DE			S Cool	Intact			
Sample No./ Identification	Sample Date	Sam	' I Lab No.		/Volume ontainers	Pi HNO ₃	reservativ HCI	ve	TPH (N	BTEX (VOC (A	RCRA	Cation	RCI	TCLP v	CO Tat	TPH (418.1)	CHLORIDE			Sample Cool	Sample Intact
146-17 E SEPARATOR	8/20/13	14:1	P308069-61	\-	40%				Х	ζ.							X	X			√	
											•										-	
·																						
Relinquished by: (Signature)				Date	Time	Rece	ived by	y: (Siç	gnatu	ıre)										Date	Tir	ne
Relinquished by: (Signature)				8/22	\6:30	Rece	ent ived by	/: (Sig	7/2 gnátů	ire)	3 <i>a</i> n	<u></u>								8/22/E	16	<u>31</u>
			<u> </u>													 .	,				_	
Sample Matrix	Amazus T	1 04	[T]																			
Soil Solid Sludge Sudge Sample(s) dropped off after				<u>,</u>										***		_		,, <u>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>		<u> </u>	<u></u>	
envirotech Analytical Laboratory																						
5795 US Highway 64	Farmington	on, NM	87401 • 505-632-0615 •	Three Spi	ings • 65 i	Merca	do Stre	et, Su	ite 1	15, Du	urang	go, C	0 813	801 •	labor	atory	@en	virote	ch-inc.	com		

<u>District 1</u>
1625 N. French Dr., Hobbs, NM 88240
<u>District II</u>
811 S. First St., Artesia, NM 88210
<u>District III</u>
1000 Rio Brazos Road, Aztec, NM 87410
<u>District IV</u>

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

	OPERATOR	☐ Initial	Report X Final Report								
Name of Company Enervest Operating	Contact Lee Gardner										
Address 2700 Farmington Ave Building K, Suite #1	Telephone No. 505-325-0318										
Facility Name Jicarilla Contract 146-17E	Facility Type Oil & Gas Production										
Surface Owner Jicarilla Tribe Mineral Owne	er Jicarilla Tribe API No. 30-039-22175										
LOCATION OF RELEASE											
	th/South Line Feet from the	County Rio Arriba									
Latitude N. 36.42662 Longitude W -107.34387											
NATURE OF RELEASE											
Type of Release None	Volume of Release None		ecovered none								
Source of Release	Date and Hour of Occurren	ce Date and	Hour of Discovery								
Was Immediate Notice Given? ☐ Yes X☐ No ☐ Not	If YES, To Whom?										
Required											
By Whom?	Date and Hour										
Was a Watercourse Reached?	If YES, Volume Impacting	the Watercourse.									
☐ Yes X☐ No											
If a Watercourse was Impacted, Describe Fully.*											
Describe Cause of Problem and Remedial Action Taken.* Below grade tank excavation closure A five point composite sample was collect from the excavation and submitted analysis, the results are Benzene – .05 mg/kg (EPA Method 8021) BTEX – .15 mg/kg (EPA Method 8021) GRO/DRO – 300 mg/kg (EPA 8015) Total Petroleum Hydrocarbons – 2270 mg/kg (EPA Method 418.1) Chloride – 13.2 mg/kg (EPA Method 300.0)											
Describe Area Affected and Cleanup Action Taken.* No release was detected by analysis											
I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.											
OIL CONSERVATION DIVISION											
Signature: Del Handl											
Printed Name: Lee Gardner	Approved by Environmental Specialist:										
Title: Senior HSE Specialist	Approval Date:	Expiration I	Date:								
E-mail Address: wgardner@ enervest.net	Conditions of Approval:	Attached									
Date: 1-2-2014 Phone: 505-325-0318	/tudened										

Gardner, Wilbert

From:

Gardner, Wilbert

Sent:

Thursday, October 31, 2013 3:27 PM

To:

'Kelly, Jonathan, EMNRD'; 'Hobson Sandoval'

Cc:

Cross, Jeff; 'costillaoilfields@yahoo.com'; Greene, Roy; Trevino, Bart

Subject:

Enervest Operating 72 hour Notice of Below Grade Tank Excavation Closure

Attachments:

Soil Test Results 146-17E.pdf

Expires:

Saturday, February 08, 2014 12:00 AM

Gentlemen:

Enervest Operating is planning on closing the below grade tank excavation located on the Jicarilla Contract 146-17E on Wednesday November 6, 2013. The work will start at approximately 9:00 AM.

The API number for the location is 30-039-22175. The site is located at UL-J, Sec 3, T-25N, R-5W.

Attached is a copy of the soil test report for your examination

Thank you

Lee Gardner CHMM, CSP
Sr. HSE Specialist
Enervest Operating LLC
2700 Farmington, Bldg K, Suite #1
Farmington, NM 87401
Office 505-325-0318 Ext 13
Mobile 505-320-7924
Wgardner@enervest.net

Gardner, Wilbert

From:

Kelly, Jonathan, EMNRD [Jonathan.Kelly@state.nm.us]

To:

Sent:

Subject:

Gardner, Wilbert
Thursday, October 31, 2013 3:34 PM
Read: Enervest Operating 72 hour Notice of Below Grade Tank Excavation Closure

Your message was read on Thursday, October 31, 2013 4:34:00 PM (GMT-06:00) Central Time (US & Canada).



