

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

FEB 03 2014
SUDDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No. **SF-068990**
6. If Indian, Allottee or Tribe Name

1. Type of Well
 Oil Well Gas Well Other

7. If Unit of CA/Agreement, Name and/or No.
8. Well Name and No. **Shiotani Federal Com 400S**

2. Name of Operator **Burlington Resources Oil & Gas Company LP**

9. API Well No. **30-045-33183**

3a. Address **PO Box 4289, Farmington, NM 87499**

3b. Phone No. (include area code) **(505) 326-9700**

10. Field and Pool or Exploratory Area **Basin FC**

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Surface Unit F (SENW), 1780' FNL & 1470' FWL, Sec. 8, T29N, R12W

11. Country or Parish, State **San Juan New Mexico**

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA


TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once Testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Burlington Resources requests permission to P&A the subject well bore per the attached procedure, current & proposed well bore schematics. A Closed Loop system will be utilized for this P&A. This well is a FEE owner surface.

**Notify NMOCD 24 hrs
prior to beginning
operations**

**RCVD FEB 6 '14
OIL CONS. DIV.
DIST. 3**

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) **Kenny Davis** Title **Staff Regulatory Technician**
Signature  Date **2/3/2014**

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by **Original Signed: Stephen Mason** Title _____ Date **FEB 04 2014**
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Office _____

NMOCD

ConocoPhillips
SHIOTANI FEDERAL COM 400S
Expense - P&A

Lat 36° 44' 38.159" N

Long 108° 7' 30.691" W

PROCEDURE

This project requires a NMOCD C-144 CLEZ Closed-Loop System Permit for the use of an A-Plus steel tank to handle waste fluids circulated from the well and cement wash up.

1. Hold pre-job safety meeting. Comply with all NMOCD, BLM, and COPC safety and environmental regulations. Test rig anchors prior to moving in rig.
2. MIRU work over rig. Check casing, tubing, and bradenhead pressures and record them in Wellview. If there is pressure on the bradenhead, contact Wells Engineer.
3. When an existing primary valve (i.e. casing valve) is to be used, the existing piping should be removed and replaced with the appropriate piping for the intended operation.
4. RU blow lines from casing valves and begin blowing down casing pressure.
5. Unseat pump and kill well down tubing with at least tubing capacity of produced Fruitland Coal water.
6. ND wellhead and NU BOP. Pressure and function test BOP to 200-300 psi low and 1000 psi above SICP up to 2000 psi high as per COP Well Control Manual. PU and remove tubing hanger.
7. TOOH with tubing (per pertinent data sheet).

Tubing:	Yes	Size:	1.66"	Length:	1,699'
Tubing:	Yes	Size:	2-7/8"	Length:	1,713'

Round trip with a 3-7/8" bit and watermelon mill to the top perf @ 1,439' or as deep as possible above the perms.

All cement volumes use 100% excess outside pipe and 50' excess inside pipe. The stabilizing wellbore fluid will be 8.3 ppg, sufficient to balance all exposed formation pressures. All cement will be Class B/ASTM Type II mixed at 15.6 ppg with a 1.18 cf/sk yield.

9. Plug #1 (Pictured Cliffs, Perfs, and Fruitland tops : 1,389'-996', 34 sacks Class B cement)

Note: 10bbls cement circulated to surface during production cement job. TIH and set 4-1/2" CR on tubing at 1,389'. Pressure test tubing to 1000 psi. Sting out of CR and load and circulate casing clean, pressure test casing to 800 psi. TOOH with tubing. RIH with wireline and run CBL from 1,389' to surface under 500 psi pressure. Send CBL to Wells Engineer, Superintendent and Regulatory. Based on TOC, adjust plugs as needed to ensure cement coverage inside and outside of pipe for isolation. If casing does not test, tag plugs as necessary. TIH with tubing open ended or with cement plugging sub. Mix 34 sx Class B cement and spot a balanced plug inside casing to isolate the Pictured Cliffs, perforations, and Fruitland formation tops. PUH.

10. Plug #2 (Surface Casing Shoe, Ojo Alamo, and Kirtland tops: 496' – 0', 42 sacks Class B cement)


Connect the pump line to the bradenhead valve and attempt to pressure test the BH annulus to 300psi; note the volume to load. If the BH annulus holds pressure then establish circulation out casing valve with water. Mix 42 sx Class B cement and spot balanced plug inside casing from 496' to surface, circulating good cement out casing valve. TOOH and LD tubing. Shut in well and WOC. Shut well in and WOC.

11. Nipple down BOP and cut off casing below the casing flange. Install P&A marker with cement to comply with regulations. Rig down, move off location, cut off anchors, and restore location.

CURRENT SCHEMATIC SHOTANI FEDERAL COM #400S

District NORTH	Field Name BASIN (FRUITLAND COAL)	API / UWI 3004533183	County SAN JUAN	State/Province NEW MEXICO
Original Spud Date 2/8/2006	Surface Legal Location 008-029N-012W-F		E/W Dist (ft) 1,500.00	N/S Dist (ft) 1,775.00
			E/W Ref FWL	N/S Ref FNL


VERTICAL - Original Hole; 11/3/2013 1:17:10 PM



Well Name: **SHOTANI FEDERAL COM #400S**

API Well No. 3004533183	Surface Tag at Location 008-029N-012W-F	Field Name EASIN (FRUITLAND COAL)	License No. 11.00	State/Province NEW MEXICO	Well Configuration Type VERTICAL
Ground Elevation (ft) 5,660.00	Original KBRT Elevation (ft) 5,671.00	KB-Ground Distance (ft) 11.00	KB-Casing Flange Distance (ft) 5,671.00	KB-Tubing Flange Distance (ft) 5,671.00	

VERTICAL - Original Hole: 1/1/2020 12:15:00 AM



**GENERAL REQUIREMENTS FOR
PERMANENT ABANDONMENT OF WELLS ON FEDERAL AND INDIAN LEASES
FARMINGTON FIELD OFFICE**

1.0 The approved plugging plans may contain variances from the following minimum general requirements.

1.1 Modification of the approved plugging procedure is allowed only with the prior approval of the Authorized Officer, Farmington Field Office.

1.2 Requirements may be added to address specific well conditions.

2.0 Materials used must be accurately measured. (densimeter/scales)

3.0 A tank or lined pit must be used for containment of any fluids from the wellbore during plugging operations and all pits are to be fenced with woven wire. These pits will be fenced on three sides and once the rig leaves location, the fourth side will be fenced.

3.1 Pits are not to be used for disposal of any hydrocarbons. If hydrocarbons are present in the pit, the fluids must be removed prior to filling in.

4.0 All cement plugs are to be placed through a work string. Cement may be bull-headed down the casing with prior approval. Cement caps on top of bridge plugs or cement retainers may be placed by dump bailer.

4.1 The cement shall be as specified in the approved plugging plan.

4.2 All cement plugs placed inside casing shall have sufficient volume to fill a minimum of 100' of the casing, or annular void(s) between casings, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug.

4.3 Surface plugs may be no less than 50' in length.

4.4 All cement plugs placed to fill annular void(s) between casing and the formation shall be of sufficient volume to fill a minimum of 100' of the annular space plus 100% excess, calculated using the bit size, or 100' of annular capacity, determined from a caliper log, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug.

4.5 All cement plugs placed to fill an open hole shall be of sufficient volume to fill a minimum of 100' of hole, as calculated from a caliper log, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug. In the absence of a caliper log, an excess of 100% shall be required.

4.6 A cement bond log or other accepted cement evaluation tool is required to be run if one had not been previously run or cement circulated to surface during the original casing cementing job or subsequent cementing jobs.

5.0 All cement plugs spotted across, or above, any exposed zone(s), when; the wellbore is not full of fluid or the fluid level will not remain static, and in the case of lost circulation or partial returns during cement placement, shall be tested by tagging with the work string.

- 5.1 The top of any cement plug verified by tagging must be at or above the depth specified in the approved plan, without regard to any excess.
- 5.2 Testing will not be required for any cement plug that is mechanically contained by use of a bridge plug and/or cement retainer, if casing integrity has been established.
- 5.3 Any cement plug which is the only isolating medium, for a fresh water interval or a zone containing a prospectively valuable deposit of minerals, shall be tested by tagging.

6.0 Before setting any cement plugs the hole needs to be rolled. All wells are to be controlled by means of a fluid that is to be of a weight and consistency necessary to stabilize the wellbore. This fluid shall be left in place as filler between all plugs.

- 6.1 Drilling mud may be used as the wellbore fluid in open hole plugging operations.
- 6.2 The wellbore fluid used in cased holes shall be of sufficient weight to balance known pore pressures in all exposed formations.

7.0 A blowout preventer and related equipment (BOPE) shall be installed and tested prior to working in a wellbore with any exposed zone(s); (1) that are over pressured, (2) where the pressures are unknown, or (3) known to contain H₂S.

8.0 Within 30 days after plugging work is completed, file a Sundry Notice, Subsequent Report of Abandonment (Form 3160-5), five copies, with the Field Manager, Bureau of Land Management, 1235 La Plata Highway, Suite A, Farmington, NM 87401. The report should show the manner in which the plugging work was carried out, the extent, by depth(s), of cement plugs placed, and the size and location, by depth(s), of casing left in the well. Show date well was plugged.

9.0 All permanently abandoned wells are to be marked with a permanent monument as specified in 43 CFR 3162.6(d). Unless otherwise approved.

10.0 If this well is located in a Specially Designated Area (SDA), compliance with the appropriate seasonal closure requirements will be necessary.

All of the above are minimum requirements. Failure to comply with the above conditions of approval may result in an assessment for noncompliance and/or a Shut-in Order being issued pursuant to 43 CFR 3163.1. You are further advised that any instructions, orders or decisions issued by the Bureau of Land Management are subject to administrative review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4 and 43 CFR 4.700.