

Submit 1 Copy To Appropriate District Office -  
 District I  
 1625 N. French Dr., Hobbs, NM 88240  
 District II  
 1301 W. Grand Ave., Artesia, NM 88210  
 District III  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 October 13, 2009

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

WELL API NO. <b>30-031-20247</b>
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name <b>Hospah Sand Unit</b>
8. Well Number <b>#70</b>
9. OGRID Number <b>291567</b>
10. Pool name or Wildcat <b>Hospah</b>

**SUNDRY NOTICES AND REPORTS ON WELLS**  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well  Gas Well  Other

2. Name of Operator  
**Dominion Production Co. LLC**

3. Address of Operator  
**1414 W Swann, Suite 100, Tampa Fl. 33606**

4. Well Location  
 Unit Letter N : 800' feet from the South line and 1800' feet from the West line  
 Section 36 Township 18N Range 9W NMPM McKinley County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
**7000' GR**

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK  PLUG AND ABANDON   
 TEMPORARILY ABANDON  CHANGE PLANS   
 PULL OR ALTER CASING  MULTIPLE COMPL   
 DOWNHOLE COMMINGLE

SUBSEQUENT REPORT OF:

- REMEDIAL WORK  ALTERING CASING   
 COMMENCE DRILLING OPNS.  P AND A   
 CASING/CEMENT JOB

OTHER:

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.


10-31-2012- Mixed and Pumped 34 Sks, Class B Cement @ 15.4 ppg for bottom plug.  
 10-31-2013- Tagged Plug at 1345'. Mixed and Pumped 101 Sks, Class B Cement @ 17.5 ppg from 650' to 90' through 2 7/8" Tubing.  
 Pull Tubing, squeeze cement from 90' squeeze holes to surface.  
 Cut and Cap Casings at 3' feet from Surface  
 Place and Label P&A Marker  
 Clean & Level Location

RCVD MAR 5 '14  
 OIL CONS. DIV.  
 DIST. 3


Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE President DATE: 3-4-2014

Type or print name David Burns E-mail address: davidburns@dominionproduction.com PHONE: 832-545-4600  
**For State Use Only**

APPROVED BY:  TITLE Deputy Oil & Gas Inspector, District #3 DATE 3/11/14  
 Conditions of Approval (if any): AV

