

API/UWI 3004535066	Surface Legal Location 021-029N-009W-H	Field Name MV/DK COM	License No.	State/Province NEW MEXICO	Well Configuration Type VERTICAL
Ground Elevation (ft) 5,699.00	Original KBART Elevation (ft) 5,714.00	K5-Ground Distance (ft) 15.00	K5-Casing Flange Distance (ft)	K5-Tubing Hanger Distance (ft)	

OIL CONS. DIV DIST. 3
MAY 14 2014

MD (ft)

- 4,937.2
- 250.7
- 5.2
- 1.0
- 15.1
- 17.1
- 227.7
- 233.9
- 1,019.0
- 1,434.9
- 1,580.1
- 1,960.0
- 2,250.0
- 2,324.1
- 2,775.9
- 2,813.6
- 3,451.8
- 3,454.4
- 3,925.0
- 4,030.5
- 4,072.3
- 4,084.0
- 4,424.9
- 4,342.8
- 6,317.3
- 6,423.9
- 6,505.9
- 6,659.3
- 6,692.9
- 6,694.9
- 6,759.3
- 6,773.0
- 6,777.2
- 6,813.9

Vertical schematic (actual)

Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 15.0 ftKB;
6,659.7 ftKB

Tubing Pup Joint/Marker; 2 3/8 in; 4.70 lb/ft; J-
55; 6,659.7 ftKB; 6,661.7 ftKB

Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 6,661.7 ftKB;
6,692.9 ftKB

Profile Nipple/F-Nipple; 2 3/8 in; 4.70 lb/ft; J-55;
6,692.9 ftKB; 6,693.8 ftKB

Mule Shoe Guide; 2 3/8 in; 4.70 lb/ft; J-55;
6,693.8 ftKB; 6,694.8 ftKB

PETD; 6,760.0

Callout 1 (approx. 2,813.6 ft): This section contains detailed technical specifications and notes regarding the wellbore construction and equipment used.

Callout 2 (approx. 4,030.5 ft): This section provides information about the wellbore's structural integrity and the placement of various components.

Callout 3 (approx. 6,659.7 ft): This section describes the tubing and its properties, including weight and joint type.

Callout 4 (approx. 6,692.9 ft): This section details the profile nipple and its specifications.

Callout 5 (approx. 6,694.9 ft): This section discusses the mule shoe guide and its role in the wellbore.

Callout 6 (approx. 6,760.0 ft): This section mentions the PETD (Perforated Tubing Element) and its location.