Form 3160-5 (February 2005)

UNITED STATES DEPARTMENT OF THE INTERIOR

JUL 09 2014

FORM APPROVED OMB No. 1004-0137

| BUREAU OF LAND MANAGEMENT | | | | | | Expires: March 31, 2007 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|-------------------------------|-----------------------------|------------------------|------------------------------|------------------------------------|
| | | | | | 5. Lease S | |
| SUNDRY NOTICES AND REPORTS ON WELLS | | | | | | |
| Do not use this form for proposals to drill or to re-enter an | | | | | | |
| abandoned well. Use Form 3160-3 (APD) for such proposals. | | | | | 6. If India | n, Allottee or Tribe Name |
| SUBMIT IN TRIPLICATE – Other instructions on page ? | | | | | 7. If Unit | of CA/Agreement, Name and/or No. |
| 1. Type of Well | | | | | 1 | |
| OIL CONS. DIV DIST. 3 | | | | | 8. Well Name and No. | |
| M ∩il Well Gos Well Other | | | | I Chaco 2306-19E #205H | | |
| 2. Name of Operator | | | 2014 | 9. API Well No. | | |
| WPX Energy Production, LLC | | | | 30-043-21204 | | |
| 3a. Address 3b. Phone No. (include | | | * * * | | | |
| PO Box 640 Aztec, NM 87410 505-333-1806 | | | Lybrook Gallup | | | |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) | | | | | 11. Country or Parish, State | |
| SHL: 1801' FNL & 302' FWL, sec 19, T23N, R6W – | | | | Sandoval County, NM | | |
| BHL: 1396' FNL & 230' FEL, Sec 19, T23N, R6W | | | | | | |
| 12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA | | | | | | |
| TYPE OF SUBMISSION | TYPE OF ACTION | | | | | |
| Notice of Intent | Acidize | Deepen | | Produ (Start/Res | uction ' ume) | Water Shut-Off |
| | Alter Casing | Fracture Treat | | Recla | amation | Well Integrity |
| | | _ | | _ | | Other: INTERMEDIATE |
| | Casing Repair | New Construction | | Reco | mplete | CASING |
| Subsequent Report | | | | | | |
| (A) | I I Change Plans I I Pling and Abandon — | | Temp Abandon | mporarily n | | |
| Final Abandanment Notice | Convert to Injection | Plug Back | | | r Dienocal | |
| Final Abandonment Notice Convert to Injection Plug Back Water Disposal 13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of | | | | | | |
| all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| 6/26/14 - MIRU AWS #730 - note: 9-5/8" surface previously set @ 426' by MoTe on 4/5/14 | | | | | | |
| <u>6/27/14</u> – Drlg 388' – 646' | | | | | | |
| 6/28/14 - Drlg 646' - 987'. TOH to inspect bit & BHA, Hit 7" csg on 188H @ 778'-783'. Pressure test 7" csg on the 188H 1500# for 30 min, | | | | | | |
| lost 200#. CALL Jim Lovato, BLM & Brandon Powell, NMOCD @ 16:45 & 17:05, verbal approval to plug 205H back 50' into surface csg and | | | | | | |
| sidetrack | | | | | | |
| 6/29/14- Cmt balanced plug F/ 980' T/ 380' (TEST TOC) 25 Bbl FW AHEAD, 280sx CLASS G + 2% CaCl + 0.1% HR5 + 0.3% CFR3 + 3.86 wgps (50 Bbl, 280cf) (17 ppg, 1 Yld) DISPLACE W/ 4 Bbl FW. TOH 40 fpm TO 300', DP WAS DRY, CIRC BOTTOMS UP, NO CEMENT TO SURFACE. | | | | | | |
| DU DUI, ZOUCI J (17 PPE, 1 TIU / DISPLACE W/ 4 DUI FW. TOTI 40 IPIT TO 300, DE WAS DITT, CINC DOTTOWS OF, NO CLINENT TO SOM ACE. | | | | | | |
| 14 Thember and if what the foregoing | is true and appropri | | | | | |
| 14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) | | | | | | |
| Larry Higgins | | | Title Regulatory Specialist | | | |
| 1 14 5 | | | | | | |
| | | | | ate 7/9/14 | | |
| THIS SPACE FOR FEDERAL OR STATE OFFICE USE | | | | | | |
| Approved by Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify | | | | | | |
| | | | | Title | | Date |
| | | | hat | Office | | |
| the applicant holds legal or equitable title to those rights in the subject lease which would entitle the | | | | | | |
| applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212 make it a crime for any person knowingly and willfully to make to any dependence of the conduction of the | | | | | | |
| Title 19 II C Caction 1001 and Title | 43 IIS C Section 1212 mak | e it a crime for any person k | knowin | gly and willful | lly to make to | any dependent on a coco of the pin |

JUL 10 2014



United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Chaco 2306-19E #205H - Page 2

6/30 - 7/4/14 - Time drlg off plug and continue drilling intermediate hole.

7/5/14 - TD 8-3/4" intermediate hole @6048', 1300 hrs.

7/6/14 - Circ & CO hole

7/7/14 - Run 143 jts 7", 23#, J-55, LT&C csg, landed @ 6042' MD, FC @ 5997'. Cmt with 10 BBL FW SPACER, 40 BBL CHEM WASH, 20 BBL, 112 CF, 52sx

ELASTISEAL SCAVENGER (11.5ppg, 2.15 Yld + 12 WGPS) FOAMED LEAD = 710 SX ELASTISEAL (184.6 BBL, 1037 CF) + 2% CHEM - FOAMER 760 + 6.93 wgp (13ppg, 1.46 Yld) TAIL = 100SX ELASTISEAL (23.2 BBL, 130 CF) + 5.7 wgps (13.5ppg, 1.3 Yld) DROP PLUG & DISPLACE W/ 236.5 BBL, 20 BBL FW, 190 BBL DRLG MUD, 26.5 BBL FW. PLUG DN @ 19:31, 7/7/14. NO CEMENT TO SURFACE, ESTIMATED TOC -

SCAVENGER @ 420', ESTIMATED TOC FOAMED LEAD @ 1167'. DID NOT PUMP CAP CEMENT. Called Jim Lovato, BLM, @1945 hr. Jim said finish well and have completion run CAST bond log to pick TOC, Called Brandon Powell, NMOCD. Brandon wanted cementers to estimate TOC. Brandon Wood, Halliburton, estimated TOC scavenger @ 420', TOC foamed lead @ 1167'.

7-8-14 – Pressure test 7" csg and 4" pipe rams, 250 psi low for 5 min and 1500 psi high for 30 min. Good test, chart used.