District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Proposed Alternative Method Permit or Closure Plan Application Proposed Alternative Method Permit or Closure Plan Application Permit of a pit or proposed alternative method Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Permit of a pit or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Permit of a pit or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
ease be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
vironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
acility or well name:Atlantic LS 17
NPI Number:3004523574OCD Permit Number:
J/L or Qtr/QtrLSection24Township31NRange10WCounty:San Juan
Center of Proposed Design: Latitude36.881162 Longitude107.839832 NAD: ☐1927 ☑ 1983
surface Owner: 🔲 Federal 🔲 State 🔀 Private 🔲 Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC
'emporary: ☐ Drilling ☐ Workover ☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
String-Reinforced
iner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
olume:95.0bbl Type of fluid:Produced water
ank Construction material: Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Double walled/double bottomed
iner type: Thicknessmil
Alternative Method: ubmittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6. Notting: Subsection E of 10.15.17.11 NIMAC (Applies to payment pits and payment a payment pits.)	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	
	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
 initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC 	.15.17.9 NMAC
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC	
 Quality Control/Quality Assurance Construction and Installation Plan ○ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ○ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ○ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ○ Emergency Response Plan ○ Oil Field Waste Stream Characterization 	
 ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative	luid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	
Within a 100-year floodplain.	☐ Yes ☐ No
. FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	II NMAC 5.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: OCD Permit Number:	ø14
▼	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:8/6/2013	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this

Page 5 of 6

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirements.	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Rosse	Date:September 25, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Atlantic LS 17 Tank A BGT (95 bbl) API No. 3004523574 Unit Letter L, Section 24, T31N, R10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	2.3

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and will be reclaimed with the rest of the site since the well has been plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT will be reclaimed with the rest of the site as part of final reclamation since the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT will be reclaimed with the rest of the site as part of final reclamation since the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT will be reclaimed with the rest of the site as part of final reclamation since the well has been plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation since the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	eation	and Co	rrective A	ction	1			
						OPERA	ГOR		☐ Initia	al Report 🛛 Final Report		
Name of Co	mpany: B	P			(Contact: Jeff Peace						
		Court, Farmi	ngton, N	M 87401		Telephone No.: 505-326-9479						
Facility Nat	ne: Atlant	ic LS 17			ا	Facility Typ	e: Natural gas v	ve11				
Surface Ow	ner: Priva	te		Mineral C	wner: I	Private			API No	. 3004523574		
				LOCA	TION	OF REI	LEASE					
Unit Letter L	Section 24	Township 31N	Range 10W	Feet from the 1,680	North/South	South Line	Feet from the 965	East/V West	Vest Line	County: San Juan		
		Latit	ude36.	881162		_ Longitud	e_107.839832					
				NAT	URE	OF RELI	EASE					
Type of Rele			~				Release: N/A			tecovered: N/A		
Source of Re Was Immedia		v grade tank –	95 bbl, Ta	ank A			our of Occurrenc	e:	Date and	Hour of Discovery:		
was immedia	ate Notice (Yes	No 🛭 Not Re	quired	If YES, To	wnom?					
By Whom?						Date and I-						
Was a Watercourse Reached? ☐ Yes ☑ No ☐ If YES, Volume Impacting the Watercourse Reached?								ercourse.				
If a Watercou	irse was Im	pacted, Descr	be Fully.*									
		•	,									
				n Taken.* Samplii und chloride belov					g removal (o ensure no soil impacts from		
backfilled and	d compacte	d and will be i	reclaimed	with the rest of th	e site sin	nce the well h	as been plugged a	and abai	ndoned.	ne excavated area was		
regulations al public health should their of or the environ	I operators or the envi- operations had need. In a	are required to ronment. The lave failed to a	report an acceptance dequately CD accep	d/or file certain re e of a C-141 repo investigate and re	elease no rt by the emediate	otifications ar NMOCD made contamination	nd perform correctarked as "Final Reconstruction that pose a three	tive acti eport" d eat to gr	ons for rele oes not reli ound water	uant to NMOCD rules and cases which may endanger eve the operator of liability, surface water, human health ompliance with any other		
(00	0					OIL CON	SERV	ATION	DIVISION		
Signature:	1966	goes										
Printed Name) / / e: Jeff Peac	e			A	Approved by	Environmental S	pecialist	:			
Title: Area E	nvironment	al Advisor			A	Approval Dat	e:		Expiration l	Date:		
E-mail Addre	ess: peace.je	effrey@bp.com	n			Conditions of	Approval:			Attached		
Date: Septen	nber 25, 20)14	Pho	one: 505-326-947	9							

^{*} Attach Additional Sheets If Necessary

		 				
CHENT: BP	BLAGG ENGI	,		API#: 300	0452357	74
CLIENT:	P.O. BOX 87, BLOG (505) 6	OMFIELD, NM 532-1199	87413	TANK ID (if applicble):	A & D	
				(ii applicble)	7.00	
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELE	ASE INVESTIGATION / OT	HER:	PAGE#:	1 of	_1
SITE INFORMATION	: SITE NAME: ATLANTIC	LS #17		DATE STARTED:	07/29/	/13
QUAD/UNIT: L SEC: 24 TWP:	31N RNG: 10W PM: N	M CNTY: SJ	st: NM	DATE FINISHED:		
1/4-1/4/FOOTAGE: 1,680'S/965'W	NW/SW LEASE TYPE:	FEDERAL / STATE /	FEE INDIAN	ENVIRONMENTAL		
	PROD. FORMATION: PC CONTR	ELVHODN		SPECIALIST(S):	JCB	3
REFERENCE POINT	WELL HEAD (W.H.) GPS COO	RD.: 36.88137	7 X 107.83968	GL EL	EV.: 6,4 4	49 '
1) 95 BGT (DW/DB) - A		162 X 107.839832		ARING FROM W.H.:	87', S33.	
2) 21 BGT (CW/DD) B	GFS COORD. 36.001	 51 X 107.639538	DISTANCE/BE/	AKING PKOW W.H.:	-99' , 62 (CE
3)	GPS COORD.:		DISTANCE/BE/	ARING FROM W.H.:		
4)	GPS COORD.:		DISTANCE/BE/	ARING FROM W.H.:		
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB			· ·		OVM EADING
	·	IIALL		004 ED 10004 D104		(ppm)
1) SAMPLE ID: 95 BGT 5 - pt. @ 5					` '	0.0
2) SAIVIPLE TO					0.0(C)	0.0
3) SAMPLE ID:						
4) SAMPLE ID:		SAMPLE TIME: L	_AB ANALYSIS:			
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND	O / SILT SILTY CLAY / CI	LAY / GRAVEL / OTI	HER		
	ELLOWISH BROWN					
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC		PLASTICITY (CLAYS): NON PLA				
MOISTURE: DRY (SLIGHTLY MOIST) MOIST / WE		DENSITY (COHESIVE CL HC ODOR DETECTED				U
SAMPLE TYPE: GRAB COMPOSITE #		HC ODOR DETECTED	D. TES (INC) EXPL	ANATION		
DISCOLORATION/STAINING OBSERVED:	YES /NO EXPLANATION -					
<u></u>						
ANY AREAS DISPLAYING WETNESS: YES / NO		UO EVELANATION				
APPARENT EVIDENCE OF A RELEASE O ADDITIONAL COMMENTS:	BSERVED AND/OR OCCURRED: YES (NO EXPLANATION:				
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <50" N		XNA ft. AREST SURFACE WATER:	EXCAVATION EST	IMATION (Cubic Ya D TPH CLOSURE STI		JA ppm
SITE SKETCH	\oplus	PLOT PLAN circle	e: attached 0\M	CALIB. READ. = 100	D.1 ppm _{Pl}	RF = 1.00
	P& A		♦ low	CALIB. GAS = 10		.r - 1.00
	MARKER		N TIME	_ 9:52 amjpm	DATE: 07/29	//13
			· ` '	MISCELL	NOTE	<u> </u>
			١,	O: N15224		.0
				0. <u>1113224</u> 0#:	141	
			I —	K: ZFEIRK	05,15	
/A#\			· ·	J#: X7-0056		
(95) PBGTL→	$(\mathbf{x} \mathbf{x} \mathbf{x})$		_	ermit date(s):	06/02/10	0
T.B. ~ 5' B.G.	X		l	CD Appr. date(s):	06/28/11	
=141			Tar ID	k OVM = Organ	ic Vapor Meter	
			Ā	BGT Sidewalls Vis		
		X - S	S.P.D.	DCT Sidewelle Vie	ible V 🕦	_
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	N DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.	H. = TEST HOLE; ~ = APPROX.; W	/H. = WELL HEAD;	BGT Sidewalls Vis		
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELI	OW-GRADE TANK LOCATION; SPD = SAMPLE POINT DE	SIGNATION; R.W. = RETAINING V		lagnetic declina	tion: 10° E	Ξ
APPLICABLE OR NOT AVAILABLE; SW - SINGLE TRAVEL NOTES: CALLOUT:	WALL, DW - DOUBLE WALL, SB - SINGLE BOTTOM, DE		9/13			

Analytical Report

Lab Order 1307D69

Date Reported: 8/6/2013

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT 5-pt @ 5'

Project: Atlantic LS 17

Collection Date: 7/29/2013 11:15:00 AM

Lab ID: 1307D69-002

Matrix: SOIL

Received Date: 7/30/2013 10:01:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	E ORGANICS				Analyst	JME
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	8/2/2013 5:33:38 AM	8651
Surr: DNOP	73.5	63-147	%REC	1	8/2/2013 5:33:38 AM	8651
EPA METHOD 8015D: GASOLINE RA	NGE				Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	8/2/2013 12:46:32 AM	8655
Surr: BFB	87.4	80-120	%REC	1	8/2/2013 12:46:32 AM	8655
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.048	mg/Kg	1	8/2/2013 12:46:32 AM	8655
Toluene	ND	0.048	mg/Kg	1	8/2/2013 12:46:32 AM	8655
Ethylbenzene	ND	0.048	mg/Kg	1	8/2/2013 12:46:32 AM	8655
Xylenes, Total	ND	0.096	mg/Kg	1	8/2/2013 12:46:32 AM	8655
Surr: 4-Bromofluorobenzene	98.7	80-120	%REC	1	8/2/2013 12:46:32 AM	8655
EPA METHOD 300.0: ANIONS					Analyst	: JRR
Chloride	2.3	1.5	mg/Kg	1	8/2/2013 1:12:26 PM	8696
EPA METHOD 418.1: TPH		•			Analyst	LRW
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	8/1/2013	8654

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 2 of 7

- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1307D69

06-Aug-13

Client:

Blagg Engineering

Project:

Atlantic LS 17

Sample ID: MB-8696

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 8696

RunNo: 12405

Prep Date: 8/2/2013

Analysis Date: 8/2/2013

SeqNo: 353018

Units: mg/Kg

Analyte _ Chloride

Result ND

PQL 1.5

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD **RPDLimit**

Qual

Sample ID: LCS-8696

Client ID: LCSS

SampType: LCS

TestCode: EPA Method 300.0: Anions

RunNo: 12405

SeqNo: 353019

Units: mg/Kg

RPDLimit

Analyte

Prep Date: 8/2/2013 Analysis Date: 8/2/2013

PQL

1.5

Batch ID: 8696

SPK value SPK Ref Val %REC

96.0

90

LowLimit

HighLimit

%RPD

Qual

Chloride

14

15.00

110

Qualifiers:

Value exceeds Maximum Contaminant Level.

Е Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDIimit 0

RPD outside accepted recovery limits

В Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

Sample pH greater than 2 for VOA and TOC only.

RLReporting Detection Limit Page 3 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#:

1307D69

06-Aug-13

Client:

Blagg Engineering

Project:

Atlantic LS 17

Sample ID: MB-8654

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID: PBS

Batch ID: 8654

RunNo: 12331

Prep Date: 7/31/2013

Analysis Date: 8/1/2013

SeqNo: 350879

Units: mg/Kg

RPDLimit

Qual

Analyte

Result ND

PQL SPK value SPK Ref Val 20

%REC LowLimit

HighLimit

%RPD

Petroleum Hydrocarbons, TR

SampType: LCS

RunNo: 12331

SeqNo: 350880

TestCode: EPA Method 418.1: TPH

Sample ID: LCS-8654 Client ID: LCSS

Batch ID: 8654

Units: mg/Kg

120

Analyte

Result 99

Analysis Date: 8/1/2013 PQL 20

SPK value SPK Ref Val 100.0

%REC LowLimit 99.4 80 HighLimit

%RPD **RPDLimit** Qual

Qual

Petroleum Hydrocarbons, TR

Client ID: LCSS02

Prep Date: 7/31/2013

Prep Date: 7/31/2013

Sample ID: LCSD-8654

SampType: LCSD Batch ID: 8654

TestCode: EPA Method 418.1: TPH

RunNo: 12331 SeqNo: 350881

Units: mg/Kg

80

HìghLimit

RPDLimit %RPD

Petroleum Hydrocarbons, TR

Analysis Date: 8/1/2013 Result **PQL**

100

20

SPK value SPK Ref Val 100.0

%REC

101

120

1.38

20

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range

RSD is greater than RSDlimit 0

Analyte detected below quantitation limits

RPD outside accepted recovery limits

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н

ND Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit RL

Page 4 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#: 1307D69

06-Aug-13

Project:	
Sample ID:	MB-
Client ID:	PBS
Prep Date:	7/2
Analyte	

Surr: DNOP

Client:

Blagg Engineering Atlantic LS 17

SampT	ype: ME	BLK	TestCode: EPA Method 8015D: Diesel Range Organics						
Batch	n ID: 85	98	RunNo: 12312						
Analysis Date: 7/31/2013		SeqNo: 350434			Units: %REC				
Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
7.4		10.00		73.7	63	147			
	Batcl Analysis D Result	Batch ID: 85 Analysis Date: 7 Result PQL	Result PQL SPK value	Batch ID: 8598 F Analysis Date: 7/31/2013 S Result PQL SPK value SPK Ref Val	Batch ID: 8598 RunNo: 1: Analysis Date: 7/31/2013 SeqNo: 3: Result PQL SPK value SPK Ref Val %REC	Batch ID: 8598 RunNo: 12312 Analysis Date: 7/31/2013 SeqNo: 350434 Result PQL SPK value SPK Ref Val %REC LowLimit	Batch ID: 8598 RunNo: 12312 Analysis Date: 7/31/2013 SeqNo: 350434 Units: %RE Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit	Batch ID: 8598 RunNo: 12312 Analysis Date: 7/31/2013 SeqNo: 350434 Units: %REC Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD	Batch ID: 8598 RunNo: 12312 Analysis Date: 7/31/2013 SeqNo: 350434 Units: %REC Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit

Sample ID: LCS-8598	SampT	ype: LC	s	TestCode: EPA Method 8015D: Diesel Range Organics										
Client ID: LCSS	Batch	ID: 85	98	F	RunNo: 1	2312								
Prep Date: 7/29/2013	Analysis D	31/2013	\$	SeqNo: 3	50435	Units: %RE								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Surr: DNOP	3.5		5.000		70.2	63	147							

Sample ID: MB-8651	TestCode: EPA Method 8015D: Diesel Range Organics											
Client ID: PBS	ID: PBS Batch ID: 8651 RunNo: 12312											
Prep Date: 7/31/2013 Analysis Date: 8/2/2013			S	SeqNo: 3	51592	Units: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range Organics (DRO)	ND	10										
Surr: DNOP	7.2		10.00		71.8	63	147					

Sample ID: LCS-8651	Sampl	Гуре: LC	s	TestCode: EPA Method 8015D: Diesel Range Organics									
Client ID: LCSS	Batc	h ID: 86 :	51	F									
Prep Date: 7/31/2013	Analysis [Analysis Date: 8/2/2013 Seq				51593	Units: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Diesel Range Organics (DRO)	37	10	50.00	0	73.4	77.1	128			S			
Surr: DNOP	3.0		5.000		59.9	63	147			S			

Sample ID: LCS-8651	Tes	tCode: El	PA Method	8015D: Dies	el Range C	Organics						
Client ID: LCSS	Batch	n ID: 86 9	51	F	RunNo: 1:	2371						
Prep Date: 7/31/2013	Analysis D	oate: 8/	2/2013	S	SeqNo: 3	52158	Units: mg/Kg					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range Organics (DRO)	46	10	50.00	0	92.5	77.1	128					
Surr: DNOP	4.1		5.000		81.4	63	147					

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Ē Value above quantitation range
- Analyte detected below quantitation limits
- 0 RSD is greater than RSDlimit
- RPD outside accepted recovery limits

- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2 for VOA and TOC only.
- Reporting Detection Limit

Page 5 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#:

1307D69

06-Aug-13

Client:

Blagg Engineering

Project:

Atlantic LS 17

Sample ID: MB-8655	Samp1	ype: ME	BLK	Tes	TestCode: EPA Method 8015D: Gasoline Range										
Client ID: PBS	Batcl	h ID: 86	55	F											
Prep Date: 7/31/2013	Analysis [Date: 8/	1/2013	S	51757	Units: mg/K	(g								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Gasoline Range Organics (GRO)	ND	5.0								-					
Surr: BFB	880		1000		88.4	80	120								

Sample ID: LCS-8655	Samp	Гуре: LC	S	TestCode: EPA Method 8015D: Gasoline Range										
Client ID: LCSS	Batc	h ID: 86	55	F										
Prep Date: 7/31/2013	Analysis [Date: 8/	1/2013	8	51758	Units: mg/h	(g							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Gasoline Range Organics (GRO)	27	5.0	25.00	0	107	62.6	136							
Surr: BFB	960		1000		96.2	80	120							

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 6 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#:

1307D69 06-Aug-13

Client: Project: Blagg Engineering

Atlantic LS 17

Sample ID: MB-8655	Samp	Гуре: МЕ	BLK	Tes	TestCode: EPA Method 8021B: Volatiles								
Client ID: PBS	Batc	h ID: 86	55	F	RunNo: 1:	2346							
Prep Date: 7/31/2013	Analysis [Date: 8 /	1/2013	SeqNo: 3517			Units: mg/K	g					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	ND	0.050			-								
Toluene	ND	0.050											
Ethylbenzene	ND	0.050											
Xylenes, Total	ND	0.10											
Surr: 4-Bromofluorobenzene	1.0		1.000		100	80	120						
Sample ID: LCS-8655	Samp	ype: LC	s	Tes	tCode: El	PA Method	8021B: Volat	iles					
Client ID: LCSS	Batcl	h ID: 86 9	55	F	RunNo: 12								

Sample ID: LCS-8655	Samp	Type: LC	s	Tes						
Client ID: LCSS	Bato	h ID: 86	55	F	RunNo: 1	2346				
Prep Date: 7/31/2013	Analysis I	Date: 8/	1/2013	5	SeqNo: 3	51798	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.0	0.050	1.000	0	100	80	120		-	
Toluene	0.97	0.050	1.000	0	96.7	80	120			
Ethylbenzene	0.98	0.050	1.000	0	98.1	80	120			
Xylenes, Total	2.9	0.10	3.000	0	98.3	80	120			
Surr: 4-Bromofluorobenzene	1.0		1.000		120					

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range E
- Analyte detected below quantitation limits
- RSD is greater than RSDIimit 0
- RPD outside accepted recovery limits

- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2 for VOA and TOC only.
- Reporting Detection Limit

Page 7 of 7



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name:	BLAGG	Work Orde	r Number:	1307D69	9			RcptN	lo: 1
Received by/dat	ME	7/30/2013 10	173 :01:00 AM			Sincely 44	Homen		
Logged By:	Lindsay Man						// ~		
Completed By:	Lindsay Man					Janes Ly 4	HayaysD		
Reviewed By:	TO	67/31/							
Chain of Cus	tody								_
1. Custody sea	als intact on sam	ple bottles?		Yes		No		Not Present ▼	•
2. Is Chain of C	Custody complet	e?		Yes ¥	•	No	. !	Not Present	
3. How was the	e sample deliver	ed?		Courier					
Log In									
4. Was an atte	empt made to co	ol the samples?		Yes A	•	No		NA:	:
5. Were all sar	mples received a	at a temperature of >0° C to 6.	.0°C	Yes 🗸	r i	No	i	NA	
6. Sample(s) i	n proper contain	er(s)?		Yes 🦠	∕ !	No	:		
7. Sufficient sa	ample volume for	r indicated test(s)?		Yes •	į.	No			,
8. Are samples	(except VOA a	nd ONG) properly preserved?		Yes ¥	/	No	٠		
9. Was preserv	vative added to I	pottles?		Yes		No	✓	NA	
10.VOA vials h	ave zero headsp	pace?		Yes		No	:	No VOA Vials 🔻	/ .
11. Were any s	ample container	s received broken?		Yes		No	v	# =6 =4000=110d	
							:	# of preserved bottles checked	
	work match bottl			Yes •	/ :	No	: .	for pH:	2 or >12 unless noted)
•	pancies on chai	**		Yes :	/ .	No	: :	Adjusted?	2 or - 12 unless notedy
14. Is it clear wh		fied on Chain of Custody?		Yes V		No	:	-	
15. Were all hol				Yes V	_	No	i	Checked by	y:
	customer for au								
Special Hand	lling (if appl	icable)							
16. Was client n	notified of all disc	crepancies with this order?		Yes	:	No	:	NA N	•
Perso	n Notified:		Date:			an night of the state of the st	unany		
By Wi	nom:		Via:	eMail		hone	Fax	In Person	
Regar	ding:	Parama Maria (1801) (1801) (1801) (1801) (1801) (1801) (1801) (1801) (1801) (1801) (1801) (1801) (1801) (1801)	*********************	chiamaina is.		NAME OF TAXABLE PARTY.			P
Client	Instructions:			78.17 7.15 67 68 17 68 47 69 181	de Were de de				•
17. Additional r	emarks:								
18. Cooler Info	ormation								
Coaler N	lo Temp °C	Condition Seal Intact Sea	al No 5	Seal Date	=	Signed E	Зу		
	1				'				

С	hain-	of-Cu	stody Record	Turn-Around	Turn-Around Time:										NEX.		20	ni s	a e	BIT	'AL	
Client:	3LAGG	, ENGIN	EERNG INC.	Standard		<u> </u>			(784)												AL OR'	
T	ζ Αζ	480. CA		Project Name):										rironi							•
Mailing	Address	P.O. P	20x 97	ATLANTIC	LS 17				490)1 Ha									109			
- R	LOMF	VECD N	M 87413	Project #:	· · · · · · · · · · · · · · · · · · ·					1. 50					-	•		410				
Phone #			32-1199						#				Α	nály	/sis	Req	uesi				ts.	
email o				Project Mana	ger:			_	only)	\$					(ہر							
QA/QC F	Package: dard		☐ Level 4 (Full Validation)	J. B.	ALI		!	∓₩B's (8021)	(Gas o	(O / MRG)			IMS)		PO4,S	PCB's						
Accredi	tation	□ Othe	r	Sampler: J			i de la companya de	E HATE	+ TPH (Gas	(GRO / DRO	18.1)	04.1)	8270 S		3,NO ₂ ,	/ 8082		A)	_			(S)
□ EDD	(Type)_			Sampleslein	je kujijese (MTBE -	9	b 4	2d 5	o or	tals	N.	ides	₽	0/-	W			\ <u>\</u>
Date	Time	Matrix	Sample Request ID	ļ	Preservative Type			BTEX + ANTEE	BTEX + MT	TPH 8015B	TPH (Method 418.1)	EDB (Method 504.1)	PAH's (8310 or 8270 SIMS)	RCRA 8 Metals	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE			Air Bubbles (Y or N)
70/5	27.47	Soil	21 BGT /	(32)4 (_ المحادث			SZ		X	×	_							*			1
11	1115	##	5-PE @ 6 95 BGT 5-PE @ 5	u	14	$-\Delta \Omega Z$		X		-+	X	_							X		+	+
	1113		3-pe @ 3	12			<u> </u>					_								+	+	+
											\dashv									+	\dashv	+
		-								-+	\dashv									+	_	+
	<u> </u>	-									_								-	+	\dashv	+
										1									\dashv	+	+	+-
				<u> </u>						-	-									+		+
										-	\dashv			-					\dashv	+	_	+
											\dashv	\dashv				\vdash			-	+	+	+
	ļ								_		\dashv	\dashv								+	+	+
				<u> </u>							\dashv								-	\dashv	+	十
Date:	Time:	Relinquish	ed by: [Slogg	Received by: Onte Time 727213 1150				Ren	l narks	<u>_</u>			B		اا			~ 	<u> </u>			
Date:	Time:	Relinquish	_	Received by:	1	Date Tim	,									_		SJ	5			
129/3	1750	1/ <u> </u>	tu Wale			30/13/10		L	.014.						對千							
, ,	t necessary,	samples sub	mitted to Hall Environmental may be sub	contracted to other a	credited laboratori	es. This serves as not	ice of this	possit	oility. A	any sub	o-contr	racted	data	wiii be	clear	y nota	ted on	the ar	alytica	report.	•	



