District I 1625 N. French Dr., Hobbs, NM 88240 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

### State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe. NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

<u>Pit, Below-Grade Tank, or </u>	
Proposed Alternative Method Permit or Closure Plan Application	. CONS. DIV DIST.
Type of action:   Below grade tank registration	
45-26438 Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method	NOV 0 5 2014
95 - 20 9 50 Closure of a pit, below-grade tank, or proposed alternative method	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
☐ Modification to an existing permit/or registration	
Closure plan only submitted for an existing permitted or non-permitted pit, belo	w-grade tank,
or proposed alternative method	

Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. Operator: XTO Energy, Inc. OGRID #: 5380 Address: 382 Road 3100, Aztec, New Mexico 87410 Facility or well name: OH Randel # 11 API Number: 30-045-26438 OCD Permit Number: U/L or Qtr/Qtr J Section 10 Township 26N Range 11W County: San Juan Center of Proposed Design: Latitude <u>36.49753</u> Longitude <u>-107.98853</u> NAD: □1927 ☑ 1983 Surface Owner: Federal State Private Tribal Trust or Indian Allotment ☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined Liner type: Thickness \_\_\_\_\_ mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other \_\_\_\_ String-Reinforced Liner Seams: Welded Factory Other \_\_\_\_\_\_ Volume: \_\_\_\_\_\_bbl Dimensions: L\_\_\_\_\_ x W\_\_\_\_\_ x D\_\_\_ Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: 120 bbl Type of fluid: Produced Water Tank Construction material: <u>Steel</u> Secondary containment with leak detection Usible sidewalls, liner, 6-inch lift and automatic overflow shut-off ☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other Visable sidewalls, vaulted, automatic high-level shut off Liner type: Thickness mil HDPE PVC Other Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
☐ Screen ☐ Netting ☒ Other: Expanded metal or solid vaulted top	
Monthly inspections (If netting or screening is not physically feasible)	
7	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
	·
Variances and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	otable source
<b>General siting</b>	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. ( <b>Does not apply to below grade tanks</b> )  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No

Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No										
Temporary Pit Non-low chloride drilling fluid											
thin 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site											
thin 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image											
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site											
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No										
Permanent Pit or Multi-Well Fluid Management Pit											
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No										
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No										
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No										
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No										
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NI Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.  Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number:  or Permit Number:	numents are  NMAC  5.17.9 NMAC										
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Previously Approved Design (attach copy of design) API Number:  or Permit Number:	15.17.9 NMAC										

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the description.	locuments are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Climatological Factors Assessment  Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan  Emergency Response Plan  Oil Field Waste Stream Characterization  Monitoring and Inspection Plan  Erosion Control Plan  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
<u>Proposed Closure</u> : 19.15.17.13 NMAC  Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Flaternative  Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	uid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	nttached to the
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P. 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	<ul><li>☐ Yes ☐ No</li><li>☐ NA</li></ul>
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	<ul><li>☐ Yes ☐ No</li><li>☐ NA</li></ul>
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

1												
adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No											
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Yes \[ \] N												
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Yes \[ \subseteq \text{Yes} \subseteq \text{N}												
Within a 100-year floodplain.  FEMA map												
- PENIA map												
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan a check mark in the box, that the documents are attached.  □ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  □ Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  □ Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  □ Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC											
Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel	ief.											
Name (Print): Title:												
Signature: Date:												
e-mail address: Telephone:												
18.  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature: Approval Date: 1/19/19/19/19/19/19/19/19/19/19/19/19/19	<b>2014</b>											
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date: 5-15-2009												
20.	,											
Closure Method:  ☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-le ☐ If different from approved plan, please explain.	oop systems only)											

22. Operator Closure Certification:												
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.												
Name (Print): Kurt Hoekstra	Title: _	EHS Coordinator										
Signature: _ hurt Horkethur.	_Date: _	11-4-14										
e-mail address: Kurt_Hoekstra@xtoenergy.com_	Teleph	none: <u>505-333-3100</u>										

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

\* Attach Additional Sheets If Necessary

# State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

### Release Notification and Corrective Action

					OPERATOR ☐ Initial Report ☒ Final Report											
Name of Co	mpany: X	TO Energy,		(	Contact: Kurt Hoekstra											
Address: 382	2 Road 31	00, Aztec, N	7	Telephone No.: (505) 333-3100												
						Facility Type: Gas Well (Gallegos Gallup)										
Surface Own	ner: Feder	al		Mineral O	wner				API No.	. 30-045-2	6438					
				LOCA	TION	OF REI	TASE									
I Imit I attan	Cantian	T	D					F . (03								
Unit Letter	Section	Township	Range	Feet from the	North/	South Line	Feet from the	East/W	est Line	County						
J	10	26N	11W	1650		FSL	1980	F	EL		San Ju	an				
<b>Latitude:</b> <u>36.49753</u> <b>Longitude:</b> <u>-107.98853</u>																
NATURE OF RELEASE																
Type of Relea						Volume of	Release: N/A		Volume R	ecovered: 1	√A					
Source of Rel	ease: N/A					Date and H	our of Occurrence	e	Date and I	Hour of Dis	covery:	N/A				
						N/A										
Was Immedia	ite Notice C					If YES, To	Whom?									
		Ц	Yes _	] No 🛛 Not Re	quired											
By Whom?						Date and H	our									
Was a Watero	ourse Reac	hed?		_		If YES, Vo	lume Impacting t	he Wate	rcourse.							
			Yes 🗵	] No												
If a Watercou	rse was Im	nacted Descri	ihe Fully	k		<u></u>			······································							
II a Watercoa	100 1111	paetea, 2000	.co r ung.													
				n Taken.*The belo												
				led for TPH via U									e			
				dards of 100 ppm	ГРН, 0.2	2 ppm benzer	ie,50ppm total BT	EX, and	d 250 ppm	chlorides, c	onfirmi	ng that a	ļ			
release has no	ot occurred	at this location	n.													
Describe Are	a Affected :	and Cleanup A	Action Tal	ken.*No release ha	s heen o	onfirmed at	this location and r	o furthe	er action is	required						
Describe 7 tree	a / illected (	and Cicanapi	tetion rai	con. 140 release ne	is occir c	ommined at	inis location and i	io ruitiii	or action is	required.						
I hereby certi	fy that the i	nformation gi	ven above	is true and compl	ete to th	e best of my	knowledge and u	nderstar	nd that purs	uant to NM	OCD rı	iles and				
				nd/or file certain re												
				ce of a C-141 repo												
				investigate and re									1			
				otance of a C-141	report do	oes not reliev	e the operator of i	responsi	bility for co	ompliance v	vith any	other	l			
rederal, state,	or local lav	ws and/or regu	nations.		т	***	OH COM	CEDV	ATIONI	DIVICIO	<u> </u>					
		1 11 1					OIL CONS	<u>SEK v</u>	AHON	DIAIZIG	<u>)N</u>		ŀ			
	1////	/ <del>- / - /</del>	,													
Signature:	met No	exelle			Annroyad hu	Environmental S	naaialist									
					'	Approved by	Elivirolillicitai 5	рестаны	••							
Printed Name	: Kurt Hoe	kstra					· · · · · · · · · · · · · · · · · · ·									
T'A DUG C	1					A			Danieria : 1	Datas						
Title: EHS Co	oordinator				- 1	Approval Dat	ie:	]	Expiration 1	vate:						
E mail Add	oce Vuet 11	laaketra@vtaa	maray oo	n	,	Conditions of	f Approval:				1					
E-man Addre	.55. Kurt H	loekstra@xtoe	mergy.cor		─ '	Conditions 0	Approvai.			Attached			- 1			
Date: 11-4	-14 Pho	one: 505-333-	3100	÷												

# XTO Energy Inc. San Juan Basin Below Grade Tank Closure Report

Lease Name: OH Randel # 11 API No.: 30-045-26438

Description: Unit J, Section 10, Township 26N, Range 11W, San Juan County

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure requirements of below-grade tanks on XTO Energy Inc. (XTO) locations. This is XTO's standard procedure for all below-grade tanks. A separate plan will be submitted for any below-grade tank which does not conform to this plan.

#### General Plan

1. XTO will close below-grade tanks within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the division requires because of imminent danger to fresh water, public health or the environment.

Closure Date is May 15th, 2009

- 2. XTO will close a below-grade tank that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC.

  Closure Date is May 15<sup>th</sup>, 2009
- 3. XTO will close a permitted below-grade tank within 60 days of cessation of the below-grade tank's operation or as required by the transitional provisions of Subsection B of 19.15.17.17 NMAC in accordance with a closure plan that the appropriate division district office approves. The closure report will be filed on form C-144.

Required C-144 Form is attached to this document.

4. XTO will remove liquids and sludge from below-grade tanks prior to implementing a closure method and will dispose of the liquids and sludge in a division-approved facility. Approved facilities and waste streams include:

Envirotech Permit No. NM01-0011 and IEI Permit No. NM 01-0010B

Soil contaminated by exempt petroleum hydrocarbons

Produced sand, pit sludge and contaminated bottoms from storage of exempt wastes

Basin Disposal Permit No. NM01-005 Produced water

All liquids and sludge were removed from the tank prior to closure activities.

5. XTO will remove the below-grade tank and dispose of it in a division approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves. XTO has removed the below grade tank, and will dispose of it at a division approved facility, or recycle, reclaim or reuse it in a manner that is approved by the division.

6. XTO will remove any on-site equipment associated with a below-grade tank unless the equipment is required for some other purpose.

All Equipment has been removed due to the plugging and abandoning of the OH Randel # 11 well.

At a minimum 5 point composite sample will be collected along with individual grab samples from any area that is wet, discolored or showing other evidence of a release. Samples will be analyzed for BTEX, TPH and chlorides to demonstrate that the benzene concentration, as determined by EPA SW-846 methods 8021B or 8260B or EPA method that the division approves, does not exceed 0.2 mg/kg; total BTEX concentration, as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 50 mg/kg; the TPH concentration, as determined by EPA method 418.1 or other EPA method that the division approves, does not exceed 50 mg/kg; the TPH concentration, as determined by EPA method 300.1 or other EPA method that the division approves, does not exceed 250 mg/kg, or the background concentration, whichever is greater. XTO will notify the division of its results on form C-141.

A five point composite sample was taken of the pit using sampling tools and all samples tested per Subsection B of 19.15.17.1 3(B)(1)(b). (Sample results attached).

Components	Test Method	Limit (mg/Kg)	Results
Benzene	EPA SW-846 8021B or 8260B	0.2	<0.050 mg/kg
BTEX	EPA SW-846 8021B or 8260B	50	< 0.25 mg/kg
ТРН	EPA SW-846 418.1	100	< 20 mg/kg
Chlorides	EPA 300.1	250 or background	71 mg/kg

8. If XTO or the division determines that a release has occurred, XTO will comply with 19.15.3.116 NMAC and 19.15.1.19NMAC as appropriate.

No release has been confirmed at this site.

9. If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Paragraph (4) of Subsection E of 19.15.17.13 NMAC, XTO will backfill the excavation with compacted, non-waste containing, earthen material; construct a division prescribed soil cover; recontour and re-vegetate the site.

The pit cellar was backfilled using compacted, non-waste containing earthen material, with a division prescribed soil cover.

- 10. Notice of Closure operations will be given to the Aztec Division District III office between 72 hours and one week prior to the start of closure activities via email or verbally.

  The notification will include the following:
  - i. Operator's name
  - ii. Well Name and API Number
  - iii. Location by Unit Letter, Section, Township, and Range

Due to misunderstanding regarding the 'pit rule' in 2008-2009, the proper notifications were not made prior to the beginning of closure activities. These misunderstandings have been corrected, and proper notifications are made currently.

The surface owner shall be notified of XTO's proposal to close the BGT as per the approved closure plan using certified mail, return receipt requested.

Due to misunderstanding regarding the 'pit rule' in 2008-2009, the proper notifications were not made prior to the beginning of closure activities. These misunderstandings have been corrected, and proper notifications are made currently.

11. Re-contouring of location will match fit, shape, line, form and texture of the surrounding area. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be placed in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.

The location has been recontoured to match the above specifications.

12. A minimum of 4 feet of cover shall be achieved and the cover shall include 1 foot of suitable material to establish vegetation at the site, or the background thickness of topsoil, whichever is greater.

The site has been backfilled to match these specifications after P&A.

13. XTO will seed the disturbed areas the first growing season after the operator closes the pit. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will be used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

The site has been reclaimed pursuant to the surface use agreement upon P&A.

- 14. All closure activities will include proper documentation and be available for review upon request and will be submitted in closure report form to OCD within 60 days of closure of the below-grade tank. Closure report will be filed on form C-144 and incorporate the following:
  - i. Proof of closure notice to division and surface owner; Not made
  - ii. Details on capping and covering, where applicable; per OCD Specifications
  - iii. Inspection reports; attached
  - iv. Confirmation sampling analytical results; attached
  - v. Disposal facility name(s) and permit number(s); see above
  - vi. Soil backfilling and cover installation; per OCD Specifications
  - vii. Re-vegetation application rates and seeding techniques, (or approved alternative to re-vegetation requirements if applicable); **per BLM MOU**
  - viii. Photo documentation of the site reclamation. attached
- 15. This closure report is being submitted after the 60 day deadline required by the 'Pit Rule' due to a misunderstanding of the 'Pit Rule' in 2008-2009.



#### COVER LETTER

Friday, April 10, 2009

Martin Nee XTO Energy 382 County Road 3100 Aztec, NM 87410

TEL: (505) 333-3100 FAX (505) 333-3280

RE: B.G.T. Samples

Dear Martin Nee:

Order No.: 0904005

Hall Environmental Analysis Laboratory, Inc. received 1 sample(s) on 4/1/2009 for the analyses presented in the following report.

These were analyzed according to EPA procedures or equivalent. Below is a list of our accreditations. To access our accredited tests please go to www.hallenvironmental.com or the state specific web sites.

Reporting limits are determined by EPA methodology. No determination of compounds below these (denoted by the ND or < sign) has been made.

Please don't hesitate to contact HEAL for any additional information or clarifications.

Sincerely,

Andy Freeman, Business Manager Nancy McDuffie, Laboratory Manager

NM Lab # NM9425 AZ license # AZ0682 ORELAP Lab # NM100001 Texas Lab# T104704424-08-TX



## Hall Environmental Analysis Laboratory, Inc.

Date: 10-Apr-09

CLIENT:

XTO Energy

Lab Order:

0904005

Project: Lab ID:

B.G.T. Samples 0904005-01

Client Sample ID: OH Randel #11 BGT Pit

Collection Date: 3/31/2009 9:30:00 AM

Date Received: 4/1/2009

Matrix: SOIL

Analyses	Result	PQL	Qual Units	DF	Date Analyzed
EPA METHOD 8021B: VOLATILES					Analyst: DAM
Benzene	ND	0.050	mg/Kg	.1	4/9/2009 1:11:21 PM
Toluene	ND	0.050	mg/Kg	1	4/9/2009 1:11:21 PM
Ethylbenzene	ND	0.050	mg/Kg	1	4/9/2009 1:11:21 PM
Xylenes, Total	ND	0.10	mg/Kg	1	4/9/2009 1:11:21 PM
Surr: 4-Bromofluorobenzene	90.6	66.8-139	%REC	· . 1	4/9/2009 1:11:21 PM
EPA METHOD 300.0: ANIONS					Analyst: RAGS
Chloride	71	1.5	mg/Kg	5	4/9/2009 12:53:26 AM
EPA METHOD 418.1: TPH					Analyst: LRW
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	· 1	4/3/2009

Qualifiers:

Spike recovery outside accepted recovery limits

RL Reporting Limit

Value exceeds Maximum Contaminant Level

E Estimated value

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н

MCL Maximum Contaminant Level

Date: 10-Apr-09

# **QA/QC SUMMARY REPORT**

Client:

XTO Energy

Project:

B.G.T. Samples

Work Order:

0904005

Project: B.O.T. Sam	pies						W	ork (	rder:	0904005
Analyte	Result	Units	PQL	%Rec	LowLimit	HighLimit	%RPD	RPDI	_imit Q	ual
Method: EPA Method 300.0: A	nions									
Sample ID: MB-18764	,	MBLK			Batch I	D: 18764	Analysis Dat	:e:	4/8/200	9 4:40:24 AN
Chloride	. ND	mg/Kg	0.30							
Sample ID: MB-18764		MBLK	•		Batch I	D: 18764	Analysis Dat	<b>:</b>	4/8/200	9 1:51:55 PN
Chloride	ND	mg/Kg	0.30							
Sample ID: LCS-18764		LCS			Batch I	D: <b>18764</b>	Analysis Dat	:e:	4/8/200	19 4:57:49 AN
Chloride	14.97	mg/Kg	0.30	99.8	90	110				
Sample ID: LCS-18764		LCS			Batch I	D: 18764	Analysis Dat	:ө:	4/8/200	9 2:09:19 PN
Chloride	15.55	mg/Kg	0.30	104	90	110	<u>-</u>			
Method: EPA Method 418.1: T	РН				•					
Sample ID: MB-18726		MBLK			Batch I	D: <b>18726</b>	Analysis Dat	<b>:</b>		4/3/2009
Petroleum Hydrocarbons, TR	ND	mg/Kg	20							
Sample ID: LCS-18726		LCS			Batch I	D: 18726	Analysis Dat	e:		4/3/2009
Petroleum Hydrocarbons, TR	87.32	mg/Kg	. 20	87.3	82	114				
Sample ID: LCSD-18726		LCSD			Batch I	D: <b>18726</b>	Analysis Dal	e:		4/3/2009
Petroleum Hydrocarbons, TR	95.92	mg/Kg	20	95.9	82	114	9.39	20		
Method: EPA Method 8021B:	√olatiles									
Sample ID: 0904005-01A MSD		MSD			Batch I	D: 18715	Analysis Dat	te:	4/9/200	9 3:13:45 PM
Benzene	1.084	mg/Kg	0.050	107	78.8	132	7.16	27		
Toluene	1.061	mg/Kg	0.050	106	78.9	112	5.14	19		
Ethylbenzene	1.122	mg/Kg	0.050	112	69.3	125	3.62	10		
Xylenes, Total	3.376	mg/Kg	0.10	113	73	128	3.56	13		
Sample ID: MB-18715		MBLK		•	Batch II	D: <b>18715</b>	Analysis Dat	te:	4/9/200	9 4:14:43 PM
Benzene	ND	mg/Kg	0.050							
Toluene	ND	mg/Kg	0.050							
Ethylbenzene	ND	mg/Kg	0.050							
Xylenes, Total	ND	mg/Kg	0.10		•					
Sample ID: LCS-18715		LCS			Batch I	D: 18715	Analysis Dat	te:	4/9/200	9 3:44:15 PN
Benzene	1.057	mg/Kg	0.050	104	78.8	132			•	
Toluene	0.9977	mg/Kg	0.050	99.0	78.9	112				
Ethylbenzene	1.076	mg/Kg	0.050	108	69.3	125				
Xylenes, Total	3.207	mg/Kg	0.10	107	73	128				
Sample ID: 0904005-01A MS		MS			Batch I	D: 18715	Analysis Dat	te:	4/9/200	9 2:43:11 PM
Benzene	1.009	mg/Kg	0.050	99.6	78.8	132				
Toluene	1.008	mg/Kg	0.050	101	78.9	112				
Ethylbenzene	1.082	mg/Kg	0.050	108	69.3	125				
•	3.258	mg/Kg	0.10	109	73	128				

Ous	lifi	iers

E Estimated value

J Analyte detected below quantitation limits

R RPD outside accepted recovery limits

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

S Spike recovery outside accepted recovery limits

#### Hall Environmental Analysis Laboratory, Inc. Sample Receipt Checklist Client Name XTO ENERGY 4/1/2009 Date Received: Work Order Number 0904005 Received by: ARS Sample ID labels checked by: Checklist completed by: Sionature Matrix: Carrier name: FedEx Yes 🗹 No 🗆 Not Present Shipping container/cooler in good condition? Yes 🗸 No 🗌 Not Present Custody seals Intact on shipping container/cooler? Not Shipped Yes [ No 🗌 Custody seals intact on sample bottles? N/A Yes 🗹 No 🗆 Chain of custody present? Yes 🗹 No 🗌 Chain of custody signed when relinquished and received? No 🗆 Yes 🗹 Chain of custody agrees with sample labels? Samples in proper container/bottle? Yes V No 🗆 Yes 🔽 No 🗌 Sample containers intact? Yes 🗹 No 🗌 Sufficient sample volume for indicated test? No 🗆 Yes 🗹 All samples received within holding time? No 🖂 Yes 🗍 No VOA vials submitted 😾 Water - VOA vials have zero headspace? Yes 🗍 No 🗆 N/A 🔽 Water - Preservation labels on bottle and cap match? Yes 🗌 No 🗆 N/A 🔽 Water - pH acceptable upon receipt? Container/Temp Blank temperature? 4° <6° C Acceptable If given sufficient time to cool. COMMENTS: Person contacted Client contacted Date contacted: Regarding: Contacted by: Comments:

**Corrective Action** 

C	Chain	-of-Cι	istody Record	Turn-Around	Time:						_											
Client: XTO ENERGY				T Standard	_ □ Rush	1 .														N		
Project Name:				<b>9:</b>		<del></del>	<b>-</b>											K	AT(	JK	Y	
Mailing Address: 382 POAD 3100				B.G.T. SAMPLES Project #: B.G.T. PIT					www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109													
			M 87410	Project #:	B.G.T. 7	ीन			Tel. 505-345-3975 Fax 505-345-4107													
Phone			33-3207	1 AH R	ANDEL	# 11		0 - 1 sp														
email o				Project Mana									· · ·						·			
QA/QC Package:  □ Standard □ Level 4 (Full Validation)			1	<u>MARTIN</u>	N		TMB'e (8021)	TPH (Gas only)	s/Dies					05,50	⊃CB's			q				
Accred		·		Sampler:	KURT	Met	<u> </u>	┦ 🐉	Ę	Ö					7,2,F	82			300.0			
□ NEL		□ Othe	er	Golde C				副手		15B	18.1	4.1	Æ		3, N	/ 80		<b>a</b>				ź
	(Type)			Sample rein	erailine as s				3.	80	4 6	d 5(	٩	tals	S,	des	_	0	4			l°,
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type		1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1	BTEX + MTBE	BTEX + MTBE +	TPH Method 8015B (Gas/Diesel)	TPH (Method 418.1)	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	CHLORIDES			Air Bubbles (Y or N)
3/31	9:30	Soil	OH RANDEL # 11 BGT PIT	12) Aoz JAR	ON ICES		1	×			×			-			~		X		$\neg \vdash$	+
9/31	1.00		100-1111	(2) 102 JHZ	105			\ <u>\</u>			$\overline{}$	$\dashv$	$\dashv$	十		-				$\dashv$	+	+
						-		+				-		$\dashv$		$\dashv$			$\rightarrow$	<u>-</u>		
											-	_	-							$\dashv$	_	┿-
**=		-	<u> </u>			<u>.</u>	· · · · · · · · · · · · · · · · · · ·	+			-	$\dashv$		_					_		-	+
<u></u>											_			_		4	_		$\dashv$			$\bot$
		GPS	N36°29,994 W10	7°59.312			<u> </u>	4				_	_							_	-	
			ļ , , , , , , , , , , , , , , , , , , ,								_	_								$\bot$	_	
		SAME	LED FOR MIKE HAR	TSELL											_							
												_							$\Box$			
	ļ				_																	
					<u> </u>																	
			1111																			
Date: 3/31 Date:	Time: 3:20 Time:	Relinquishe Relinquishe	it Hoekelle	Received by:	9:55	P Date Date	Time	Ren E K	MAN Wen	: - H	Res loev	w. 457	rs RA	T0	•							
							K	۱۳۸	C,	ten.	191	411										



Division

Denver

Dates

06/01/2008 - 06/01/2011

Type

Route Stop

Type Value

0

RouteName Below Grade Pit Forms (Temp.)		StopName Oh Randel # 11		Pumper Blackburn, Shawn	Foreman Unassigned	WellName OH RANDEL 11 (PA)			APIWellNumber 3004526438		Section 10	Range 11W	Township 26N
InspectorName	Inspection Date	Inspection Time	Visible LinerTears	VisibleTankLeak Overflow	Collection OfSurfaceRun	Visible LayerOil	Visible Leak	Freeboard EstFT	PitLocation	PitType			Notes
Sanders	08/20/2008	1345:00	No	No	No	No	No	72					
Sanders	09/24/2008	1400:00	No	No	No	No	No	72					pit is dry
Sanders	10/23/2008	1400:00	No	No	No	No	No	72	Well Water Pit	Below Ground			pit is dry
Sanders	11/22/2008	1045:00	No	No	No	No	No	72	Well Water Pit	Below Ground			pit is dry
Sanders	12/24/2008	900:00	No	No	No	No	No	72	Well Water Pit	Below Ground			pit is dry
Sanders	01/23/2009	915:00	No	No	No	No	No	72	Well Water Pit	Below Ground			pit is dry
Sanders	02/26/2009	915:00	No	No	No	No	No	72	Well Water Pit	Below Ground			pit is dry
													pit is dry

