

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports on Wells

1. Type of Well
GAS

RECEIVED

JAN 23 2015

NMOCD

DISTRICT III

2. Name of Operator
Meridian Oil Inc.

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
820' FNL, 1500' FWL Sec. 27, T-28-N, R-9-W, NMPM

5. Lease Number

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Hancock B #8

9. API Well No.
30-045-07202

10. Field and Pool
Aztec Pic. Cliffs

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA
Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

06-15-92 MOL&RU. ND WH. NU BOP. TIH to 3146'. Est rate down tbg w/10 BW. Cmt plug #1 w/20 sx Class "B" neat cmt w/2.5% calcium chloride. Displace w/3.5 BW. TOO. WOC. Tag cmt @ 2713'. Cmt plug #2 w/15 sx Class "B" neat 2682-2340'. Displace w/2.5 BW. TOO. Circ. clean @ 2340'. SI. SDFN.

06-16-92 Attempt PT csg, would not hold. Tag TOC @ 2295'. PU to 2292'. Perf 2 holes. TIH w/cmt ret set @ 1090'. Est rate thru ret. Cmt plug #3 w/171 sx Class "B" neat cmt. Displace w/2 BW. Sting out of ret, dump 2.5 sx on top of ret. TOO. Attempt PT csg, would not hold. TIH, perf 2 holes @ 970'. Set cmt ret @ 872'. Est rate thru ret. Cmt plug #4 w/56 sx cmt under ret, spot 15 sx on top of ret. Displace w/1.5 BW. Csg will not hold pressure. TOO. Cmt plug #5 w/5 sx Class "B" neat cmt. Displace w/1.5 BW. Tag @ 505'. Hole @ approx 505'. PU to 180'. Perf 2 holes. TIH to 498', est circ down tbg & out bradenhead w/7 BW. Cmt plug #6 w/78 sx Class "B" neat cmt until approx 1 bbl good cmt ret out bradenhead. Close valve & open csg valve, fill 2 7/8" csg. TOO. w/tbg, refilled 2 7/8". SI. SDFN.

06-17-92 Cut off WH. Install dry hole marker w/15 sx Cmt. Well P&A.

14. I hereby certify that the foregoing is true and correct. Approved as to plugging of the well bore.

Signed John Headfield Title Regulatory Affairs Date 6/18/92

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

APPROVED

JUN 25 1992
AREA MANAGER

OPERATOR