

RECEIVED

RECEIVED

Form 3160-5
(February 2005)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FEB 17 2015

FORM APPROVED
OMB No. 1004-0137
Expires: March 31, 2007

FEB 20 2015

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		5. Lease Serial No. NMNM110324
2. Name of Operator WPX Energy Production, LLC		6. If Indian, Allottee or Tribe Name
3a. Address PO Box 640 Aztec, NM 87410	3b. Phone No. (include area code) 505-333-1806	7. If Unit of CA/Agreement, Name and/or No.
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) SHL: 1744' FNL & 195' FEL SEC 24 T23N R8W BHL: 1676' FNL & 230' FWL SEC 24 T23N R8W		8. Well Name and No. CHACO 2308-24H #154H
		9. API Well No. 30-045-35549
		10. Field and Pool or Exploratory Area Basin Mancos (660')
		11. Country or Parish, State San Juan, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other FINAL CASING
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

2/11/15 thru 2/12/15 - Drill 6-1/8" lateral
2/13/15 - TD 6-1/8" lateral @ 11602 (TVD 5049')
2/14/15 - Run 120 jts 4-1/2", 11.6#, P-110, LT&C. CSG set @ 10588' (TVD 5048'), LC @ 10499', RSI tool 10498', marker jts @ 7232' & 8956', IOL @ 5587'
 Cementing: Halliburton to pump 10bbbls of fresh water, 40bbbls of Tuned Spacer III, 10.5ppg, yield 6.22, mix ratio 98.9, Cap Cement 35sx (9bbl Slurry) of Elastiseal Cement with .2% versaset, .15% Halad-766 .2% Halad-344, 6.92gal water, 13.0ppg, Yield 1.42, Mix 6.43, Foam Lead 245sks (61.1bbl Slurry) of Elastiseal Cement with .2% versaset, .15% Halad-766 .2.5% Chem-Foamer 760, .2% Halad-344, 6.924gal fresh water, 13.0ppg, Yield 1.42, Mix 6.43, Tail Cement 100sx (23bbl Slurry) of Elastiseal Cement with 2% versaset, .15% Halad-766, .05% SA-1015, 5.81gal fresh water, 13.5ppg, yield 1.3, Mix ratio 5.81, Displace with 40bbbls of MMCR spacer + 40bbbls of 2% KCL Water +20bbbls fresh water + 27.8bbbls of KCL water. Total displacement 126bbbls Final Circulating Pressure 1380psi @ 3bbbls/min Bumped Plug to 1600psi Plug Down @ 19:06hrs 2/14/2015 Floats held Drop ball Set liner with 4100psi Release from liner hanger Circulate with 2% KCL water Cement to Surface - trace Pressure tested liner top to 1500psi for 30min good test
 Release Rig @ 1100 hrs 2/15/15 ✓

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) Lacey Granillo		Title Permit Tech III
Signature		Date 2/17/15

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by	Title	Date
	Office	

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)



FARMINGTON FIELD OFFICE
BY: William Tambekou