:
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

Ĩ

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
12850 Proposed Alternative Method Permit or Closure Plan Application Oil CONS. DIV DIST. 3
Type of action: \square Below grade tank registration
$\square \text{ Permit of a pit or proposed alternative method} APR 08 2015$
$45-25262$ \square Closure of a pit, below-grade tank, or proposed alternative method \square Modification to an existing permit/or registration \square Modification \square Modification to an existing permit/or registration \square Modification \square Modifi
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1. Operator: BP America Production Company OGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Gallegos Canyon Unit 204E
API Number: 3004525262 OCD Permit Number:
U/L or Qtr/Qtr Section34 Township28N Range12W County:San Juan
Center of Proposed Design: Latitude36.61732 Longitude108.09190 NAD: □1927 ⊠ 1983
Surface Owner: 🛛 Federal 🔲 State 🗌 Private 🗌 Tribal Trust or Indian Allotment
2
□ <u>Pit:</u> Subsection F, G or J of 19.15.17.11 NMAC
Temporary: 🔲 Drilling 🔲 Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:21.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection 🗋 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
🗌 Visible sidewalls and liner 🗌 Visible sidewalls only 🛛 Other _Single walled/double bottomed; side walls not visible
Liner type: Thickness mil HDPE PVC Other
4.
Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

 s. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
 6. <u>Netting</u>: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible) 	
 <u>Signs:</u> Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC 	
 8. <u>Variances and Exceptions</u>: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. <i>Please check a box if one or more of the following is requested, if not leave blank:</i> Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
 Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes 🗌 No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗋 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗍 No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗌 Yes 🗌 No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No

٠

.

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗍 Yes 🗍 No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗋 Yes 🗌 No
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
10. <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 NM <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docu attached.</i>	
 Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 	NMAC
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC 	5.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
^{11.} <u>Multi-Well Fluid Management Pit Checklist</u> : Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doct attached.	uments are
 Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15 	15.17.9 NMAC
and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

•

,

<u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
 attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	uocumenis are
 Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan 	
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance on Hammedous Odern including H.S. Parametrica Plane 	
 Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan O'I Ei MW et Oregon Classical de la construction 	
 Oil Field Waste Stream Characterization Monitoring and Inspection Plan 	
Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Fype: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management I
Alternative Proposed Closure Method: Waste Excavation and Removal	fuld whinagement i
Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems)	
In-place Burial On-site Trench Burial	
4.	· · ·
 Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	
is. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 10.15.14.0 NMAC for pridemon	rce material are Please refer to
19.15.17.10 NMAC for guidance.	
	□ Yes □ No □ NA
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	NA Ves No
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	 NA Yes No NA Yes No Yes No
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa ake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	 NA Yes No NA Yes No NA Yes No NA
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa ake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	 NA Yes No NA Yes No Yes No NA Yes No Yes No
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa ake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence t the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	 NA Yes No NA Yes No NA Yes No NA Yes No Yes No
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa ake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	$ \begin{array}{c c c c c c c c c c c c c c c c c c c $

•

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	
	🗋 Yes 🗌 No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	🗌 Yes 🗌 No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain. - FEMA map	☐ Yes ☐ No
 On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure play a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	.11 NMAC 15.17.11 NMAC
^{17.} Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure play) Image: Closure Rlan (only) OCD Conditions (see attachment) OCD Representative Signature: October Representative Signature: Image: Approval Date: Image: Approval Date:	
18. OCD Approval: Permit Application (inclu A ing closure plan) 🗹 Closure Rlan (only) 🔲 OCD Conditions (see attachment)	
18. OCD Approval: Permit Application (including closure play) Image: Closure Rlan (only) OCD Conditions (see attachment) OCD Representative Signature: October Representative Signature: Image: Approval Date: Image: Approval Date:	the closure report.
 18. OCD Approval: Permit Application (including closure plan) Closure Rlan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 4/23 Title: Conce Office Office Office OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. 	the closure report.
18. OCD Approval: □ Permit Application (including closure plan) Image: Closure Report (required within 60 days of closure completion): 19. OCD Permit Number:	the closure report. complete this

•

•

Operator Closure Certification:

22

Signature:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print):		Jeff	Peace
· · · -	Λ	_	ρ

_____ Title: Field Environmental Coordinator_____

Date: __April 7, 2015_____

e-mail address:__peace.jeffrey@bp.com_

e

are

_____ Telephone: __(505) 326-9479_

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Gallegos Canyon Unit 204E, BGT Tank A (21 bbl)</u> <u>API No. 3004525262</u> Unit Letter I, Section 34, T28N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. **Notice is attached.**
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number. **Notice is attached.**
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.
 All equipment associated with the BCT has been removed.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

D

۲

.

2-

State of New Mexico Energy Minerals and Natural Resources

> Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141

Revised August 8, 2011

			Rele	ease Notific		n and Co		ction	
						OPERA		_	l Report 🛛 Final Report
Name of Co	mpany: B	Р				Contact: Jef			
		Court, Farmi	ington, N	M 87401			No.: 505-326-94	79	
		os Canyon U					e: Natural gas v		
Surface Owner: Federal Mineral Owner:)wner:	Federal		API No.	. 3004525262
				LOCA	ATIO	N OF REI	LEASE		
Unit Letter	Section	Township	Range	Feet from the	North	/South Line	Feet from the	East/West Line	County: San Juan
Ι	34	28N	12W	1,710	South				
			l						
		Lat	itude3	6.61732		Longitude	e108.09190_		
				NAT	URE	OF RELI	EASE		
Type of Relea	ase: none					Volume of	Release: N/A	Volume R	ecovered: N/A
Source of Re	lease: below	v grade tank –	- 21 bbl, T	ank A		1	our of Occurrenc	e: Date and I	Hour of Discovery: N/A
Was Immedia	to Notice (Siven?				N/A If YES, To	Whom?		
was mineura			Yes 🗌] No 🖾 Not Re	equired	11 163, 10	whom?		
By Whom?						Date and H	our		
Was a Water	course Read	ched?	<u> </u>				lume Impacting t	he Watercourse.	
			Yes 🛛] No					
If a Watercou	irse was Im	pacted, Descr	ibe Fully.*	k					
				n Taken.* Sampli and chlorides belo					o ensure no soil impacts from
				cen.* BGT was re active well area.	moved	and the area u	nderneath the BG	T was sampled. Th	e area under the BGT was
regulations al public health should their o	l operators or the envir operations homent. In a	are required to ronment. The ave failed to a ddition, NMC	o report ar acceptanc adequately)CD accep	nd/or file certain r ce of a C-141 repo investigate and r	elease n ort by th emediat	otifications ar le NMOCD ma te contamination	nd perform correc arked as "Final R on that pose a thre e the operator of r	tive actions for rele eport" does not relie eat to ground water responsibility for co	Lant to NMOCD rules and ases which may endanger eve the operator of liability , surface water, human health ompliance with any other
() 00	Ω					<u>OIL CON</u>	SERVATION	DIVISION
Signature:	off	Pose	•						
Printed Name	01					Approved by	Environmental S	pecialist:	
Title: Field E	nvironment	al Coordinate	or			Approval Dat	e:	Expiration I	Date:
E-mail Addre	ss: peace.je	effrey@bp.com	m			Conditions of	Approval:		Attached
Date: April Attach Addit		ets If Necess)5-326-9479					

V				······································
		G ENGINEERIN 7, BLOOMFIELI		API #: 3004525262
		(505) 632-1199		(if applicble):
FIELD REPORT:	(circle one): BGT CONFIRMA	TION / RELEASE INVESTIGAT	non / other:	PAGE #: <u>1</u> of <u>1</u>
SITE INFORMATION	SITE NAME: GCI	U # 204E		DATE STARTED: 02/11/15
QUAD/UNIT: SEC: 34 TWP:	28N RNG: 12W	PM: NM CNTY:	SJ ST: NM	DATE FINISHED:
1/4 -1/4/FOOTAGE: 1,710'S / 42	5'E NE/SE LE	EASE TYPE: FEDERAL		
LEASE #: SF078903A	PROD. FORMATION: DK	CONTRACTOR: MBI	RIKE F - S. GLYNN	SPECIALIST(S): NJV
REFERENCE POINT	WELL HEAD (W.H	.) GPS COORD.: 3	6.61613 X 108.0914	0 GL ELEV.: 5,878'
1) 21 BGT (SW/DB) - A	GPS COORD.:	36.61732 X 108.09	0190 DISTANCE/E	BEARING FROM W.H.: 456', N18W
2) 95 BGT (DW/DB) - B	GPS COORD.:	<u>36.61617 X 108.05</u>	DISTANCE/E	EARING FROM W.H.:
3)	GPS COORD.:		DISTANCE/E	BEARING FROM W.H.:
4)	GPS COORD.:		DISTANCE/E	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD	D(S) # OR LAB USED:	HALL	OVM READING (ppm)
1) SAMPLE ID: 5PC - TB @ 5' (2	21) - A SAMPLE DATE:	02/11/15 SAMPLE TIME:	11 <u>50</u> LAB ANALYSIS:4	
2) SAMPLE ID:	SAMPLE DATE: C	92/11/15 SAMPLE TIME:	1130 LAB ANALYSIS: 4	10.1/8621B/300.0 (GI) NA
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:	
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:	
SOIL DESCRIPTION	SOIL TYPE: SANDI SILTY S	AND SILT / SILTY CLAY / CLAY	/ / GRAVEL / OTHER	
SOIL COLOR: DARK YELLOV				/ COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE) SLIGHTL' CONSISTENCY (NON COHESIVE SOILS): LC				// STIFF / VERY STIFF / HARD
MOISTURE: DRY /SLIGHTLY MOIST / MOIST / W				
SAMPLE TYPE: GRAB		ANY AREAS DISPLAYIN	GWETNESS: YES NO EXPL	ANATION -
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE	DAND/OR OCCURRED : YES INC	EXPLANATION:	·N ·	
EQUIPMENT SET OVER RECLAIMED AREA:	YES NO EXPLANATION - 9	5 LOW PROFILE ABOVE-G	RADE TANK TO BE SET	ATOP BOTH BGT LOCATIONS.
OTHER: WELL HEAD & 95 BGT LOCATE	D WITHIN CENTER PIVOT A	AGRICULTURAL CROP CI	RCLE OPERATION.	
SOIL IMPACT DIMENSION ESTIMATION:	NAft. X	NA ft. X NA	ft. EXCAVATION E	STIMATION (Cubic Yards) :NA
	EAREST WATER SOURCE:	1,000' NEAREST SURFACE	WATER: <u>>1,000'</u> NM	OCD TPH CLOSURE STD: ppm
SITE SKETCH	BGT Located : off of	n site PLOT PLA	N circle: attached	VM CALIB. READ. = NAppm RF =0.52
	K			VM CALIB. GAS = Ppm
$\langle \rangle$	- COMPRESSOR		N [[ME: <u>NA</u> am/pm DATE: <u>NA</u>
			' [MISCELL. NOTES
. (21)				WO:
$(x x x x) \leftarrow PBGTL T.B. \sim 5'$				REF. #: P-11 PK: ZEVH01BGT2
B.G.				PK: ZEVH01BGT2 PJ#: Z2-006Q0
				Permit date(s): 06/14/10
				OCD Appr. date(s): 11/18/14
				Tank OVM = Organic Vapor Meter ID ppm = parts per million
METER	TO			A BGT Sidewalls Visible: Y /N
RUN	W.H.		X - S.P.D.	B-BCT Sidewalls Visible: Y-(N)
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL)N DEPRESSION; B.G. = BELOW GRAD); B = BELOW; T.H. = TEST HOLE; ~ = AMPLE POINT DESIGNATION: R W =	APPROX.; W.H. = WELL HEAD;	BGT Sidewalls Visible: Y / N Magnetic declination: 10° E
APPLICABLE OR NOT AVAILABLE; SW - SINGL	E WALL; DW - DOUBLE WALL; SB - SING	GLE BOTTOM; DB - DOUBLE BOTTON	<u>. </u>	
NOTES: GOOGLE EARTH IMAG	ERY DATE: 11/17/2013.	ONSITE:	02/11/15	

.

Analytical Report Lab Order 1502526

Date Reported: 2/16/2015

1

Hall Environmental Analysis Laboratory, Inc.

1

CLIENT: Blagg Engineering Client Sample ID: 5PC-TB @ 5' (21)-A **Project:** GCU # 204E Collection Date: 2/11/2015 11:50:00 AM 1502526-001 Matrix: MEOH (SOIL) Lab ID: Received Date: 2/12/2015 7:28:00 AM Result Analyses **RL** Qual Units **DF** Date Analyzed Batch EPA METHOD 8021B: VOLATILES Analyst: NSB Benzene ND 0.040 mg/Kg 1 2/12/2015 11:39:07 AM 17666 Toluene ND 0.040 mg/Kg 1 2/12/2015 11:39:07 AM 17666 Ethylbenzene ND 0.040 mg/Kg 2/12/2015 11:39:07 AM 17666 1 Xylenes, Total ND 0.079 mg/Kg 1 2/12/2015 11:39:07 AM 17666 Surr: 4-Bromofluorobenzene 97.0 80-120 %REC 2/12/2015 11:39:07 AM 17666 1 EPA METHOD 300.0: ANIONS Analyst: JRR 20 2/12/2015 12:47:26 PM 17718 Chloride ND 30 mg/Kg EPA METHOD 418.1: TPH Analyst: BCN Petroleum Hydrocarbons, TR ND 20 mg/Kg 2/12/2015 1:00:00 PM 17712

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Metho	od Blank
	Е	Value above quantitation range	Н	Holding times for preparation or analysis	s exceeded
	J	Analyte detected below quantitation limits	ND	Not Detected at the Reporting Limit	Page 1 of 5
	0	RSD is greater than RSDlimit	Р	Sample pH Not In Range	1 4 5 1 61 5
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit	
	S	Spike Recovery outside accepted recovery limits			

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

WO#: 1502526

16-Feb-15

	g Engineering # 204E			
Sample ID MB-17718	SampType: MBLK	TestCode: EPA Method	l 300.0: Anions	
Client ID: PBS	Batch ID: 17718	RunNo: 24289		
Prep Date: 2/12/2015	Analysis Date: 2/12/2015	SeqNo: 715791	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Chloride	ND 1.5			
Sample ID LCS-17718	SampType: LCS	TestCode: EPA Method	300.0: Anions	· <u>-</u> ·
Client ID: LCSS	Batch ID: 17718	RunNo: 24289		
Prep Date: 2/12/2015	Analysis Date: 2/12/2015	SeqNo: 715792	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Chloride	14 1.5 15.00	0 91.9 90	110	······································

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 3 of 5

Ū.

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

•

.....

•

Client: Project:	Blagg I GCU #	Engineering 204E												
Sample ID M	B-17712	SampTyp	e: ME	BLK	Tes	tCode: El	PA Method	418.1: TPH						
Client ID: P	BS	Batch II	D: 17	712	F	RunNo: 2	4261							
Prep Date:	2/12/2015	Analysis Dat	e: 2 /	12/2015	S	SeqNo: 7	14993	Units: mg/k	٢g					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Petroleum Hydroc	arbons, TR	ND	20											
Sample ID LCS TestCode: EPA Method 418.1: TPH														
Client ID: LO	CSS	Batch II	D: 17	712	RunNo: 24261									
Prep Date:	2/12/2015	Analysis Dat	e: 2 /	12/2015	S	SeqNo: 7	14994	Units: mg/Kg						
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Petroleum Hydroc	arbons, TR	100	20	100.0	0	102	86.7	126						
Sample ID LO	CSD-17712	SampTyp	e: LC	SD	Tes	tCode: El	PA Method	418.1: TPH	;					
Client ID: LCSS02 Batch ID			D: 17 3	712	F	RunNo: 2	4261							
Prep Date: 2	2/12/2015	Analysis Dat	Analysis Date: 2/12/2015			SeqNo: 7	14995	Units: mg/H	(g					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Petroleum Hydroc	arbons, TR	100	20	100.0	0	100	86.7	126	1.31	20				

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH Not In Range
- RL Reporting Detection Limit

Page 4 of 5

16-Feb-15

WO#: 1502526

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering **Project:**

GCU # 204E

Sample ID MB-17666	SampType: MBLK TestCode: EPA Method 8021B: Volatiles												
Client ID: PBS	Batch	n ID: 17	666	F	RunNo: 2	4264							
Prep Date: 2/10/2015	15 Analysis Date: 2/12/2015 SeqNo: 715490				Units: mg/K	mg/Kg							
Analyte	Result PQL SPK value SPK Ref Val %REC Low		LowLimit	HighLimit	%RPD	RPDLimit	Qual						
Benzene	ND	0.050											
Toluene	ND	0.050											
Ethylbenzene	ND	0.050											
Xylenes, Total	ND	0.10											
Surr: 4-Bromofluorobenzene	0.92		1.000		92.5	80	120						
Sample ID LCS-17666	Samp1	ype: LC	S	Tes	tCode: El	PA Method	8021B: Vola	tiles					
Client ID: LCSS	Batch	n ID: 17	666 .	F	RunNo: 2	4264							
Prep Date: 2/10/2015	Analysis E)ate: 2 /	12/2015	S	SeqNo: 7	15491	Units: mg/K	ζg					
Analyte	Result.	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	1.1	0.050	1.000	0	109	80	120						
Toluene	1.1	0.050	1.000	0	108	80	120						
Ethylbenzene	1.1	0.050	1.000	D	108	80	120						
Xylenes, Total	3.2	0.10	3.000	0	107	80	120						
Surr: 4-Bromofluorobenzene	1.0		1.000		103	80	120						

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Е Value above quantitation range
- Analyte detected below quantitation limits J
- 0 RSD is greater than RSDlimit
- RPD outside accepted recovery limits R
- S Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank B
- Holding times for preparation or analysis exceeded H
- ND Not Detected at the Reporting Limit
- Р Sample pH Not In Range
- RL Reporting Detection Limit

Page 5 of 5

.

1502526 16-Feb-15

WO#:

ENVIRONMENTAL ANALYSIS LABORATORY TEL: 505-345	ental Analysis Labora 4901 Hawkin Albuquerque, NM 8 3975 FAX: 505-345- w.hallenvironmental	s NE 7109 Samp 4107	ble Log-In Chec	k List
Client Name: BLAGG Work Order Nurr	1ber: 1502526		RcptNo: 1	
Received by/date:				
Logged By: Lindsay Mangin 2/12/2015 7:28:00	AM .	Junihy Honop		
Completed By: Lindsay Mangin 2/12/2015 8:15:19	AM	timely Hopp		
Reviewed By: CS 02/12/15				
Chain of Custody				
1. Custody seals intact on sample bottles?	Yes 🗌	No 🗌	Not Present 🛃	
2. Is Chain of Custody complete?	Yes 🛃	No 🗌	Not Present	
3. How was the sample delivered?	<u>Courier</u>			
Log In				
4. Was an attempt made to cool the samples?	Yes 🛃	No 🗌	NA 🗌	
5. Were all samples received at a temperature of $>0^{\circ}$ C to 6.0°C	Yes 🛃	No 🗌	NA 🗔	
6. Sample(s) in proper container(s)?	Yes 🛃	No 🗌		
7. Sufficient sample volume for indicated test(s)?	Yes 🕢	No 🗌		
8. Are samples (except VOA and ONG) properly preserved?	Yes 🛃	No 🗌		
9. Was preservative added to bottles?	Yes 🗌	No 🛃	NA 🗌	
10.VOA vials have zero headspace?	Yes	No 🗌	No VOA Vials 🛃	
11. Were any sample containers received broken?	Yes 🗆	No 🐼 [# of preserved bottles checked	
12. Does paperwork match bottle labels?	Yes 🐱	Ňo 🗖	for pH:	

Yes 🛃

Yes

Yes

Yes 🛃

No 🗌

No 🗌

No 🗌

. ..

(<2 or >12 unless noted)

Adjusted?

Checked by:

12. Does paperwork match bottle labels?
(Note discrepancies on chain of custody)
13. Are matrices correctly identified on Chain of Custody?

14. Is it clear what analyses were requested? 15. Were all holding times able to be met?

(If no, notify customer for authorization.)

Special Handling (if applicable)

16.)	Was client notified of all d	iscrepancles with this order?		Yes 🗌	No 🗌	NA 🛃
	Person Notifled:		Date:	and an and a second	Contraction of the second second	
	By Whom:	n na na se se ad dell'a l'all'a l'all'an anna an anna anna	Via:		hone 📋 Fax	
	Regarding:	n an		a na manana katang k		gyrpan einin baranna a' an
	Client Instructions:			· ·		
17.	Additional remarks:				•	. .

18. <u>(</u>	B. Cooler Information											
	Cooler No	Temp °C	Condition	Seal Intact	Seal No	Seal Date	Signed By					
	1	2.1	Good	Yes								

Page 1 of 1

	hain-o	of-Cus	stody Record	Turn-Around	Time:	SAME				ł	łA	LL	E	NV	/IF	20	N	ME	ENT	FA	I
Client: BLAGG ENGR. / BP AMERICA			Standard	ANALYSIS LABORATORY																	
				Project Name				í.	×.		ww	w.ha	allen	viro	nme	ental	l.con	า			
Mailing A	dress:	P.O. BO	X 87	GCU # 204E				4901 Hawkins NE - Albuquerque, NM 87109													
		BLOOM	FIELD, NM 87413					Te	I. 50)5-3 [,]	45-3	975		Fax	50 5-	-345	-410)7			
Phone #:	·· ·	(505) 63	32-1199				P FT		1997 1997 1997		117.5 F	، ب	٩'nål	ysis	Rec	ques	st				
email or F	ax#:			Project Manag	ger:				97 V	_											
QA/QC Pac	-		Level 4 (Full Validation)		NELSON VI	ELEZ	<mark>MB's (</mark> 8021B)	only)	(our			S)		04,50	PCB's			er - 300.1)			
Accreditat	ion:			Sampler:	NELSON VI	ELEZ ηγ	2(8) 2(8)	TPH (Gas	DRO /	1)	1)	SIN		02,1	8082			/ wat			du
)	D Other		Onlice:	°∰ Yes		- HALL	Hdl	/	418.	504.	327(0 ₃ ,N			(Y)	0.00			e sa
	уре)	1		Sample Temp	erature: 7	e [+	(GRC	pol	por	or {	etals	CI'N	cide	(¥	i-V	il - 3(e	osit
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX + INT E	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 82705IMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 / water		Grab sample	5 pt. composite sample
2/11/15	1150	SOIL	5PC - TB @ 5' (21)-A	4 oz 1	Cool	-001	V			۷								V		-	V
-2/11/15	-1138	SOIL	5PC - TB @ 5' (95)-B	4 oz 1	Eool	-002-	*			*								*			
			2 <u></u>																		
<u> </u>			RUN TPH 8015B IF TPH																		
<u></u>			418.1 > 100 mg/Kg			-														1	+
			· · · · · · · · · · · · · · · · · · ·			-			•												
	· · · · ·				····			· · ·					•	·			-			-+	
																					-
																					-
																				-	-
. <u> </u>																					-+
Date:	Time:	Relinquisb	ed by:	Received by:	1	2/1	Ren						L	I			Ii			l.	<u> </u>
*/ 1/ /15	1357	J.C.	m	Mistin	Walt	L' /15 1001				τ <mark>ιγ τ</mark> 200 ε			urt,	Farm	ingto	on, N	IM 8.	7401			
	Time: 1		istin Waller	Received by:	H.	Date Time	Re			:									<u>01BG</u>	T2	_

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

February 5, 2015

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 204E API #: 3004525262

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J, BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about February 9, 2015. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at (505)-326-9214.

Sincerely,

9 D Verla

Jerry Van Riper Surface Land Negotiator BP America Production Company

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

February 5, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Azteć, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 204Ê API 30-045-25262 (Î) Section 34 – T28N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21 bbl BGT and a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around February 9, 2015.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincercly,

Jeff Peace BP Field Environmental Advisor

(505) 326-9479

