

State of New Mexico
Energy, Minerals and Natural Resources Department

Susana Martinez
Governor

David Martin
Cabinet Secretary

Brett F. Woods, Ph.D.
Deputy Cabinet Secretary

David R. Catanach Division Director
Oil Conservation Division



New Mexico Oil Conservation Division approval and conditions listed below are made in accordance with OCD Rule 19.15.7.11 and are in addition to the actions approved by BLM on the following 3160-3 APD form.

Operator Signature Date: 5-4-15

Well information;


Operator WPX, Well Name and Number Rosa Unit 27 #105H


API# 30-039-31318, Section 19, Township 31 N/S, Range 5 E/W

Conditions of Approval:

(See the below checked and handwritten conditions)

- ☒ Notify Aztec OCD 24hrs prior to casing & cement.
- ☒ Hold C-104 for directional survey & "As Drilled" Plat
 - ☐ Hold C-104 for NSL, NSP, DHC
 - ☐ Spacing rule violation. Operator must follow up with change of status notification on other well to be shut in or abandoned
 - ☐ Regarding the use of a pit, closed loop system or below grade tank, the operator must comply with the following as applicable:
 - A pit requires a complete C-144 be submitted and approved prior to the construction or use of the pit, pursuant to 19.15.17.8.A
 - A closed loop system requires notification prior to use, pursuant to 19.15.17.9.A
 - A below grade tank requires a registration be filed prior to the construction or use of the below grade tank, pursuant to 19.15.17.8.C
 - ☐ Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
- ☒ Regarding Hydraulic Fracturing, review EPA Underground Injection Control Guidance 84
- ☒ Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.
- ☒ Well-bore communication is regulated under 19.15.29 NMAC. This requires well-bore Communication to be reported in accordance with 19.15.29.8.


NMOCD Approved by Signature

6-29-2015
Date 

OIL CONS. DIV DIST. 3

RECEIVED

FORM APPROVED
OMB No. 1004-0136
Expires January 31, 2004

JUN 19 2015

UNITED STATES

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

MAY 05 2015

Farmington Field Office
Bureau of Land Management

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. SF-078767
1b. Type of Well: <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator WPX Energy Production, LLC		7. If Unit or CA Agreement, Name and No. Rosa Unit R-13457
3a. Address P.O. Box 640 Aztec, NM 87410		8. Lease Name and Well No. Rosa UT 27 105H
3b. Phone No. (include area code) (505) 333-1849		9. API Well No. 30-039-31318
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface 962' FNL & 466' FWL, sec 19, T31N, R5W At proposed prod. zone 2583' FNL & 35' FWL, sec 24, T31N, R6W		10. Field and Pool, or Exploratory Basin Mancos
14. Distance in miles and direction from nearest town or post office* Approximately 58 miles East from Bloomfield NM		11. Sec., T., R., M., or Blk. and Survey or Area SHL: Section 19, T31N, R5W BHL: Section 24, T31N, R6W
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 466'	16. No. of Acres in lease 967.63 2518.04	17. Spacing Unit dedicated to this well West Rosa Unit Project Area 24,118.76 Acres
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 15'	19. Proposed Depth 12,347 MD / 6,809 TVD	20. BLM/BIA Bond No. on file UTB000178
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 6305' GR	22. Approximate date work will start* June 1, 2015	23. Estimated duration 1 month
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, shall be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan.
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification.
- Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature 	Name (Printed/Typed) Andrea Felix	Date 5-4-2015
Title Regulatory Specialist Senior		
Approved by (Signature) 	Name (Printed/Typed) D. Mantecón	Date 6/17/15
Title AFM	Office FFO	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on reverse)

WPX Energy Production, LLC, proposes to develop the Basin Mancos Pool at the above described location in accordance with the attached drilling and surface use plans.

The well pad surface is on lease on BLM surface within the Rosa Unit and will be co-located with the Rosa UT 101H / Rosa UT 102H / Rosa UT 103H / Rosa UT 104H / Rosa UT 106H / Rosa UT 107H / Rosa UT 108H / Rosa UT 109H & Rosa UT 110H.

This location has been archaeologically surveyed by LaPlata Archeology. Copies of their report have been submitted directly to the BLM.

New access road is approximately 71.0' on lease on BLM surface.

New pipeline is approximately 5,956.7' with 1,623.4' on lease on BLM surface and 4,333.31 on NM Game & Fish surface. A grant of easement is currently being processed by the NM Game & Fish portion for their portion of the pipeline.

DRILLING OPERATIONS
AUTHORIZED ARE SUBJECT TO
COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS"BLM'S APPROVAL OR ACCEPTANCE OF THIS
ACTION DOES NOT PRECLUDE THE APPLICANT FROM OBTAINING ANY OTHER
OPERATOR FROM OBTAINING ANY OTHER
AUTHORIZATION REQUIRED FOR OPERATIONS
ON FEDERAL AND INDIAN LANDS
NMOCDFVThis action is subject to technical
and procedural review pursuant to
43 CFR 3165.3 and appeal
pursuant to 43 CFR 3165.4

District IV
1220 S. St. Francis Drive, Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

Certificate Number 15269

WPX ENERGY

Operations Plan

(Note: This procedure will be adjusted on site based upon actual conditions)

DATE: 4/14/15 **FIELD:** Basin Mancos

WELL NAME: ROSA UT 27 #105H **SURFACE:** BLM

SH Location: NWNW Sec 19-31N-05W **ELEVATION:** 6305' GR

BH Location: SWNW Sec 24-31N-06W **MINERALS:** BLM
Rio Arriba, NM

MEASURED DEPTH: 12347'

I. GEOLOGY: Surface formation – San Jose

A. FORMATION TOPS: (KB)

Name	MD	TVD	Name	MD	TVD
Ojo Alamo	2498	2424	Point Lookout	5898	5634
Kirtland	2601	2521	Mancos	6211	5940
Picture Cliffs	3476	3346	Kickoff Point	6563	6365
Lewis	3763	3617	Top Target	7131	6804
Chacra	4772	4569	Landing Point	7641	7027
Cliff House	5613	5362	Base Target	7641	7027
Menefee	5661	5407			
			TD	12347	6809

- B. **MUD LOGGING PROGRAM:** Mudlogger on location from surface csg to TD.
- C. **LOGGING PROGRAM:** LWD GR from surface casing to TD.
- D. **NATURAL GAUGES:** Gauge any noticeable increases in gas flow. Record all gauges in Tour book and on morning reports.

II. DRILLING

- A. **MUD PROGRAM:** LSND mud (WBM) will be used to drill the 12-1/4" Surface hole and the 8 3/4" Directional Vertical hole of the wellbore. A LSND (WBM) or (OBM) will be used to drill the curve portion and the lateral portion of well. Treat for lost circulation as necessary. Obtain 100% returns prior to cementing. Notify Engineering of any mud losses.
- B. **BOP TESTING:** While drill pipe is in use, the pipe rams and the blind rams will be function tested once each trip. The anticipated reservoir is expected to be less than 5000 psi, so the BOPE will be tested to **250 psi (Low) for 5 minutes** and **5000 psi (High) for 10 minutes**. Pressure test surface casing to **1500psi for 30 minutes** and intermediate casing to **1500 psi for 30 minutes**. Utilize a BOPE Testing Unit with a recording chart and appropriate test plug for testing. **All tests and inspections will be recorded in the tour book as to time and results.**

III. MATERIALS

A. CASING PROGRAM:

CASING TYPE	OH SIZE (IN)	DEPTH (MD) (FT)	CASING SIZE (IN)	WEIGHT(LB)	GRADE
Surface	12.25"	320'+	9.625"	36#	J-55
Intermediate	8.75"	6461'	7"	23#	N-80
Long string	6.125"	12347'	4-1/2"	11.6#	P-110

B. FLOAT EQUIPMENT:

1. SURFACE CASING: 9-5/8" notched regular pattern guide shoe. Run (1) standard centralizer on each of the bottom (4) joints of Surface Casing.
2. INTERMEDIATE CASING: 7" cement nose guide shoe with a self-fill insert float. Place float collar one joint above the shoe. Install (1) centralizer on each of the bottom (3) joints and one standard centralizer every (3) joints to 2,500 ft. Run (1) centralizer at 2,700 ft., 2,500 ft., 2,300ft., 2,000ft., 1,500 ft., and 1,000 ft.
3. PRODUCTION CASING: Run 4-1/2" csg with cement nose guide Float Shoe + 2jts. of 4-1/2" casing + Landing Collar + 4-1/2" pup joint + 1 RSI (Sliding Sleeve). Centralizer program will be determined by Wellbore condition and when Lateral is evaluated by Geoscientists and Reservoir Engineers.
4. TIE-BACK CASING: None.

C. CEMENTING:

(Note: Volumes may be adjusted onsite due to actual conditions)

1. SURFACE: 5 bbl Fresh Water Spacer, 100 sx (160 cu.ft.) of 14.5 ppg Type I-II (Neat G) + 20% Fly Ash cement w/ 7.41 gal/sack mix water ratio @ 1.61 cu ft/sx yield. Calculated @ volume + 50% excess. WOC 12 hours. Test csg to 600psi. Total Volume: (160 cu-ft/100 sx/ Bbls). TOC at Surface.
2. INTERMEDIATE: 20 bbl (112 cu-ft) Mud Flush III spacer + Lead: +/- 700 sx Foamed 50/50 Poz Cement. 13.0 ppg + 0.1% Halad 766 + 0.2% Versaset + 1.5% Chem-Foamer 760 (Yield :1.43 cu-ft/ sk. / Vol: 1001 cu-ft / 178.3 Bbls.) + TAIL: 100 sx 13.5 #/gal. + 0.2% Versaset + 0.15% HALAD-766 (Yield: 1.28 cu-ft / sk / Vol: 128 cu-ft / 22.8 Bbls.). + Fresh Water Displacement (1,362 cu-ft / +/- 242 Bbls) + 100 sx Top-Out Cement Premium: Yield: (1.17 cu-ft/ sk / (Vol: 117 cu-ft / 20.8 Bbls). WOC 12 hrs. Test Casing to 1500 PSI for 30 minutes. Total Cement Volume: (900 sx / 1246 cu-ft / 222 bbls). Mix with +/- 84,000 SCF Nitrogen. TOC at surface.
3. PRODUCTION CASING: **Spacer #1**: 10 bbl (56 cu-ft) Water Spacer. **Spacer #2**: 40 bbl 9.5 ppg (224.6 cu-ft) Tuned Spacer III. **Spacer #3**: 10 bbl Water Spacer. **Lead Cement**: Extencem™ System. Yield 1.29 cu ft/sk, 13.5 ppg, (505 sx / 652 cu ft. / 116 bbls). **Tail Spacer**: 20 BBL of MMCR. **Displacement**: Displace w/ +/- 170 bbl Fr Water. Total Cement (652 cu ft / 116 bbls).

IV. COMPLETION**A. CBL**

1. Run CCL for perforating.

B. PRESSURE TEST

1. Pressure test 4-1/2" casing to 4500 psi max, hold at 1500 psi for 30 minutes. Increase pressure to Open RSI sleeves.

C. STIMULATION

1. Stimulate with approximately 87,500# 100 mesh sand and 4,620,000# 40/70 mesh sand in 6,188,000 gallons water for 14 stages.
2. Isolate stages with flow through frac plug.
3. Drill out frac plugs and flowback lateral.

D. RUNNING TUBING

1. Production Tubing: Run 2-3/8", 4.7#, J-55, EUE tubing with a SN on top of bottom joint. Land tubing in curve.
- Although this horizontal well will be drilled past the applicable setbacks, an unorthodox location application is not required because the completed interval in this well, as defined by 19.15.16.7 B(1) NMAC, will be entirely within the applicable setbacks. This approach complies with all applicable rules, including 19.15.16.14 A(3) NMAC, 19.15.16.14 B(2) NMAC, 19.15.16.15 B(2) NMAC, and 19.15.16.15. B(4) NMAC.
-

NOTE:

Installation of RSI sleeves at Toe of Lateral.

WPX Energy

T31N R5W Rosa Unit

Pad 27

ROSA UT 27 #105H - Slot A05

Wellbore #1

Plan: Design #2 16Mar15 sam

Standard Planning Report

13 April, 2015

WPX Planning Report

Database:	COMPASS-SANJUAN	Local Co-ordinate Reference:	Well ROSA UT 27 #105H (A05) - Slot A05
Company:	WPX Energy	TVD Reference:	KB @ 6330.00usft (Aztec 1000)
Project:	T31N R5W Rosa Unit	MD Reference:	KB @ 6330.00usft (Aztec 1000)
Site:	Pad 27	North Reference:	True
Well:	ROSA UT 27 #105H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #2 16Mar15 sam		

Project	T31N R5W Rosa Unit		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico West 3003		

Site	Pad 27		
Site Position:		Northing:	2,143,400.02 usft
From:	Lat/Long	Easting:	625,077.55 usft
Position Uncertainty:	0.00 usft	Slot Radius:	13.20 in
		Latitude:	36.8897153
		Longitude:	-107.4056260
		Grid Convergence:	0.26 °

Well	ROSA UT 27 #105H - Slot A05		
Well Position	+N/-S	-12.10 usft	Northing:
	+E/-W	12.63 usft	Easting:
Position Uncertainty	0.00 usft	Wellhead Elevation:	0.00 usft
		Latitude:	36.8896821
		Longitude:	-107.4055828
		Ground Level:	6,305.00 usft

Wellbore	Wellbore #1		
Magnetics	Model Name	Sample Date	Declination (°)
	IGRF2010	12/18/2014	9.33
			Dip Angle (°)
			63.57
			Field Strength (nT)
			50,520

Design	Design #2 16Mar15 sam		
Audit Notes:			
Version:	Phase:	PLAN	Tie On Depth:
			0.00
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W
	(usft)	(usft)	(usft)
	0.00	0.00	0.00
			Direction (°)
			270.23

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
420.00	0.00	0.00	420.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,180.70	15.21	162.94	1,171.79	-95.99	29.45	2.00	2.00	0.00	162.94	
6,563.02	15.21	162.94	6,365.48	-1,446.29	443.81	0.00	0.00	0.00	0.00	
7,641.28	92.66	270.23	7,027.00	-1,624.02	-220.09	9.00	7.18	9.95	106.05	PP Rosa 27 #105H
12,347.00	92.66	270.23	6,809.00	-1,604.90	-4,920.71	0.00	0.00	0.00	0.00	TD / PBHL Rosa 27 #

WPX Planning Report

Database: COMPASS-SANJUAN
Company: WPX Energy
Project: T31N R5W Rosa Unit
Site: Pad 27
Well: ROSA UT 27 #105H
Wellbore: Wellbore #1
Design: Design #2 16Mar15 sam

Local Co-ordinate Reference: Well ROSA UT 27 #105H (A05) - Slot A05
TVD Reference: KB @ 6330.00usft (Aztec 1000)
MD Reference: KB @ 6330.00usft (Aztec 1000)
North Reference: True
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
320.00	0.00	0.00	320.00	0.00	0.00	0.00	0.00	0.00	0.00
9 5/8"									
420.00	0.00	0.00	420.00	0.00	0.00	0.00	0.00	0.00	0.00
Start Build 2.00									
500.00	1.60	162.94	499.99	-1.07	0.33	-0.33	2.00	2.00	0.00
1,000.00	11.60	162.94	996.05	-55.94	17.17	-17.39	2.00	2.00	0.00
1,180.70	15.21	162.94	1,171.79	-95.99	29.45	-29.84	2.00	2.00	0.00
Hold 15.21 Inclination									
1,500.00	15.21	162.94	1,479.90	-176.09	54.04	-54.74	0.00	0.00	0.00
2,000.00	15.21	162.94	1,962.38	-301.53	92.53	-93.74	0.00	0.00	0.00
2,500.00	15.21	162.94	2,444.85	-426.97	131.02	-132.73	0.00	0.00	0.00
3,000.00	15.21	162.94	2,927.33	-552.41	169.51	-171.73	0.00	0.00	0.00
3,500.00	15.21	162.94	3,409.81	-677.85	208.00	-210.72	0.00	0.00	0.00
4,000.00	15.21	162.94	3,892.28	-803.28	246.50	-249.72	0.00	0.00	0.00
4,500.00	15.21	162.94	4,374.76	-928.72	284.99	-288.72	0.00	0.00	0.00
5,000.00	15.21	162.94	4,857.24	-1,054.16	323.48	-327.71	0.00	0.00	0.00
5,500.00	15.21	162.94	5,339.71	-1,179.60	361.97	-366.71	0.00	0.00	0.00
6,000.00	15.21	162.94	5,822.19	-1,305.04	400.47	-405.70	0.00	0.00	0.00
6,461.00	15.21	162.94	6,267.03	-1,420.69	435.96	-441.66	0.00	0.00	0.00
7"									
6,500.00	15.21	162.94	6,304.67	-1,430.48	438.96	-444.70	0.00	0.00	0.00
6,563.02	15.21	162.94	6,365.48	-1,446.29	443.81	-449.61	0.00	0.00	0.00
Start Build/Turn DLS 9.00 TFO 106.05									
7,000.00	37.59	249.75	6,765.26	-1,551.39	331.13	-337.35	9.00	5.12	19.87
7,500.00	80.35	267.00	7,018.40	-1,620.65	-79.40	72.89	9.00	8.55	3.45
7,641.28	92.66	270.23	7,027.00	-1,624.02	-220.09	213.57	9.00	8.71	2.29
POE at 92.65 Inclination									
8,000.00	92.66	270.23	7,010.38	-1,622.57	-578.42	571.90	0.00	0.00	0.00
8,500.00	92.66	270.23	6,987.22	-1,620.53	-1,077.88	1,071.36	0.00	0.00	0.00
9,000.00	92.66	270.23	6,964.06	-1,618.50	-1,577.34	1,570.83	0.00	0.00	0.00
9,500.00	92.66	270.23	6,940.89	-1,616.47	-2,076.80	2,070.29	0.00	0.00	0.00
10,000.00	92.66	270.23	6,917.73	-1,614.44	-2,576.26	2,569.75	0.00	0.00	0.00
10,500.00	92.66	270.23	6,894.57	-1,612.40	-3,075.71	3,069.22	0.00	0.00	0.00
11,000.00	92.66	270.23	6,871.40	-1,610.37	-3,575.17	3,568.68	0.00	0.00	0.00
11,500.00	92.66	270.23	6,848.24	-1,608.34	-4,074.63	4,068.14	0.00	0.00	0.00
12,000.00	92.66	270.23	6,825.08	-1,606.31	-4,574.09	4,567.61	0.00	0.00	0.00
12,347.00	92.66	270.23	6,809.00	-1,604.90	-4,920.71	4,914.23	0.00	0.00	0.00
TD at 12347.00									

Design Targets

Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
TD / PBHL Rosa 27 #10 - plan hits target center - Point	0.00	0.00	6,809.00	-1,604.90	-4,920.71	2,141,761.04	620,176.76	36.8852725	-107.4224081
PP Rosa 27 #105H - plan hits target center - Point	0.00	0.00	7,027.00	-1,624.02	-220.09	2,141,762.98	624,877.42	36.8852212	-107.4063353

WPX
Planning Report

Database:	COMPASS-SANJUAN	Local Co-ordinate Reference:	Well ROSA UT 27 #105H (A05) - Slot A05
Company:	WPX Energy	TVD Reference:	KB @ 6330.00usft (Aztec 1000)
Project:	T31N R5W Rosa Unit	MD Reference:	KB @ 6330.00usft (Aztec 1000)
Site:	Pad 27	North Reference:	True
Well:	ROSA UT 27 #105H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #2 16Mar15 sam		

Casing Points




Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (in)	Hole Diameter (in)
320.00	320.00	9 5/8"	9.62	12.25
6,461.00	6,267.03	7"	7.00	8.75

Plan Annotations


Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
420.00	420.00	0.00	0.00	Start Build 2.00
1,180.70	1,171.79	-95.99	29.45	Hold 15.21 Inclination
6,563.02	6,365.48	-1,446.29	443.81	Start Build/Turn DLS 9.00 TFO 106.05
7,641.28	7,027.00	-1,624.02	-220.09	POE at 92.65 Inclination
12,347.00	6,809.00	-1,604.90	-4,920.71	TD at 12347.00



Well Name: ROSA UT 27 #105H
Surface Location: Pad 27
NAD 1927 (NADCON CONUS) , US State Plane 1927 (Exact solution) New Mexico West 3003
Ground Elevation: 6305.00
+N/-S +E/-W Northing Easting Latitude Longitude Slot
0.00 0.00 2143387.97 625090.23 36.8896821 -107.4055827 A05
KB @ 6330.00usft (Aztec 1000)



DESIGN TARGET DETAILS										Project: T31N R5W Rosa Unit	
Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Shape	Point	Site: Pad 27	Well: ROSA UT 27 #105H
PP Rosa 27 #105H	7027.00	-1624.02	-220.09	2141762.98	624877.42	36.8852212	-107.4063353	Point		Design #2 16Mar15 sam	
TD / PBHL Rosa 27 #105H	6809.00	-1604.90	-4920.71	2141761.04	620176.76	36.8852726	-107.4224081	Point			
- plan hits target center											
- plan hits target center											



3. Cuttings disposal construction, operation and closure will be permitted and regulated under NMOCD Rule 17.

After the completion phases and pipeline installation, portions of the project area not needed for operation will be reclaimed. When all wells are plugged, final reclamation will occur within the remainder of the project area. Reclamation is described in detail in the Reclamation Plan (Appendix C).

7.0 Methods for Handling Waste

A. Cuttings



1. Drilling operations will utilize a closed-loop system. Drilling of the horizontal laterals will be accomplished with water-based mud. All cuttings will be placed in roll-off bins and hauled to Section 23 cuttings disposal and/or a cuttings disposal at Section 25 recycling containment. WPX will follow Onshore Oil and Gas Order No. 1 regarding the placement, operation, and removal of closed-loop systems. No blow pit will be used.
2. If oil-based mud drilling is used, a closed-loop system will be used to minimize potential impacts to surface and groundwater quality. A 30-mil reinforced liner will be placed under the drill rig mats and all drilling machinery. This area will be enclosed by a containment berm and ditches, which will drain to sump areas for spill prevention and control. The containment berm will be ramped to allow access to the solids control area.
3. Closed-loop tanks will be adequately sized for containment of all fluids.

B. Drilling Fluids

1. Drilling fluids will be stored onsite in above-ground storage tanks. Upon termination of drilling operations, the drilling fluids will be recycled and transferred to other permitted closed-loop systems or returned to the vendor for reuse, as practical. All residual fluids will be hauled to a commercial disposal facility.

C. Spills

1. Any spills of non-freshwater fluids will be immediately cleaned up and removed to an approved disposal site.

D. Sewage

1. Portable toilets will be provided and maintained during construction, as needed (see Figure 11 and 12 in Appendix B for the location of toilets).

E. Garbage and other waste material

1. All garbage and trash will be placed in a metal trash basket. The trash and garbage will be hauled off site and dumped in an approved landfill, as needed.

F. Hazardous Waste

1. No chemicals subject to reporting under Superfund Amendments and Reauthorization Act Title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of these wells.
2. No extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of these wells.
3. All fluids (i.e., scrubber cleaners) used during washing of production equipment will be properly disposed of to avoid ground contamination or hazard to livestock or wildlife.

Directions from the Intersection of US Hwy 550 & US Hwy 64

in Bloomfield, NM to WPX Energy Production, LLC Rosa UT 27 #105H

962' FNL & 466' FWL, Section 19, T31N, R5W, N.M.P.M., Rio Arriba County, NM

Latitude: 36.889688°N Longitude: 107.406186°W Datum: NAD1983

From the intersection of US Hwy 550 & US Hwy 64 in Bloomfield, NM, travel Easterly on US Hwy 64 for 38.0 miles to Mile Marker 102.3 to State Hwy 527 (Simms Hwy);

Go Left (North-westerly) on State Hwy 527 (Simms Hwy) for 7.9 miles to Rosa Road @ La Jara Station;

Go Right (Northerly) on Rosa Road for 6.5 miles to 4-way intersection;

Go Left which is straight (North-easterly) remaining on Rosa Road for 5.9 miles to fork in road;

Go Right (Easterly) for 0.25 miles to fork in roadway;

Go Right which is straight (Easterly) for 0.1 miles to fork in roadway;

Go Left which is straight (Easterly) for 1.3 miles to fork in roadway;

Go Right (Westerly) for 0.1 miles to new access on right-hand side of roadway which continues for 71.0' to staked WPX Rosa UT 27 #105H location.

