District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505State of New Mexico Santa Fe, NM 87505Form C-144 Revised June 6, 2013District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
Pit, Below-Grade Tank, or 12962 Proposed Alternative Method Permit or Closure Plan Application Type of action: Below grade tank registration Permit of a pit or proposed alternative method JUN 09 2015 45-09190 Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration JUN 09 2015 Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1. Operator: BP America Production CompanyOGRID #:778 Address:200 Energy Court, Farmington, NM 87401 Facility or well name:Florance 46 API Number:3004509190OCD Permit Number: U/L or Qtr/QtrH Section29Township30NRange8W County:San Juan Center of Proposed Design: Latitude36.78476 Longitude107.69418 NAD: [_1927 ⊠ 1983 Surface Owner: ⊠ Federal [] State [] Private [] Tribal Trust or Indian Allotment
 2. Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Other Volume: bbl Dimensions: L x W x D
3. Tank★C 𝔅 𝔅/𝔅/𝔅 𝔅 𝔅 𝔅𝔅𝔅𝔅 Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank ★ C 𝔅 𝔅/𝔅/𝔅 𝔅 𝔅 𝔅 𝔅 Tank 𝔅 𝔅𝔅 Volume: 21.0 bbl Type of fluid: Produced water Tank Construction material: Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other _Single walled/double bottomed Liner type: Thickness mil HDPE PVC Other

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

17

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.
 Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting							
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells							
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA						
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No						
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No						
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No						
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map							
Below Grade Tanks							
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)							
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	🗌 Yes 🗌 No						
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 							
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site							
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 							
Temporary Pit Non-low chloride drilling fluid							
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,							
or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No						
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No						
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock							
 watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						
Permanent Pit or Multi-Well Fluid Management Pit							
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa							
 lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 							
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of							
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site							
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 							
10. <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 N <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the down and the second sec</i>							
 attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC) NMAC						
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC							
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 	15.17.9 NMAC						
Previously Approved Design (attach copy of design) API Number: or Permit Number:							
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC							
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do	cuments are						
<i>attached.</i> Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC							
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC							
 A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 	.15.17.9 NMAC						
and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC							
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.3 NMAC							
Previously Approved Design (attach copy of design) API Number: or Permit Number:							

12 The mean This Permit Application Checklist: Subsection B 191517.9 NMAC Mathematic Line Look of the Application Phase indicates by a check mark in the back, that the documents are analytication. Phase indicates by a check mark in the back, that the documents are analytication. Phase indicates of 191517.10 NMAC Clinited Engineering Design Plans - based upon the appropriate requirements of 191517.11 NMAC Design Engineering Design Plans - based upon the appropriate requirements of 191517.11 NMAC Design Engineering Design Plans - based upon the appropriate requirements of 191517.11 NMAC Departing and Maintenuce Plans - based upon the appropriate requirements of 191517.12 NMAC Departing and Maintenuce Plans - based upon the appropriate requirements of 191517.12 NMAC Departing and Maintenuce Plans - based upon the appropriate requirements of 191517.12 NMAC Departing and Maintenuce Plans - based upon the appropriate requirements of 191517.13 NMAC Departing and Maintenuce Plans - based upon the appropriate requirements of 191517.13 NMAC Departing and Maintenuce Plans - based upon the appropriate requirements of 191517.13 NMAC Departing and Maintenuce Plans - based upon the appropriate requirements of 191517.13 NMAC Departing and Maintenuce Plans Departing and Maintenuce Plans Departing and Maintenuce Plans Departing and Maintenuce Plans Deparetring andeplans		
Proposed Closure: 19.15.17.13 NNAC Instructions: Prease complete the applicable baxes, Baxes 14 through 18, in regards to the proposed closure plan. Multi-well Fluid Management Pit Type: Drilling Workover Energancy Cavitation PRA Permanent Pit Below-grade Tank Multi-well Fluid Management Pit Proposed Closure Method: Waste Excavation and Removal Closure Plan. Multi-well Fluid Management Pit Implace Burial On-site Closure Method Multi-well Fluid Management Pit Maste Excavation and Removal Closure Plan. Multi-well Fluid Management Pit Waste Excavation and Removal Closure Plan. Protocols and Procedures - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Confirmation Sampling Plan (flapelicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Stite Reclamation Plan - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Stite Reclamation Plan - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Stite Reclamation Plan - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Stite Reclamation Plan - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Instructions: Each sting criteria requires a demonstration of compliance in the closure plan. Recoregatation Plan - bas	 Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	e documents are
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items nust be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (of thiquids, drilling fuldis and drilling tudids, and illing fuldis and artiflu cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 25 feet below the bottom of the buried waste.	Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial	Pluid Management Pit
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each sting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 25 feet below the bottom of the buried waste.	Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA Yes No NA Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No Yes No<th>Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency.</th><th></th>	Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency.	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA NA Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste	NA NA Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Yes No Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Yes No Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. Yes No • NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Yes No Within 300 feet of a wetland. Yes Inspection (certification map; Topographic map; Visual inspection (certification) of the proposed site Yes No	- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	□ NA
at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality	 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Image: Proposed site	at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	
	Within 300 feet of a wetland.	
		Yes No

Within the area overlying a subsurface mine. - Writen confirmation or verification or map from the NM EMNRD-Mining and Mineral Division - Yes No Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map - Yes No Within a 100-year floodplain. - - Yes No * FEMA map - Yes No * Gonstite Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check must in the box, that the documents are attached. - - Proof of Surface Owner Notice - based upon the appropriate requirements of 19.15.17.10 NMAC - - - Proof of Surface Owner Notice - based upon the appropriate requirements of 19.15.17.10 NMAC -	- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No						
Signature:		🗌 Yes 🗌 No						
Within a 100-year floodplain. PEMA map ⁶ On-Site Closure Plan Checklist: (19.15.17.13 NMAC) <i>Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.</i> ⁶ On-Site Closure Plan Checklist: (19.15.17.13 NMAC) <i>Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.</i> ⁶ On-Site Closure Plan Checklist: (19.15.17.13 NMAC) <i>Instructions: - based upon the appropriate requirements of</i> 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan of Temporary Plif (for in-place burial of a <i>trying</i> pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan of Temporary Plif (for in-place burial of a <i>trying</i> pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan in the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC <i>Tr.</i> Coperator Application Certification: Interest certification: Intereste cerity that the information submitted with th	- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological							
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. by a check mark in the box, that the documents are attached. check mark in the box, that the documents are attached. by a check mark in the box, that the documents are attached. check mark in the box, that the documents are attached. by a check mark in the box, that the documents are attached. check mark in the box, that the documents are attached. by a check mark in the box, that the documents are attached. check mark in the box, that the documents are attached. check mark in the box, that the documents are attached. check mark in the box, that the documents are attached upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan of Burilicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan (3 Burilicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cutings or in case on-site closure standards cannot be achieved) Sign Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Procediation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Procedification Plan - based upon the appropriate requirements of Subsection I of 19.	Within a 100-year floodplain.							
by a check mark in the box, that the documents are attached.		an. Please indicate,						
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief. Name (Print):	by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC							
Name (Print):	Operator Application Certification:							
Signature: Date: e-mail address: Telephone: 18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: \$\frac{3}{2015}\$ Title: Construction (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report.								
e-mail address: Telephone: B. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: <u>8/3/2015</u> Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this	Name (Print): Title:							
18. OCD Approval: Permit Application (including closure plan) Image: Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Image: Closure Plan (only) OCD Conditions (see attachment) Title: Image: Closure Plan (only) OCD Permit Number: Image: Closure Plan (only) 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities.	Signature: Date:							
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:	e-mail address: Telephone:							
^{19.} <u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC <i>Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report.</i> <i>The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this</i>	OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:							
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this	OCD Representative Signature: Approval Date: 8/3/2	2015						
section of the form until an approved closure plan has been obtained and the closure activities have been completed.	OCD Representative Signature: Approval Date: Approval Date:	2015						
Closure Completion Date: 1/7/2011	OCD Representative Signature:	the closure report.						
 20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain. 	OCD Representative Signature: Approval Date: Approval Date: Title: OCD Permit Number: ^{19.} <u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.						
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. □ Proof of Closure Notice (surface owner and division) □ Proof of Deed Notice (required for on-site closure for private land only) □ Plot Plan (for on-site closures and temporary pits) ○ Confirmation Sampling Analytical Results (if applicable) □ Waste Material Sampling Analytical Results (required for on-site closure) ○ Disposal Facility Name and Permit Number ○ Soil Backfilling and Cover Installation □ Re-vegetation Application Rates and Seeding Technique ○ Site Reclamation (Photo Documentation) ○ On-site Closure Location: Latitude 36.78476 Longitude -107.69418 NAD: □1927 □1983	OCD Representative Signature:	the closure report. complete this						
Closure Method:	OCD Representative Signature: Approval Date: Approval Date: Title: OCD Permit Number: ^{19.} <u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.						

*

Operator Closure Certification:

22.

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Joh Pare	Date:June 9, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Florance 46 API No. 3004509190 Unit Letter H, Section 29, T30N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. No notice was made due to misunderstanding of the BGT notice requirements at that time.
- BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 No notice was made due to misunderstanding of the BGT notice requirements at

No notice was made due to misunderstanding of the BGT notice requirements a that time.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	0.24
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	0.81
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

State of New Mexico Energy Minerals and Natural Resources

> Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action OPERATOR Initial Report Final Report Name of Company: BP Contact: Jeff Peace Telephone No.: 505-326-9479 Address: 200 Energy Court, Farmington, NM 87401 Facility Name: Florance 46 Facility Type: Natural gas well Mineral Owner: Federal API No. 3004509190 Surface Owner: Federal LOCATION OF RELEASE Range Feet from the North/South Line East/West Line Unit Letter Section Township Feet from the County: San Juan 29 30N 8W 1,650 North 950 East Η Latitude 36.78476 Longitude 107.69418 NATURE OF RELEASE Type of Release: none Volume of Release: N/A Volume Recovered: N/A Source of Release: below grade tank - 21 bbl Date and Hour of Occurrence: Date and Hour of Discovery: Was Immediate Notice Given? If YES, To Whom? Yes No Not Required By Whom? Date and Hour Was a Watercourse Reached? If YES, Volume Impacting the Watercourse. Yes No If a Watercourse was Impacted, Describe Fully.* Describe Cause of Problem and Remedial Action Taken.* Sampling of the soil beneath the BGT was done during removal to ensure no soil impacts from the BGT. Soil analysis resulted in TPH, BTEX and chloride below standards. Analysis results are attached. Describe Area Affected and Cleanup Action Taken.* BGT was removed and the area underneath the BGT was sampled. The area under the BGT was backfilled and compacted and is still within the active well area. I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations. OIL CONGEDUATION DIVISION

Signature: Sthe Peace		NSERVATION	DIVISION
Printed Name: Jeff Peace	Approved by Environmental	Specialist:	
Title: Field Environmental Coordinator	Approval Date:	Date:	
E-mail Address: peace.jeffrey@bp.com	Conditions of Approval:		Attached
Date: June 9, 2015 Phone: 505-326-9479			

* Attach Additional Sheets If Necessary

BLAGG ENGINEERING, INC.	2004500100
	API #: 3004509190
(505) 632-1199	
FIELD REPORT: BGT CONFIRMATION TEMP. PIT CLOSURE / RELEASE INVESTIGATION (other)	PAGE No: _1 of _1
SITE INFORMATION: SITE NAME: FLORANCE # 46	DATE STARTED: 11/15/10
QUAD/UNIT: H SEC: 29 TWP: 30N RNG: 8W PM: NM CNTY: SJ ST: NM	DATE FINISHED:
QTR-QTR/FOOTAGE: 1,650'N / 950'E SE/NE LEASE TYPE: FEDERAL STATE / FEE / INDIAN	ENVIRONMENTAL
LEASE #: SF080597 PROD. FORMATION: MV CONTRACTOR: BP - J. NUNEZ	SPECIALIST: NJV
REFERENCE POINT: WELL HEAD (W.H.) GPS COORD.: 36.78486 X 107.694	02 GL ELEV.: 6,193'
	ARING FROM W.H.: 82', S57.5W
2) GPS COORD.: DISTANCE/BE	ARING FROM W.H.:
3) GPS COORD.: DISTANCE/BE	ARING FROM W.H.:
4) GPS COORD.: DISTANCE/BE	ARING FROM W.H.:
LAB INFORMATION: CHAIN OF CUSTODY RECORD(S): HALL	OVM READING
1) SAMPLE ID: 5PC - TB @ 6' (21 BBL BGT) SAMPLE DATE: 12/17/10 SAMPLE TIME: 1300 LAB ANALYSIS: 418.1/2	8015B/8021B/300.0 (CI) NA
2) SAMPLE ID:	
3) SAMPLE ID:	
4) SAMPLE ID:	
SOIL DESCRIPTION: SOIL TYPE: SAND SILTY SAND SILT / SILTY CLAY / GRAVEL / OT	HER
SOIL COLOR: PALE YELLOWISH BROWN	
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / SUBJECT /	
CONSISTENCY (NON COHESIVE SOILS): LOOSE FIRM DENSE / VERY DENSE DENSITY (COHESIVE CLAYS & SILTS): SOFT MOISTURE: DRY / SLIGHTLY MOIST MOIST WET SATURATED / SUPER SATURATED HC ODOR DETECTED: YES NO EXPL	
MOISTURE: DRY/SLIGHTLYMOIST MOIST WET SATURATED / SUPER SATURATED HC ODOR DETECTED: YES NO EXPL SAMPLE TYPE: GRAB COMPOSITE # OF PTS. 5	ANATION -
DISCOLORATION/STAINING OBSERVED: YES NO EXPLANATION -	
ANY AREAS DISPLAYING WETNESS: YES NO EXPLANATION -	
ADDITIONAL COMMENTS: NO APPARENT EVIDENCE OF A RELEASE OBSERVED FROM BGT.	
EXCAVATION DIMENSIONS (if applicable): NA ft. X NA ft. X NA ft. Cubic yards ex	cavated (if applicable): NA
	CALIBY READ. = ppm $RF = 0.52$ CALIB, GAS = ppm $RF = 0.52$
VVELL	am/pm DATE:
	MISCELL. NOTES
PROD.	
	VO: N1115880 AYKEY: ZVALEN0LAB
PBGTL T.B. ~ 5'	
B.G. BERM B	GT SIDEWALLS VISIBLE
WOODEN COMPRESSOR	W - SINGLE WALLED
	B - DOUBLE BOTTOM
95 BBL BGT	
FENCE	
X - S.P.D.	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~ = APPROX.;	lagnetic declination: 10 ° E
T,B, = TANK BOTTOM; PBGTL = PREVIOUS BELOW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL.	
TRAVEL NOTES: CALLOUT: 11/12/10 ONSITE: 11/15/10 - After. (Sci	nea.)

revised: 10/02/10

	and shares and a state of a state					
CLIENT:	Blagg Engineering			Client Sample I	D: 5PC-TB(@5'-21 BBL BGT
Lab Order:	1012865			Collection Dat	te: 12/17/20	10 1:00:00 PM
Project:	Florance #46			Date Receive	d: 12/23/20	10
Lab ID:	1012865-01			Matri	ix: SOIL	
Analyses		Result	PQL	Qual Units	DF	Date Analyzed
EPA METHOD	8015B: DIESEL RANGE	ORGANICS				Analyst: JB
Diesel Range C	Irganics (DRO)	13	10	mg/Kg	1	1/3/2011 1:26:16 PM
Surr: DNOP		96.1	81.8-129	%REC	1	1/3/2011 1:26:16 PM
EPA METHOD	8015B: GASOLINE RAN	GE				Analyst: NSB
Gasoline Range	e Organics (GRO)	ND	5.0	mg/Kg	1	12/28/2010 6:36:04 PM
Surr: BFB		89.9	89.7-125	%REC	1	12/28/2010 6:36:04 PM
EPA METHOD	8021B: VOLATILES		×			Analyst: NSB
Benzene		0.24	0.050	mg/Kg	1	12/28/2010 6:36:04 PM
Toluene		0.45	0.050	mg/Kg	1	12/28/2010 6:36:04 PM
Ethylbenzene		ND	0.050	mg/Kg	1	12/28/2010 6:36:04 PM
Xylenes, Total		0.12	0.10	mg/Kg	1	12/28/2010 6:36:04 PM
Surr: 4-Brom	ofluorobenzene	99.8	88.9-151	%REC	1	12/28/2010 6:36:04 PM
EPA METHOD	300.0: ANIONS					Analyst: SRM
Chloride		ND	7.5	mg/Kg	5	12/28/2010 12:14:40 AM
EPA METHOD	418.1: TPH					Analyst: JB
Petroleum Hydr	ocarbons, TR	ND	20	mg/Kg	1	12/29/2010

Hall Environmental Analysis Laboratory, Inc.

Date: 07-Jan-11

Qualifiers:

* Value exceeds Maximum Contaminant Level

E Estimated value

J Analyte detected below quantitation limits

NC Non-Chlorinated

PQL Practical Quantitation Limit

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

MCL Maximum Contaminant Level

ND Not Detected at the Reporting Limit

S Spike recovery outside accepted recovery limits

QA/QC SUMMARY REPORT

Client: Blagg Engir	neering										
Project: Florance #4	6								Work	Order:	1012865
Analyte	Result	Units	PQL	SPK Val SP	PK ref	%Rec L	owLimit Hi	ghLimit	%RPD	RPDLimit	Qual
Method: EPA Method 300.0: A	nlons										
Sample ID: MB-25014		MBLK				Batch ID:	25014	Analys	is Date:	12/27/2010	5:51:39 PM
Chloride	ND	mg/Kg	1.5								
Sample ID: LCS-25014		LCS				Batch ID:	25014	Analys	is Date:	12/27/2010	6:09:04 PM
Chloride	14.18	mg/Kg	1.5	15	0	94.5	90	110		•••• • • • ••• • • • • • • • • • • • •	
Method: EPA Method 418.1: TI	PH										
Sample ID: MB-25004		MBLK				Batch ID:	25004	Analys	is Date:		12/29/2010
Petroleum Hydrocarbons, TR	ND	mg/Kg	20								
Sample ID: LCS-25004		LCS				Batch ID:	25004	Analys	is Date:		12/29/2010
Petroleum Hydrocarbons, TR	96.90	mg/Kg	20	100	0	96.9	86.8	116			
Sample ID: LCSD-25004		LCSD				Batch ID:	25004	Analys	is Date:		12/29/2010
Petroleum Hydrocarbons, TR	98.18	mg/Kg	20	100	0	98.2	86.8	116	1.31	16.2	
Method: EPA Method 8015B: D	Diesel Range	Organics									
Sample ID: MB-25044	Ū	MBLK				Batch ID:	25044	Analys	is Date:	1/3/2011	9:57:28 AM
Diesel Range Organics (DRO)	ND	mg/Kg	10								
Sample ID: LCS-25044		LCS				Batch ID:	25044	Analys	is Date:	1/3/2011 1	0:31:34 AM
Diesel Range Organics (DRO)	45.92	mg/Kg	10	50	0	91.8	66.2	120			
Sample ID: LCSD-25044		LCSD				Batch ID:	25044	Analysi	is Date:	1/3/2011 1	1:05:42 AM
Diesel Range Organics (DRO)	48.92	mg/Kg	10	50	0	97.8	66.2	120	6.33	14.3	
Method: EPA Method 8015B: G	asoline Ran	ae				francisco de sole foid a definir del faciente de sus dessen					
Sample ID: MBLK-24987		MBLK				Batch ID:	24987	Analysi	s Date:	12/24/2010	4:39:10 AM
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0								
Sample ID: LCS-24987		LCS				Batch ID:	24987	Analysi	s Date:	12/24/2010	4:09:14 AM
Gasoline Range Organics (GRO)	25.57	mg/Kg	5.0	25	0	102	95.7	120			
Method: EPA Method 8021B: V	olatiles										
Sample ID: LCS-24987		LCS				Batch ID:	24987	Analysi	s Date:	12/28/2010	3:35:32 PM
Benzene	1.023	mg/Kg	0.050	1	0	102	83.3	107			
Toluene	0.9712	mg/Kg	0.050	1	0	97.1	74.3	115			
Ethylbenzene	1.021	mg/Kg	0.050	1	0	102	80.9	122			
Xylenes, Total	3.194	mg/Kg	0.10	3	0	106	85.2	123			

Qualifiers:

E Estimated value

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

H Holding times for preparation or analysis exceeded

NC Non-Chlorinated

R RPD outside accepted recovery limits

Hall Environmental Analysis Laboratory, Inc.

	Sample	Receipt C	hecklist		
Client Name BLAGG			Date Received	::	12/23/2010
Work Order Number 1012865			Received by	AMG	
Checklist completed by:		2/22) (Date	0	bels checked by:	Initials
Matrix:	Carrier name:	Priority US	Mail		
Shipping container/cooler in good condition?		Yes 🖌	No	Not Present]
Custody seals intact on shipping container/cod	oler?	Yes 🖌	No 🗌	Not Present	Not Shipped
Custody seals intact on sample bottles?		Yes	No 🗌	N/A]
Chain of custody present?		Yes 🖌	No 🗌		
Chain of custody signed when relinquished an	d received?	Yes 🖌	No 🗌		
Chain of custody agrees with sample labels?		Yes 🔽	No		
Samples in proper container/bottle?		Yes 🗹	No		
Sample containers intact?		Yes 🖌	No 🗌		
Sufficient sample volume for indicated test?		Yes 🖌	No 🗌		
All samples received within holding time?		Yes 🖌	No 🗌		Number of preserved
Water - VOA vials have zero headspace?	No VOA vials subm	itted 🗹	Yes	No 🗌	bottles checked for pH:
Water - Preservation labels on bottle and cap	match?	Yes	No	N/A	
Water - pH acceptable upon receipt?		Yes	No	N/A	<2 >12 unless noted below.
Container/Temp Blank temperature?		3.0°	<6° C Acceptabl	9	Delow.
COMMENTS:			If given sufficient	time to cool.	
				-	
Client contacted	Date contacted:		Perso	n contacted	
Contacted by:	Regarding:				
Contacted by: Comments: <u>Spoke wrt</u> BTEX, <u>not</u> full 80	h Nelson	12/2	12/23/10	2, Ohlu	4912123 - & Waints
Corrective Action					

			stody Record	Turn-Around Time:						10												•
Client: BLACE ENER. (BP AMERICA				Standard				ANALYSIS LABORATORY														
				Project Name:				www.hallenvironmental.com														
Mailing Address: P.O. BOX 87				FLORANCE #46				4901 Hawkins NE - Albuquerque, NM 87109														
				Project #:					el. 50						505-							
BLFD. NM 87413 Phone #: (505) 632 - 1199												and the second se	of the local division of the local divisiono	COLUMN TWO IS NOT	Req	-	Contraction of the local division of the loc					
email or Fax#:				Project Manager:				(yh	sel))4)								
QA/QC Package:				NELSON VELEZ M Sampler: NELSON VELEZ				TPH (Gas only)	as/Dies					04,SC	PCB's			(0)		Comor C	Jan 1	
Accreditation				Sampler NEISal JEEFZ			TMB's (80278)) H	(C					0 ₂ ,F	8082			.00.		V	5	
NELAP Other				On fce with WYeskin and Northernau said				+	15B	418.1)	04.1	(HH)		03,N	-		(A	in.		4	or N)	
EDD (Type)				Sample Température				BE	d 80	pd 4	od 5	or F	etals	SI,NC	sides	(A)	0^-	w		2001	12	
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type		BTEX + MTBE	BTEX + MTBE	TPH Method 8015B (Gas/Diesel)	TPH (Method 4	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE		5 PT PANDONITE	1 - 1	
12/10/10	1300	SOIL	5PC-TB 05- 21 BBL BET	4021	COOL		\checkmark		\checkmark	\checkmark		_						\checkmark		Y	F	
												_										
																				_		
													_									
																				+		
																	-					
Date: Time: Relinquished by: 12 21 1 3 1445 Date: Time: Relinquished by:			Received by: Received by:	Remarks: 35 TPH(8015B) - DRO + GRO ON-Y.																		



