

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-039-31309
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: Many Canyons 24-03 8
8. Well Number #4H
9. OGRID Number 162928
10. Pool name or Wildcat West Lindrith Gallup-Dakota
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6878' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	2. Name of Operator Energen Resources Corporation
3. Address of Operator 2010 Afton Place, Farmington, NM 87401	4. Well Location Unit Letter P : 1230 feet from the South line and 716 feet from the East line Section 8 Township 24N Range 03W NMPM County Rio Arriba
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: **Spud** ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/1/15 Spud well @ 12:00 PM on 7/1/15. Drill 12.25" hole to 215'. Ream 12.25" hole out to 17.50" from 0'-215'. Run 5 jts of 13.375", 48#, H-40 ST&C csg, set @ 208'. Cement with 270 sks (318 cf) Class G + 1% CaCl +.50#/sk Poly-e-flake. Circulated 19 bbls of cmt to surface. Plug down @ 12:45 on 7/3/15. John Durham (NMCD) on location to witness csg and cement job. WOC. PT csg to 1400#, 30 minutes, tested ok.
Rig released on 7/6/15.✓

OIL CONS. DIV DIST. 3

JUL 13 2015

Spud Date:

7/01/15

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Anna Stotts

TITLE

Regulatory Analyst

DATE

7/10/15

Type or print name Anna Stotts

E-mail address:

astotts@energen.com

PHONE

324-4154

For State Use Only

APPROVED BY

[Signature]

TITLE

DEPUTY OIL & GAS INSPECTOR

DISTRICT #3

DATE

7/27/15

Conditions of Approval (if any):

AV