Current Schematic ConocoPhillips Well Name: SAN JUAN 28-7 UNIT 186 rface Legal Locatio **NEW MEXICO** 3003920644 013-028N-007W-K Vertical ng Hanger Distance (ff) Ground Elevation (KB-Ground Distance (ft B-Casing Flange Distance (ft B-Tubi 6,677.00 6,690.00 13.00 13.00 13.00 Vertical - Original Hole, 8/18/2015 12:16:08 PM Formation MD (ftKB) Tops Vertical schematic (actual) 13.1 1; Surface; 9 5/8 in; 9.000 in; 13.0 ftKB; 228.0 229.0 ftKB Cement; 13.0-229.0; 6/23/1973; Cemented 229.0 with 190 sxs of Class A, 1.18 yield. Circulated 13 bbls of cement to surface 2,725.1 3 259 8 3,711.0 2; Intermediate1; 7 in; 6.460 in; 13.0 ftKB; 3,713.0 ftKB Cement; 2,725.0-3,713.0; 7/2/1973; Cemented with 155 sxs of class C, 1.98 Tubing Joints; 2 3/8 in; 4.70 lb/ft; J-55; 3.712.9 TRANSFERRED ON MT # 73191 R. average yield. TOC at 2725' as determined 9/24/99.; 13.0 ftKB; 7,728.5 ftKB by temperature survey. MESAV... POINT L .. 5,607.9 6,625.0 GALLUP 7,571.8 GREEN... GRANE... 7,628.0 7 959 9 7,680.1 7,728.3 Seating Nipple; 2 3/8 in; 4.70 lb/ft; J-55; 7,728.5 ftKB; 7,729.5 ftKB 7,729.7 Mule Shoe Collar; 2 3/8 in; 4.70 lb/ft; J-55 7,729.5 ftKB; 7,730.0 ftKB 7,730.0 Dakota; 7,670.0-7,863.0; 9/24/1999 Hydraulic Fracture: 8/4/1973; Frac'd with 7,784.1 DAKOTA 64,000# 40/60 sand and 1,582 bbls of Dakota; 7,680.0-7,917.0; 8/4/1973 7,882.9 7,917.0 Auto cement plug; 7,928.0-7,937.0; 7/8/1973; Automatically created cement plug from the casing cement because it had 7.928.1 a tagged depth. 3; Production1; 4 1/2 in; 4.000 in; 13.0 ftKB; 7,936.0 7,937.0 ftKB Cement; 3,260.0-7,937.0; 7/8/1973; Cemented with 260 sxs of 2.09 yield, and 7,937.0 100 sxs of 1.18 yield, 360 sxs total. TOC at 3260' as determined by temperature survey Report Printed: 8/18/2015 Page 1/1