Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137 Expires March 31, 2007

SUNDRY	NOTICES	AND REI	PORTS	ON WE	115
SUNDE	RUILCES	ANU IZE	TONIS.	OIA AAC	·LLG

Do not use this form for proposals to drill or to re-enter an

5. Lease Serial No. SF-078899A

abandoned well. Use Form 3160-3 (APD) for such proposals.			6. If Indian, Allottee of Tribe Name		
abana	oned well. Ode i omi oro	0-0 (Al D) for such propos	2015 S	FP 13 PM 1 19	
SUBMIT	7. If Unit or CA/Agreement, Name and/or No.				
1. Type of Well Oil Well Gas Well Other O76			RECEIVED		
				Bridle Com No. 1	
2. Name of Operator Merrion Oil & Gas Co	rporation			9. API Well No.	
3a. Address 610 Reilly Avenue, Farmington, NM 87401		3b. Phone No. (include area code) 505.324.5300		30-045-32146	
				10. Field and Pool, or Exploratory Area	
4b. Location of Well (Footage, Sec. T., R.,	M., or Survey Description)			Basin Fruitland	
1115' fnl & 900' fel	11. County or Parish, State				
Sec 20, T26N, R11W				San Juan	
12. Сн	ECK APPROPRIATE BOX(I	es) to indicate natur	E OF NOTICE, REPO	RT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
X Notice of Intent	Acidize	Deepen	Production (Stat	rt/Resume)	
	Alter Casing	Fracture Treat	Well Integrity		
Subsequent Report	Casing Repair	New Construction	Recomplete	Other	
	X Change Plans	Plug & Abandon	Temporarily Ab	andon	
Final Abandonment Report	Convert to Injection	Plug Back	☐ Water Disposal		

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Merrion Oil and Gas proposes to use a double ram BOP instead of a bag type BOP as originally proposed in the APD for the subject well. A schematic is attached.



SEE ATTACHED FOR CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)							
Connie S. Dinning	Title Production Engineer						
Signature Signature	Date August 29, 2005						
THIS SPACE FOR FEDERAL OR STATE OFFICE USE							
Approved by Orlean Brumling	Title Pet, Eng Date 9/14/05						
Conditions of approval, if any, are attached. Approval of this notice to not warrant or certify t applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	hat the Office						

Title 18 USC Section 1001 and Title 43 USC Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. MMOCD



Weatherford

Drilling & Intervention Services

Date:

8-Sep-05

Customer:

Well Information:




Weatherfort[®]

Drilling & Intervention Services

HEIGHT


Double BOP 7 1/16" 3M Studded Shaffer LWP w/ 3 1/2" and Blind Rams.



22"

Total Height

22"



Manifold consisting of Following: 4-Gate Valves, 2" 5M 2-Adjustable Choke, 2" 5M 1- Cross 2" 5M 4 way 1- Tee 2" 5M

4-Flange Comp. 2" 5M w/2" LP thrd

DRILLING CONDITIONS OF APPROVAL

Operator: M

Merrion Oil & Gas Corporation

Lease No.: Well Name: NMSF 078899A Bridle Com #1

Well Location:

sec. 20, T26N, R11W; 1115' FNL & 900' FEL

- 1. The following are required by Onshore Order No. 2: Minimum Standards for Well Control Equipment 2M system:
 - Kill line (2" minimum)
 - Kill line valve (2" minimum)
 - Upper Kelly cock valve with handle available
 - Safety valve and subs to fit all drill strings in use
 - Fill-up line above the uppermost preventor
- 2. Since no BOPE test pressures were proposed, please test the BOP and related equipment according to Onshore Order No. 2 Minimum Standards and Enforcement Provisions For Well Control Equipment Testing.