

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED
OMB No. 1004-0137
Expires March 31, 2007

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMSF-080382
1b. Type of Well: <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name N/A
2. Name of Operator XTO ENERGY INC		7. If Unit or CA Agreement, Name and No. N/A
3a. Address 2700 FARMINGTON AVE., BLDG. K-1 FARMINGTON, NM 87401	3b. Phone No. (include area code) (505) 324-1090	8. Lease Name and Well No. FRONTIER AZTEC B 1 E
4. Location of Well (Report location clearly and in accordance with any State requirements.) At surface 810 FNL & 1540 FWL At proposed prod. zone SAME		9. API Well No. 30-045- 32810
14. Distance in miles and direction from nearest town or post office* 12 AIR MILES SOUTHWEST OF BLOOMFIELD		10. Field and Pool, or Exploratory BASIN DAKOTA
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 810'	16. No. of acres in lease 480	11. Sec., T. R. M. or Blk. and Survey or Area C 28-27N-11W NMPM
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 391' (XTO's 28-2)	19. Proposed Depth 6,950'	12. County or Parish SAN JUAN
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 6,276' GL	22. Approximate date work will start* 07/01/2005	13. State NM
20. BLM/BIA Bond No. on file BLM NATIONWIDE 57 91 73		
23. Estimated duration 6 WEEKS		

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, shall be attached to this form:

- | | |
|---|--|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the authorized officer. |


25. Signature <i>Brian Wood</i>	Name (Printed/Typed) BRIAN WOOD	Date 12/24/2004
Title CONSULTANT		
PHONE: (505) 466-8120 FAX: (505) 466-9682		

Approved by (Signature) <i>John Field Manager</i>	Name (Printed/Typed) John Field Manager	Date 12/7/05
Title Office		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on page 2)



NMOCD

DRILLING OPERATIONS AUTHORIZED ARE
SUBJECT TO COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS".

DISTRICT I
1625 N. French Dr., Hobbs, N.M. 88240

DISTRICT II
1301 W. Grand Ave., Artesia, N.M. 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, N.M. 87410

DISTRICT IV
1220 South St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised June 10, 2003
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

2005 JAN 5 PM 1 ☒ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

*API Number 30-045-32810		*Pool Code 71599	*Pool Name BASIN DAKOTA
*Property Code 35302	*Property Name FRONTIER AZTEC B.		*Well Number 1E
*OGRID No. 167067	*Operator Name XTO ENERGY INC.		*Elevation 6276


10 Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
C	28	27-N	11-W		810	NORTH	1540	WEST	SAN JUAN

11 Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
*Dedicated Acres 320			*Joint or Infill		*Consolidation Code C		*Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



17 OPERATOR CERTIFICATION

I hereby certify that the information contained herein
is true and complete to the best of my knowledge and
belief

Brian Wood
Signature
BRIAN WOOD
Printed Name
CONSULTANT
Title
DEC. 24, 2004
Date

18 SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat
was plotted from field notes of actual surveys made by
me or under my supervision, and that the same is true
and correct to the best of my belief.

Date of Survey
Signature
JOHNA VUKONICH
Professional Surveyor
14831
Certificate Number


XTO ENERGY INC.

FRONTIER AZTEC B No. 1E, 810' FNL 1540' FWL

SECTION 28, T27N, R11W, N.M.P.M., SAN JUAN COUNTY, N. M.

GROUND ELEVATION: 6276', DATE: APRIL 7, 2004




LAT. = 36°33'04" N.
LONG. = 108°00'44" W
NAD 1927



RESERVE PIT DIKE: TO BE 8' ABOVE DEEP SIDE (OVERFLOW - 3' WIDE AND 1' ABOVE SHALLOW SIDE).

BLOW PIT: OVERFLOW PIPE HALFWAY BETWEEN TOP AND BOTTOM AND TO EXTEND OVER PLASTIC LINER AND INTO BLOW PIT.

NOTE: DAGGETT ENTERPRISES, INC. IS NOT LIABLE FOR UNDERGROUND UTILITIES OR PIPELINES. NEW MEXICO ONE CALL TO BE NOTIFIED 48 HOURS PRIOR TO EXCAVATION OR CONSTRUCTION.



NOTE: CONTRACTOR SHOULD CALL ONE-CALL FOR LOCATION OF ANY MARKED OR UNMARKED BURIED PIPELINES OR CABLES ON WELL PAD AND OR ACCESS ROAD AT LEAST TWO (2) WORKING DAYS PRIOR TO CONSTRUCTION.

REVISION	CORRECT LATITUDE	DATE	8/02/04	REVISION BY	B.L.
<p>Daggett Enterprises, Inc. Surveying and Oil Field Services P. O. Box 15068 • Farmington, NM 87401 Phone (505) 326-1772 • Fax (505) 326-6019 NEW MEXICO P.L.S. No. 14831</p>					
<p>DATE 04/12/04</p>				<p>DATE 04/12/04</p>	

XTO Energy Inc.
Frontier Aztec B 1 E
810' FNL & 1540' FWL
Sec. 28, T. 27 N., R. 11 W.
San Juan County, New Mexico

PAGE 1

Drilling Program

1. ESTIMATED FORMATION TOPS

<u>Formation Name</u>	<u>GL Depth</u>	<u>KB Depth</u>	<u>Elevation</u>
Nacimiento Fm	000'	12'	+6,276'
Ojo Alamo Sandstone	776'	788'	+5,500'
Kirtland Shale	876'	888'	+5,400'
Fruitland Coal	1,576'	1,588'	+4,700'
Pictured Cliffs Ss	1,826'	1,838'	+4,450'
Chacra Sandstone	2,676'	2,688'	+3,600'
Pt. Lookout Sandstone	4,176'	4,188'	+2,100'
Mancos Shale	4,576'	4,588'	+1,700'
Gallup Sandstone	5,401'	5,413'	+875'
Huerfano	5,776'	5,788'	+500'
Greenhorn Limestone	6,276'	6,288'	0'
Graneros Shale	6,336'	6,348'	-60'
Dakota Sandstone	6,436'	6,448'	-160'
Morrison	6,776'	6,788'	-500'
Total Depth (TD)*	6,950'	6,962'	-674'

2. NOTABLE ZONES

Gas & Oil Zones

Fruitland
Pictured Cliffs
Point Lookout
Gallup
Dakota

Water Zones

Nacimiento
Ojo Alamo
Fruitland

Coal Zones

Fruitland

XTO Energy Inc.
Frontier Aztec B 1 E
810' FNL & 1540' FWL
Sec. 28, T. 27 N., R. 11 W.
San Juan County, New Mexico

PAGE 2

Water zones will be protected with casing, cement, and weighted mud. Fresh water found while drilling will be recorded. Oil or gas shows will be tested for commercial potential based on the geologist's recommendations.

3. PRESSURE CONTROL

The drilling contract has not yet been awarded, thus the exact BOP model to be used is not yet known. (A typical 2,000 psi model is on PAGE 3.) An 8-5/8" x 11" 2,000 pound double ram BOP system with a choke manifold and mud cross will be tested to 200 psi and then to 1,000 psi. Upper and lower Kelly cocks with valve handle and subs to fit all drill string connections which are in use will be available on the rig floor.

Tests will be run when:

- 1) installed
- 2) anytime a pressure seal is broken (test only affected equipment)
- 3) at least every 30 days
- 4) blind & pipe rams will be activated each trip, but no more than daily

BOP systems will be consistent with API RP 53. Blowout preventers will be installed and tested before drilling surface casing plug and will remain in use until the well is completed or abandoned. Preventers will be inspected and operated daily to ensure good mechanical working order and this inspection recorded on the daily drilling report. Preventers and casing will be pressure tested before drilling casing cement plugs. Maximum expected bottom hole pressure is \approx 2,800 psi. BOP and mud system will control pressure.


4. CASING & CEMENT

<u>Hole Size</u>	<u>O. D.</u>	<u>Weight (lb/ft)</u>	<u>Grade</u>	<u>Age</u>	<u>Connections</u>	<u>Setting Depth</u>
12-1/4"	8-5/8"	24	J-55	New	8 rd, S T & C	325'
7-7/8"	5-1/2"	15.5	K-55	New	8 rd, L T & C	6,950'

Pressure Control Equipment

Note: 1. An upper Kelly cock valve will be utilized during drilling. Handle will be available for easy access.

2. Safety valves and necessary subs to fit all drill string in use will be available.



Minimum 2" Choke Line.
Minimum 2" Kill Line.
At Least One 2" Minimum Kill Line Valve.

Note: This equipment is designed to meet requirements for a 2-M rating standard per 43 CFR part 3160 (amended). Proper operation and testing of equipment will be carried out per standard. 2,000 psi equipment can be substituted in the drawing to meet minimum requirements per standard.

XTO Energy Inc.
Frontier Aztec B 1 E
810' FNL & 1540' FWL
Sec. 28, T. 27 N., R. 11 W.
San Juan County, New Mexico

PAGE 4

Surface casing will be cemented to surface with ≈ 270 cubic feet (≈ 230 sacks) Class B Neat + 1/4 pound per sack cello-flake + 2% CaCl_2 . Yield = 1.27 cubic feet per sack. Weight = 15.2 pounds per gallon.

Conventional centralizers will be set on the bottom two joints and every fourth joint to surface.

Production casing hole will be cemented to surface as follows. DV @ $\approx 4,000'$.

First stage Lead will be cemented to $\approx 4,000'$ with ≈ 640 cubic feet (≈ 464 sacks) 50:50 Poz + 5 pounds per sack gilsonite + 2% gel + 1/4 pounds per sack cello-flake, dispersant, and FLA. Yield = 1.38 cubic feet per sack. Weight = 13.5 pounds per gallon. Excess = 25%.

Second stage Lead will be cemented to surface with $\approx 1,095$ cubic feet (≈ 380 sacks) Class B or H + 10 pounds per sack gilsonite + 4% gel + 1/2 pounds per sack cello-flake + 3% Econolite. Yield = 2.88 cubic feet per sack. Weight = 11.4 pounds per gallon. Excess = 50%

Second stage Tail will be cemented to $\approx 3,600'$ with ≈ 95 cubic feet (≈ 76 sacks) Class B or H Neat + 1/4 pounds per sack cello-flake + 2% CaCl_2 . Yield = 1.26 cubic feet per sack. Weight = 15.2 pounds per gallon. Excess = 10%.

Conventional centralizers will be set on the bottom two joints, every second joint to $\approx 6,000'$ and every fourth joint from $\approx 2,000'$ to surface.

5. MUD PROGRAM

<u>RANGE</u>	<u>MUD TYPE</u>	<u>WEIGHT</u>	<u>VISCOSITY</u>	<u>WATER LOSS</u>	<u>ADDITIVES</u>
0' - 350'	Fresh-Spud	8.5-8.8	30	NC	Gel, lime
350' - 4,000'	Fresh Water	8.5-8.8	28	NC	Gel, lime sweeps
4,000' - TD	Fresh Water	8.5-8.8	35	10 cc	Gel, soda ash, LCM

XTO Energy Inc.
Frontier Aztec B 1 E
810' FNL & 1540' FWL
Sec. 28, T. 27 N., R. 11 W.
San Juan County, New Mexico

PAGE 5

6. CORING, TESTING, & LOGGING

No cores or drill stem tests are planned. Induction logs will be run from TD to $\approx 3,000'$. Neutron density - GR logs will be run from TD to base of surface casing.

7. DOWN HOLE CONDITIONS

No abnormal pressures, temperatures, nor hydrogen sulfide are expected. Maximum bottom hole pressure will be $\approx 2,780$ psi.

8. OTHER INFORMATION

The anticipated spud date is upon approval. It is expected it will take about four weeks to drill and two weeks to complete the well.