Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31,1993

5. Lease Designation and Serial No. NOG-05020-1715

6. If Indian, Alfotted or Tribe Name

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

SUNDRY NOTICES AND REPORTS ON WELLS

Use "APPLICATION FOR PERMIT -" for such proposals SUBMIT IN TRIPLICATE Navajo Allotted 1. Type of Well 7. If Unit or CA, Agreement Designation Oil Gas Well 8. Well Name and No. 2. Name of Operator Dugan Production Corp. Big Yazzie #1 3. Address and Telephone No. 9. API Well No. (505) 325 - 1821 P.O. Box 420, Farmington, NM 87499 30 045 33149 Location of Well (Footage, Sec., T., R., M., or Survey Description) 10. Field and Pool, or Exploratory Area 660' FNL & 1980' FEL (NW/4 NE/4) Bisti Gallup South Unit B, Sec. 6, T23N, R9W, NMPM 11. County or Parish, State San Juan, NM 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment \square Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Altering Casing Conversion to Injection Final Abandonment Notice Other Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Change of plans in approved APD: 41/2" casing production hale 1st stage: 400 cu ft Premium Lite High Strength FM: 12.3 ppg slurry wt; 2.18 cu ft/sx yield; 11.55 mix H20/gals/sx. 183 SK 2nd stage: 1350 cu ft Premium Lite FM: 12 ppg ppg slurry wt.; 2.26 cu ft/sx yield; 12.46 mix H20 gals/sx. 70 cu ft Type III: 14.6 ppg slurry wt.; 1.37 cu ft/sx yield; 6.64 mix H20 gals/sx. lead: 597 sk; tail: 51 sk Hole size change: 11" to 121/4" & 7" to 7-7/8" - Adjust surface hole cement volume to ensure circulation to surface as required. 14. I hereby certify that the foregoing Vice-President 11/14/2005 Date 117/05 Conditions of approval, if any