This form is not to be

NEW MEXICO OIL CONSERVATION DIVISION

used for reporting	
packer leakage tests in Southeast New Mexico	NORTH

packer leakage t in Southeast Nev	ests	NORTHWEST	NEW MEXICO I	ACKER I	EAKAGE T	EST	Revised June 10, 2003	
hn	bp America Production Company 200 Energy Court, Farmington, NM 87401 Lease Name Bouack						Well	
Operator _ZU	J Energy Lour	. Farmington,	NM 0/4U1	_ Lease Iva	me DOCH	<u> </u>	No. 100	
Location Of W	Vell: Unit Letter_	Sec2	9 Twp <u>28</u>	<u>N</u> Rge	<u> </u>	30-0 45	-24989	
	Name of Res	ervoir or Pool	Type of Prod.		Method of Prod.		Prod. Medium	
77			(Oil or Gas)		(Flow or Art. Lift)		(Tbg. Or Csg.)	
Upper Completion	BIAN	io mv	GAS		FLOW		TBG	
Lower								
Completion	BASIN	J DR	GAS		FLOW		TRG	
		Pr	e-Flow Shut-In P	ressure Da	ta			
Upper	Hour, Date, Shut		Length of Time				Stabilized? (Yes or No)	
Completion Lower	Hour, Date, Shut		72 HOURS Length of Time		SI Press. Psig		YES Stabilized? (Yes or No)	
Completion	11/29		72 HOURS		37 2		YES YES	
	·		Flow Test N	io 1				
Commenced	at (hour, date)*				g (Upper or Lo	ower):		
Time (Hour, Date)	Lapsed Time Since*		ssure DIC Lower Compl.	Prod. Ze				
11 Fa 129	DAY 1	149	368	1000 j	S J BOTH	ZONES S	HUT IN	
Hat 130	DAY 2	185	3 64		1		HUT IN A COMPANY	
12/1	DAY 3	194	372		BOTH ZONES SHUT IN			
1212	DAY 4	202	278		FLOW	Lower	ZONE	
12/3	DAY 5	208	166		FLOW	n	ZONE	
12/4	DAY 6	a13	157		FLOW	"	ZONE	
Production rate	e during test							
Oil:	BOPD based onBbls. In		s. In	Hrs Grav			GOR	
Gas:	MCFP	D; Test thru (Orif	ice or Meter):					
Mid-Test Shut-In Pressure Data								
Upper	Hour, Date, Shut		Length of Time Shut-In		SI Press. Psig		Stabilized? (Yes or No)	
Completion		2000						
Lower Completion	Hour, Date, Shut	-m	Dength of Time Shut-In		SI Press. Psig		Stabilized? (Yes or No)	
	Ė	DEC 2005	(Cominue on reve	erse side)			·····	

Flow Test No. 2

Commenced a	t (hour, date)**			Zone producin	g (Upper or Lower	:):			
Time	Lapsed Time Since**		ssure Lower Comm	Prod. Zo	one Remarks				
(Hour, Date)	Since	Upper Compl.	Lower Comp	l. Temp					
					·				
						-			
Production rate	during test								
Oil:	BOPD based	d on	Bbls. In	Hrs	Grav	GOR			
Gas: Remarks:	MCFP	D; Test thru (Orif	ice or Meter):						
I hereby certify	that the informat	ion herein contain	ned is true and	complete to the	best of my knowled	dge.			
	il Conservation I	evo	20	Operato	r <u>bp America P</u>	roduction Company			
110W MICKIEG O	ii Comsoi vation L		21 2005	Ву	Sheri Bradsh	aw 83			
By				Title	Field Tech				
Title BAS PASTECTUR, DIST. (2)			E-mail A	E-mail Address					
				Date	12/20/0	a.c.			

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).